TAG:	


# Double Pantry Faucet


### **Architect/Engineering Specifications:**

8" wall mount mixing faucet with polished chrome plated brass body, 6" cast swing spout with 2.2 GPM aerator, compression cartridges, lever handles and 1/2" NPT female inlets. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9 and NSF 372. Meets ADA ANSI/ICC A117.1 requirements.

Job Name			
Model Specified	Quantity		
Variations Specified			
Date			







#### Features & Benefits:

- 8" wall mount mixing faucet with polished chrome plated brass body
- 6" cast spout
- · Lock washer provided for rigid application
- 2.2 GPM aerator, Series 2 (B-0199-02)
- Quarter-turn Eterna compression cartridges w/ spring checks to prevent cross flow of water
- Lever handles w/ color coded indexes
- 1/2" NPT female eccentric inlets w/ Ø 2" flanges
- Adjustable centers from 7 3/4" to 8 1/4"
- Material: Polished chrome plated brass body & cast spout and chrome plated metal handles

## **Product Compliance:**

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)

Warranty: One Year (Limited)



#### **Performance Data:**

Pressure: 20 - 125 psiTemperature: 40 °F - 140 °F

• Flow Rate: 2.2 GPM @ 60 psi



## Optional Outlets (Series 2 / VR Series 7)

GPM	Aerated	Non-Aerated (Laminar)	VR Aerated	VR Non-Aerated (VR Laminar)	<ul><li>□ 4" Wrist Action</li><li>□ Lever (Standard)</li><li>□ 4-Arm</li></ul>
0.35	N/A	□ B-0199-02-N035		□ B-0199-07-N035	Optional Cartridges With Checks
0.5	N/A	□ B-0199-02-N05	N/A	□ B-0199-07-N05	optional cartilages with oncoke
1.0	□ B-0199-02-F10	) N/A	□ B-0199-07-F10	N/A	□ Quarter-Turn Cerama w/ Check Valve
1.2	□ B-0199-02-F12	2 N/A	□ B-0199-07-F12	N/A	□ Quarter-Turn Eterna w/ Spring Check (Standard)
1.5	□ B-0199-02-WS	S N/A	□ B-0199-07-WS	N/A	
2.2	Standard	N/A	□ B-0199-07	N/A	







T&S BRASS AND BRONZE WORKS, INC.



**Optional Handles**