


Incandescent

Coventry

Outdoor

| 1 -87 |
|-------|
| |
| |
| |

| | Finish | | | | | | |
|-------------|----------|--------|------------|----------------------------|--------|--------|----|
| | Textured | Field- | | Dimensions (Inches) | | | |
| Catalog No. | Black | stone | Lamping | Α | В | С | D |
| P5828 | -31 | -87 | 1 (m) 100w | 8 | 17-1/4 | 10 | 10 |
| P5829 | -31 | -87 | 2 (c) 60w | 9-3/4 | 20-1/2 | 12-1/2 | 12 |



Specifications:

General

- Cast aluminum roof
- Hammered optic glass
 P5828: 7-1/8" ht., 5-29/32" dia.
 P5829: 8-31/32" ht., 7-7/16" dia.
- Double arm attachment for stability
- Hand painted finishes
- Cast aluminum construction
- Matching chain hung and post top units available

Mounting

- Wall mounted
- Back plate covers a standard 4" hexagonal recessed outlet box
- Mounting hardware furnished

Electrical

- Prewired
- Candelabra based sockets on P5829 with matching candle covers
- Medium based ceramic socket on P5828 with nickel plated brass screw shell

Labeling

• UL-CUL wet location listed

Progress Lighting 701 Millennium Blvd. Greenville, South Carolina 29607