

For Residential and Commercial Applications

Job Name		Engineer / Architect	
Job Location		Wholesaler	
Submittal Date		Contractor	

B1-**DW Speedi Plumb® PLUS Braided Dishwasher Connector - Compression Inlet

Use: For use in potable water distribution systems in accessible locations only

Design Features:

- **Superior corrosion resistance** to harsh chemicals found in common household cleaning and plumbing repair products
- **More flexible than stainless steel**, the braided polymer-coated fibers bend freely without kinking or crimping
- **Tough inner core** is reinforced to resist chlorine and chloramine leaching and deterioration
- **Nitrile rubber washers** provide a large pliable sealing surface and ensures a long lasting water tight connection
- **8-sided pneumatic crimp** provides greater dependability for realible nut-to-hose connections
- **100% Compliant** to California and Vermont "low-lead" requirements




Operating Specifications:

Temperature: 40°- 140° F, intermittent to 180° F

Pressure: 125 psi maximum

Tubing Diameter: 0.300" I.D. (0.550" O.D.)

MATERIAL SPECIFICATIONS	
Inner Hose	Reinforced PVC
Braiding	PVC coated polyester yarn
Barb	Compliant brass
Ferrule	Zinc plated 1008 steel
Nut	C36000 brass
Washer	Nitrile rubber
Compression Ring & Nut	C36000 brass



Part Listing:

- | | | |
|--------------------------|-----------|--|
| <input type="checkbox"/> | B1-12DW F | 3/8" Compression x 3/8" Compression x 12" Length |
| <input type="checkbox"/> | B1-16DW F | 3/8" Compression x 3/8" Compression x 16" Length |
| <input type="checkbox"/> | B1-20DW F | 3/8" Compression x 3/8" Compression x 20" Length |
| <input type="checkbox"/> | B1-36DW F | 3/8" Compression x 3/8" Compression x 36" Length |
| <input type="checkbox"/> | B1-48DW F | 3/8" Compression x 3/8" Compression x 48" Length |


This specification and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This specification must be returned to BrassCraft if requested.

BrassCraft®

B1-**DW Speedi Plumb® PLUS Braided Dishwasher Connectors - Compression Inlet

Part Listing (con't):

<input type="checkbox"/>	B1-48DW6 D	3/8" Compression x 3/8" Compression w/ 3/8" M.I.P. Elbow x 48" Length, carded
<input type="checkbox"/>	B1-48DW6U D	Universal Connector - 3/8" Compression x 3/8" Compression x 48" Length with 3/8" M.I.P. elbow, 1/2" Compression & 1/2" F.I.P. adapters, carded
<input type="checkbox"/>	B1-60DW F	3/8" Compression x 3/8" Compression x 60" Length
<input type="checkbox"/>	B1-60DW B	3/8" Compression x 3/8" Compression x 60" Length, bulk
<input type="checkbox"/>	B1-60DW6 D	3/8" Compression x 3/8" Compression w/ 3/8" M.I.P. Elbow x 60" Length, carded
<input type="checkbox"/>	B1-72DW F	3/8" Compression x 3/8" Compression x 72" Length
<input type="checkbox"/>	B1-72DW6 D	3/8" Compression x 3/8" Compression w/ 3/8" M.I.P. Elbow x 72" Length, carded
<input type="checkbox"/>	B1-120DW F	3/8" Compression x 3/8" Compression x 120" Length



PART DIMENSIONS (Inches)	
Model	DIM. A
B1-12DW	12.0 / 13.0
B1-16DW	16.0 / 17.0
B1-20DW	20.0 / 21.0
B1-36DW	36.0 / 37.0

PART DIMENSIONS (Inches)	
Model	DIM. A
B1-48DW	48.0 / 49.0
B1-48DW6	48.0 / 49.0
B1-48DW6U	48.0 / 49.0
B1-60DW	60.0 / 61.0

PART DIMENSIONS (Inches)	
Model	DIM. A
B1-60DW6	60.0 / 61.0
B1-72DW	72.0 / 73.0
B1-72DW6	72.0 / 73.0
B1-120DW	120.0 / 121.0

Listings & Certifications:

- IAPMO listed to ASME A112.18.6-2003 (File # 0452)
- CSA listed to ASME A112.18.6-2003 / CSA B125 (File # 204593)
- CSA approved to AB1953 (Project # 2174785)



This specification and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This specification must be returned to BrassCraft if requested.

BrassCraft®