

**KWIK-SET® THREADED DROP PIPE
FOR SUBMERSIBLE PUMPS**

U.S. PAT NO. 6,666,480

SCH80 (SCH120 Bell) ASTM D1785 20' lengths

Size	O.D.	Min. Wall Thickness	Bell O.D.	Weight (lbs./ft.)	Approx. Max. Setting Depth (ft.)	Max. Pressure Rating (psi)	Max. HP	Ft. Per Fast Pak	Fast Paks Per Truckload	Part Number
1"	1.315	0.179	1.335	0.407	450	320	1.5	2400	40	870385
1 1/4"	1.660	0.191	1.680	0.561	400	260	2.0	2040	36	870392
2"	2.375	0.218	2.400	0.936	300	200	7.5	1060	40	870378

SCH120 ASTM D1785 20' lengths

Size	O.D.	Min. Wall Thickness	Bell O.D.	Weight (lbs./ft.)	Approx. Max. Setting Depth (ft.)	Max. Pressure Rating (psi)	Max. HP	Ft. Per Fast Pak	Fast Paks Per Truckload	Part Number
1"	1.315	0.200	1.335	0.445	500	360	1.5	2400	40	870446
1 1/4"	1.660	0.215	1.680	0.619	450	300	2.0	2040	36	870453
2"	2.375	0.250	2.400	1.054	375	240	7.5	1060	40	870460

PVC DROP PIPE

**COST-EFFECTIVE & FAST
CONNECT 20' JOINTS IN
SECONDS WITHOUT COUPLINGS!
NO CORROSION!**

**Low-profile thread lead-in area
positions joints for
ease of assembly**

**SCH120
belled-end thickness for
added strength and rigidity**

