A<u>MIFAB</u>

Plumbing and Drainage

PISTON OPERATED WATER HAMMER ARRESTOR

Specification: MIFAB[®] CL Series (specify size) piston operated water hammer arrestor with hard drawn seamless "K" copper body, RYTON PPS piston with double o-rings (Parco # 5778-80) and CDA 360 brass M.P.T. connection. Certified to the A.S.S.E. 1010-1996 and ANSI A112.26.1M Standards. Engineered to limit the system surge pressure up to 1,500 P.S.I.G.

CL

Functions: Used in commercial, institutional and residential applications on water supply lines to reduce water hammer caused by the quick opening and closing of valves within the piping system. To be installed as close as possible to quick closing valves. The resulting hydraulic shock waves can lead to broken pipes and affect valves in appliances if not reduced with the use of a water hammer arrestor. An access door is not required to provide access to MIFAB's water hammer arrestors.



MODEL NO.	SIZE TYPE	FIXTURE UNIT CAPACITY	A (LENGTH)	B (DIAMETER)	F M.P.T. CONN.
CL-AA	AA	1	4 3/4"	7/8"	1/2"
CL-A	A	1-11	6"	1 1/8"	1/2"
CL-B	В	12-30	7 1/2"	1 1/8"	3/4"
CL-C	С	31-60	9"	1 3/8"	1"
CL-D	D	61-113	10 1/2"	1 5/8"	1 1/4"
CL-E	E	114-154	11 1/4"	2 1/8"	1 1/2"
CL-F	F	155-330	13"	2 5/8"	2"

Job Name:	Page No:
Section No:	Contractor:
Schedule No:	Purchase Order No:
MIFAB reserves the right to make changes in material and design without formal notice and obligation.	USA: 1-800-465-2736 www.mifab.com CAN: 1-800-387-3880