

All torque arrestors, pump guides, cable guards are third party certified to NSF/ANSI 372.



TA48

HARVARD® Deluxe Torque Arrestor Features:

- Two piece design, molded from PVC or natural rubber.
- PVC torque arrestor is **40% heavier** than competitors to resist long-term casing abrasion.
- Field adjustable to hold pump centered in well.
- Fits all well casings from 4" to 8" I.D.
- Torque Arrestor is securely fastened to 1" or 1 1/4" drop pipe w/ **2 Ideal all stainless steel** clamps included.
- Available bagged or bulk without clamps.



TA6100




SG Series

Spider Style Torque Arrestor Features:

- Spider style molded from natural rubber.
- Installs just above discharge of submersible pump.
- Tabs are easily cut for field alteration.
- 4"-6" casing, 1" center hole.

Natural Rubber Pump Guide Features:

- Installed at the top of the submersible pump discharge.
- Permits the pump to be lowered without damage from abrading against the well casing & ledge while centering the pump in the well.



MG6



WG Series

Cable Guard Features:

- Snap-in and self clamping styles.
- Keeps power cable from abrading against well casing.
- A minimum of three to five should be used; one at the pump, one no further than 15' above the pump, and one between 25' and 30' above the pump.
- Adjustable - use in 4", 5" and 6" wells. Available for 1" or 1 1/4" drop pipe.
- Made of polyethylene and will float.

Part Number	Description	Color	Ctn Qty	
Deluxe PVC Torque Arrestor				
TA48	Bagged, with 2 Ideal all stainless steel clamps	Black	16	
TA48G	Bagged, with 2 Ideal all stainless steel clamps	Green	16	
Deluxe Rubber Torque Arrestor				
TA48R	Bagged with 2 Ideal all stainless steel clamps	Black	16	
Spider Style Rubber Torque Arrestor				
TA6100	6x1	Black	50	
Natural Rubber Pump Guides Fits Casing ID Guide OD Drop Pipe				
SG558-5X1	5-5/8"	5"	1"	Bulk
SG600-55/8X1	6"	5 5/8"	1"	Bulk
SG600-55/8X1 1/4	6"	5 5/8"	1 1/4"	Bulk
SG625-6X1	6 1/4"	6"	1"	Bulk
SG625-6X2	6 1/4"	6"	2"	Bulk
Cable Guard				
MG6	With two cable holes, fits 4"-6" casing		100	
WG100	1" Self-clamping style, fits 4"-6" casing		48	
WG125	1 1/4" Self-clamping style, fits 4"-6" casing		48	