## **ROD ATTACHMENTS**



## Fig. 290: Right Hand Thread Fig. 290L: Left Hand Thread

## **Weldless Eye Nut**

Size Range: 3/8" through  $2^{1}/2$ "

Material: Forged steel

Finish: ☐ Plain or ☐ Galvanized

**Service:** For use on high temperature piping installations.

**Approvals:** Complies with Federal Specification A-A-1192A (Type 17), WW-H-171-E (Type 17), ANSI/MSS SP-69 and MSS SP-58 (Type 17).

## **Features:**

- Supports loads equal to the full limitation of the hanger rod.
- Provides flexible connection when used with straight thread rod.

Ordering: Specify rod size, figure number, name and finish. If other

than standard combination of eye nut number and rod size, specify eye nut number and special rod tapping size.

**Note:** The acceptability of galvanized coatings at temperatures above 450°F is at the discretion of the end user. Larger eye nuts featuring smaller rod sizes are commonly available.




FIG. 290, 290L: LOADS (LBS) • WEIGHTS (LBS) • DIMENSIONS (IN)										
Rod Size A	Max Load		Weight	D	С	D	E	F		Eye Nut
	650° F	750° F	Weight	В		ט	_ E	r	G	Number
3/8	730	572	0.63	1½	13/16	1/2	2	13/8	11/16	1
1/2	1,350	1,057	0.63							
5/8	2,160	1,692	0.62							
3/4	3,230	2,530	0.60							
7/8	4,480	3,508	1.70	2	<b>1</b> <sup>11</sup> ⁄ <sub>16</sub>	3/4	25//8	<b>1</b> <sup>15</sup> ⁄ <sub>16</sub>	1	2
1	5,900	4,620	1.70							
11/4	9,500	7,440	3.60	2½	<b>1</b> <sup>13</sup> ⁄ <sub>16</sub>	1	3¾	23//8	111/4	3
11/2	13,800	10,807	3.50							
1¾	18,600	14,566	16.40	4	4	1½	61/4	4	21/4	4
2	24,600	19,265	15.90							
21/4	32,300	25,295	15.40							
21/2	39,800	31,169	14.90							

PROJECT INFORMATION	APPROVAL STAMP
Project:	☐ Approved
Address:	Approved as noted
Contractor:	☐ Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	