

# Structural Foam Sump Basins

SF15 (17 X 16) - 15 gallon capacity



Ideal for crawl space installation. Shown with SF1850S Cover. Patent pending, non-corrosive, nylon encapsulated inserts. Prevent concrete from pushing through insert and interfering with bolt.

SF15DR (17 X 16) - 15 gallon capacity - (40 holes)



Perforated basin ideally used to remove and prevent standing water in crawl space areas, yards, patios and driveways.



Reduction of standing water will minimize the chances for mold and fungus growth

## SF15 Covers

Part Number	Configuration	Slip & Slip
SF1850B	Blank	N/A
SF1850S	Slotted	N/A
SF1850E	E-Flange	1-1/4", 1-1/2", 2" and 3"

# Structural Foam Sump Basins

**SF20 (18 x 22)**

20 gallon capacity



Shown with  
structural foam  
SF60913 Cover

**SF22A (18 x 24)**

22.5 gallon capacity




Stainless Steel  
bolts and Washers

Jackel's strongest, thickest rim,  
360° EZ GRAB™ handle.

The best basin  
in the industry  
Top to bottom

Shown with  
structural foam  
SF44 Cover

"Skirted" bottom  
allows basin to set  
flat and protects  
inner radius.



Patent pending,  
non-corrosive, nylon  
encapsulated insert.  
Prevents concrete from  
pushing through the insert  
and interfering with bolt.

## Hubs and Adapters



**Universal Combo Hub**  
(patent pending)

Water and vapor tight seal. Fits 3" and 4" DWV SCH.40/80 plastic pipe.

Code approved  
Quick installation  
No tools required  
Solvent weld



**Snap-In-Hub**

Water and vapor tight seal with  
no caulking.  
Fits 4" DWV SCH.40/80 plastic pipe

Quick installation  
Built-in "O" rings  
Water tight  
Stainless steel clamp



**E-Series Inlet or  
Discharge Hub**

Water and vapor tight seal with  
no caulking.  
Fits DWV SCH.40/80 plastic pipe.  
Quick installation.  
Available in 1", 1 1/4", 1 1/2", 2",  
3" and 4" diameter.



**Plastic Pipe Adapters**

Fits 2", 3" and 4" DWV SCH.40/80  
plastic pipe.  
Quick installation  
Water tight



**Cast Iron Hub**

4-bolt configuration.  
Fits 4" DWV SCH.40/80 plastic pipe.  
Water tight seal  
Must be caulked or gasketed