



EZ-MAX® REPAIR CLAMP

(1.5"-24")

HYMAX®
Repair the past. Connect the future.

PRODUCT SPECIFICATIONS

FEATURES

- STAINLESS STEEL, MONOBLOCK DESIGN
- STRONG AND ANTI-CORROSION RESISTANT
- LIGHTWEIGHT, EASY TO INSTALL
- SUITABLE FOR ALL PIPE TYPES
- DURABLE EPDM GASKET

SPECIFICATIONS

STANDARDS

EZ-MAX MEETS THE NEW AWWA STANDARD C230, NSF-372, NSF-61.

SIZE/LENGTH

AVAILABLE IN NOMINAL DIAMETER FROM 1.5"-24":

6" LENGTH - 1.5"-12" DIAMETER.

9" LENGTH - 1.5"-12" DIAMETER.

12" LENGTH - 1.5"-24" DIAMETER.

15" LENGTH - 4"-24" DIAMETER.

24" LENGTH - 4"-24" DIAMETER.

MATERIALS

BODY

AISI 304 STAINLESS STEEL.

GASKET

EPDM COMPOUNDED FOR WATER AND SEWERAGE.
MEETS INTERNATIONAL STANDARDS FOR CONTACT WITH DRINKING WATER.

GASKET BRIDGE

AISI 304 STAINLESS STEEL.

COMPRESSION BEAM AND ADJUSTING PIN

PRECISION CASTING STAINLESS STEEL 304/304L OF ASTM-A351-CF8.

LUGS

POLYCARBONATE.

NUTS AND BOLTS

AISI 304 STAINLESS STEEL. ROLLED THREAD AND ANTI-GALLING COATING.

PRODUCT PERFORMANCE (*)

WORKING TEMPERATURE

-20°F UP TO +180°F

WORKING PRESSURE

150 PSI

RATED PRESSURE

225 PSI

PRODUCT TABLES

EZ-MAX NOMINAL SIZE 3"-12" / 9" LENGTH

Krausz Part Number	Nominal Diameter (inch)	Range (inch)	Bolts Qty. and Size (mm)	Torque (Ft-Lbs)	Working Pressure (PSI)	Rated Pressure (PSI)	Approx. Weight (Lbs)
222-56-0087-10W	3"	3.42-4.25	3 -M14	40	150	225	9.35
222-56-0113-10W	4"	4.47-5.27	3 -M14	50	150	225	9.87
222-56-0122-10W		4.80-5.60	3 -M14	50	150	225	10.12
222-56-0139-10W	6"	5.50-6.30	3 -M14	60	150	225	11.04
222-56-0167-10W		6.60-7.40	3 -M14	60	150	225	11.57
222-56-0174-10W		6.84-7.64	3 -M14	60	150	225	11.81
222-56-0198-10W	8"	7.80-8.60	3 -M14	70	150	225	13.05
222-56-0218-10W		8.60-9.40	3 -M14	70	150	225	13.6
222-56-0228-10W		9.00-9.80	3 -M14	70	150	225	13.86
222-56-0272-10W	10"	10.73-11.53	3 -M14	100	150	225	16.28
222-56-0288-10W		11.35-12.15	3 -M14	100	150	225	16.72
222-56-0323-10W	12"	12.75-13.55	3 -M14	100	150	225	20.24
222-56-0345-10W		13.60-14.40	3 -M14	100	150	225	21.03

EZ-MAX NOMINAL SIZE 3"-12" / 12" LENGTH

Krausz Part Number	Nominal Diameter (inch)	Range (inch)	Bolts Qty. and Size (mm)	Torque (Ft-Lbs)	Working Pressure (PSI)	Rated Pressure (PSI)	Approx. Weight (Lbs)
223-56-0087-10W	3"	3.42-4.25	4 -M14	40	150	225	12.54
223-56-0113-10W	4"	4.47-5.27	4 -M14	50	150	225	13.09
223-56-0122-10W		4.80-5.60	4 -M14	50	150	225	14.3
223-56-0139-10W	6"	5.50-6.30	4 -M14	60	150	225	14.63
223-56-0167-10W		6.60-7.40	4 -M14	60	150	225	15.4
223-56-0174-10W		6.84-7.64	4 -M14	60	150	225	15.77
223-56-0198-10W	8"	7.80-8.60	4 -M14	70	150	225	17.38
223-56-0218-10W		8.60-9.40	4 -M14	70	150	225	17.42
223-56-0228-10W		9.00-9.80	4 -M14	70	150	225	18.48
223-56-0272-10W	10"	10.73-11.53	4 -M14	100	150	225	21.71
223-56-0288-10W		11.35-12.15	4 -M14	100	150	225	22.37
223-56-0323-10W	12"	12.75-13.55	4 -M14	100	150	225	27.06
223-56-0345-10W		13.60-14.40	4 -M14	100	150	225	28.16