

# KICHLER®


## Large Compact Accent



PROJECT:
TYPE:
ORDERING # :
COMMENTS:

## FEATURES

- Adjustable Accent Light in a Larger Size (5" Diameter) For Up or Down Lighting
- Cast Aluminum Housing
- 8" of Usable 200° 18 AWG Wire Leads
- 4000V (4KV) Pulse Rated Medium Base Porcelain Socket
- Max Lamping 100W PAR38 Metal Halide or 100W PAR38 Incandescent (Not Included)
- Remote Ballast Required for HID Lamping
- ANSI / UL Listed Wet Location
- Housing Includes a 1-Year Warranty From Date of Purchase
- HID Ballasts Include a 2-Year Warranty From Date of Purchase



## ORDERING INFORMATION

EXAMPLE: 15250AZT (Product # & Finish)

PRODUCT	FINISH	REMOTE BALLAST SPECS	MOUNTING ACCESSORIES	LENS ACCESSORIES
15250	AZT - Textured Architectural Bronze 	<p><b>Above Ground Ballast</b></p> <p><b>15MHS100AZT</b> - Single 100W MH 120V ANSI M90</p> <ul style="list-style-type: none"> <li>- Stamped Steel w/ Textured Architectural Bronze Thermoset Powder Coat Finish</li> <li>- Copper Wrapped Core &amp; Coil w/ HPF 105° High Heat Capacitor &amp; Long Range Ignitor</li> <li>- Rated For -20° F Starting</li> <li>- 0.5" &amp; 0.75" Trade Size Combination Knockouts For Conduit Entry</li> <li>- Mounting Screws &amp; Anchors Included</li> <li>- UL Listed For US &amp; Canada</li> </ul>  <p><b>In Ground Ballast</b></p> <p><b>15IGMHS100AZ</b> - Single 100W MH 120V ANSI M90</p> <ul style="list-style-type: none"> <li>- Dimensions: 9.625" Diameter x 12" Height</li> <li>- Single Piece Polyphenylene (PPS) Glass Reinforced Composite w/ Molded-in Ribs to Prevent Ground Shift</li> <li>- Quick Disconnect Ballast w/ Bracket Handle</li> <li>- 0.5" NPSM Removable Plug For Direct Fixture Mount &amp; Remote Mount Application</li> <li>- Two Threaded 0.75" NPT Entries For Conduit Attachment</li> <li>- Re-Enterable Encapsulant 3M 8882 Potting Compound Included</li> <li>- One Piece, Molded Silicone O-Ring</li> <li>- Captive &amp; Gasketed</li> <li>- CSA Listed For US &amp; Canada</li> </ul>  <p><b>Please Note:</b> Maximum Distance From Lamp to Ballast Cannot Exceed 15 Feet</p>	<p><b>15276BK</b> - Fast, One-Step Connector</p> <ul style="list-style-type: none"> <li>- Made of Impact / Corrosion Resistant PVC</li> <li>- 2.250" Inside Diameter to Accommodate Conduits of Different Sizes</li> <li>- Accepts .50 NPSM Thread</li> <li>- Designed For 120V Line Voltage Landscape Lighting, Eliminating Need For Above or Below Ground Boxes.</li> <li>- Built-in Stabilizer Removes Need For Concrete</li> </ul>  <p><b>15601AZT</b> - Cast Aluminum Surface Mounting Flange w/ Bronze Finish, Neoprene Gasket For Watertight Seal</p>  <p><b>15601BKT</b> - Cast Aluminum Surface Mounting Flange w/ Black Finish, Neoprene Gasket For Watertight Seal</p> <p><b>15601BBR</b> - Cast Brass Surface Mounting Flange, Neoprene Gasket For Watertight Seal</p> <p><b>15609AZT</b> - Junction Box Mounting Bracket</p> <ul style="list-style-type: none"> <li>- Corrosion Resistant Cast Aluminum Alloy w/ Baked Thermoset Bronze Powder Coat Finish</li> </ul>  <p><b>15609BKT</b> - Junction Box Mounting Bracket</p> <ul style="list-style-type: none"> <li>- Corrosion Resistant Cast Aluminum Alloy w/ Baked Thermoset Black Powder Coat Finish</li> </ul>	<p><b>15650AZT</b> - PAR38 Medium Hood</p> <ul style="list-style-type: none"> <li>- 3.58" in Length</li> <li>- Heat-Resistant Clear lens</li> </ul> 

## NOTES

For Warranty Information, please visit [www.landscapelighting.com](http://www.landscapelighting.com)

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

