

Mueller® Drilling and Tapping Machine equipment required to install corporation valves having copper flare connection outlet

Valve size (nominal) (If two numbers: Inlet x Outlet)	1/2"	1/2"x3/4"	5/8"x3/4"	3/4"	3/4"x1"	1"	1-1/4"	1-1/2"	2"	
Combined drill and tap size - see section 1 for part numbers	1/2"	1/2"	5/8"	3/4"	3/4"	1"	1-1/4"	1-1/2"	2"	
B-101/B-100 inserting tool	680598	680600	680600	680600	680601	680601	-	-	-	
A-3 inserting tool	-	-	-	-	-	680601	680602	88640	88641	
Maximum allowable size drill or shell cutter - see section 2 for part numbers	AWWA I.P.	7/16"	7/16"	9/16"	11/16"	11/16"	7/8"	1-1/8"	1-7/16"	1-3/4"
	CC (AWWA taper)	7/16"	7/16"	9/16"	11/16"	11/16"	15/16"	1-3/16"	1-7/16"	1-15/16"
Mega-Cut™/E-5 machine adapter nipple	63796	52019	52019	52019	36750	36750	682256	501947	508201	
D-5 machine adapter nipple	37900	37902	37902	37902	37903	37903	682259	37905	37906	
Tru-Cut/PL-2 machine adapter nipple for use on 1.125" max. wall PVC	-	-	-	507632	507633	507633	-	-	-	

* Ball and ORI-CORP® Corporation valves IP and CC inlet: 1-7/8" maximum.

I.P. thread copper flare connection optional equipment

I.P. thread copper flare nut

This connection thread is one size larger than the copper tubing to be flared.

CATALOG NUMBER:
H-15432



3/4"	1"
------	----

Solid copper disc

Used with regular copper flare nut to shut off line.

CATALOG NUMBER:
H-15535N



1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
------	------	----	--------	--------	----

Brass cap

Cap off line

H-15540N

Copper flare thread



3/4" *	1" *	1-1/2"	2"
--------	------	--------	----

H-15545N

CTS 110 thread

1-1/2"	2"
--------	----

* 3/4" and 1" CTS 110 has copper flare thread

Flaring Tool

Used to make 45° flare on type "K" copper tubing.

CATALOG NUMBER:
H-18000



1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
------	------	----	--------	--------	----

Drilled Flaring Tool

Used to make 45° flare on type "K" copper tubing without shutting off water—drilled to exhaust water at right angle to tubing.

CATALOG NUMBER:
H-18005



3/4"	1"
------	----

Reamer

Used to ream the inside of type "K" copper tubing to remove burrs prior to flaring.

CATALOG NUMBER:
H-18010



1/2"	3/4"	1"
------	------	----

Brass Hammer

Solid brass head with 10" wooden handle.

Weight 2- 3/4 lb.

CATALOG NUMBER:
H-18025



Compression to Flare Push-in-Bushing

CATALOG NUMBERS:

3/4" - 682332 1" - 682333



Corporation Valve Wrench

For operating up to and including 1" corporation and valves.

CATALOG NUMBER:

H-10048



Note: When using any striking tool, safety eye protection must be worn. Inspect hammer and tools for any damage after each use and repair or replace if mushrooming or chipping evident.