



STANDARD RESPONSE AUTOMATIC SPRINKLERS GL SERIES UPRIGHT • PENDENT VERTICAL SIDEWALL HORIZONTAL SIDEWALL CONVENTIONAL (OLD STYLE)

DESCRIPTION AND OPERATION

The Globe Standard Response Series GL-SR Sprinklers are a low profile yet durable design which utilizes a 5mm frangible glass ampule as the thermosensitive element. While the Standard Response Sprinkler provides an aesthetically pleasing appearance, it can be installed wherever standard spray sprinklers are specified when allowed by the applicable standards. It offers the additional feature of greatly increased safety to life and is available in various styles, orifices, temperature ratings and finishes to meet varying design requirements. Standard Response Sprinklers should be used advisedly and under the direction of approving authorities having jurisdiction.

The heart of Globe's Series GL-SR sprinkler proven actuating assembly is a hermetically sealed frangible glass ampule that contains a precisely measured amount of fluid. When heat is absorbed, the liquid within the bulb expands increasing the internal pressure. At the prescribed temperature the internal pressure within the ampule exceeds the strength of the glass causing the glass to shatter. This results in water discharge which is distributed in an approved pattern depending upon the deflector style used.

The sprinkler and escutcheon are not factory assembled. Assembly is done in the field.



**STANDARD RESPONSE
SERIES GL-SR
UPRIGHT**




**STANDARD RESPONSE
SERIES GL-SR/CNV
CONVENTIONAL**



**STANDARD RESPONSE
SERIES GL-SR
PENDENT**



**STANDARD RESPONSE
SERIES GL-SR/SW
VERTICAL
SIDEWALL**



**STANDARD RESPONSE
SERIES GL-SR/SW
LPCB/CE
HORIZONTAL
SIDEWALL**



**STANDARD RESPONSE
SERIES GL-SR/SW
HORIZONTAL
SIDEWALL**

TECHNICAL DATA

- See reverse side for Approvals and Specifications.
- Temperature Ratings - 135°F (57°C), 155°F (68°C), 175°F (79°C), 200°F (93°C), 286°F (141°C), 360°F (182°C) 500°F (260°C) Available Upon Request Without Approvals
- Water Working Pressure Rating - 175 psi (12 Bars)
- Factory tested hydrostatically to 500 psi (34 Bars)
- Maximum low temperature glass bulb rating is -67°F (-55°C)
- Frame - bronze • Deflector - brass • Screw - brass
- Lodgement Wire - stainless steel • Bulb seat - copper
- Spring - nickel alloy • Seal - teflon
- Bulb - glass with glycerin solution, 5mm size
- Escutcheon Assembly - steel

• SPRINKLER TEMPERATURE RATING/CLASSIFICATION and COLOR CODING

CLASSIFICATION	AVAILABLE SPRINKLER TEMPERATURES		BULB COLOR	N.F.P.A. MAXIMUM CEILING TEMPERATURE	
ORDINARY	135°F/155°F	57°C/68°C	ORANGE/RED	100°F	38°C
INTERMEDIATE	175°F/200°F	79°C/93°C	YELLOW/GREEN	150°F	66°C
HIGH	286°F	141°C	BLUE	225°F	107°C
EXTRA HIGH	360°F	182°C	MAUVE	300°F	149°C
ULTRA HIGH	500°F	260°C	BLACK	475°F	246°C

STANDARD RESPONSE AUTOMATIC SPRINKLERS SERIES GL-SR UPRIGHT • PENDENT • VERTICAL SIDEWALL HORIZONTAL SIDEWALL • CONVENTIONAL (OLD STYLE) SPECIFICATIONS

NOMINAL "K" FACTOR	THREAD SIZE	LENGTH ¹	FINISHES
2.8 (40 metric)	1/2"NPT (15mm)	2 1/4" (5.7cm)	Factory Bronze
4.2 (60 metric)	1/2"NPT (15mm)	2 1/4" (5.7cm)	Chrome
5.6 (80 metric)	1/2"NPT (15mm)	2 1/4" (5.7cm)	White Polyester ³
8.0 (115 metric)	1/2"NPT (15mm)	2 1/4" (5.7cm)	Black Polyester ^{2,3}
8.0 (115 metric)	3/4"NPT (20mm)	2 7/16" (6.2cm)	Wax Coated ^{2,3,4}

NOTE: METRIC CONVERSIONS ARE APPROXIMATE. ³AVAILABLE AS cULus LISTED CORROSION RESISTANT WHEN SPECIFIED ON ORDER.

¹HORIZONTAL SIDEWALL IS 2 9/16".

⁴WAX COATING cULus LISTED FOR 155°F (68°C) AND 200°F (93°C) ONLY; EXCLUDING GL8161, GL8151, GL5675, GL8176

²FINISHES AVAILABLE ON SPECIAL ORDER.

LISTINGS/APPROVALS

STYLE	SIN	K FACTOR	HAZARD ¹	TEMPERATURE						cULus	FM	LPCB ²	CE	NYC - DOB MEA 101-92-E
				135°F (57°C)	155°F (68°C)	175°F (79°C)	200°F (93°C)	**286°F (141°C)	**360°F (182°C)					
UPRIGHT	GL2861	2.8	LH	X	X	X	X	X	X	X	---	---	---	X
	GL4261	4.2	LH	X	X	X	X	X	X	X	---	---	---	X
	GL5661	5.6	ALL	X	X	X	X	X	X	X	X	X	X	X
	GL8161*	8.0* (1/2" NPT)	ALL	X	X	X	X	X	X	X	---	---	---	X
	GL8164	8.0	ALL	X	X	X	X	X	X	X	X	X	X	X
PENDENT	GL2851	2.8	LH	X	X	X	X	X	X	X	---	---	---	X
	GL4251	4.2	LH	X	X	X	X	X	X	X	---	---	---	X
	GL5651	5.6	ALL	X	X	X	X	X	X	X	X	X	X	X
	GL8151*	8.0* (1/2" NPT)	ALL	X	X	X	X	X	X	X	---	---	---	X
	GL8156	8.0	ALL	X	X	X	X	X	X	X	X ³	X	X	X
VERTICAL SIDEWALL [†]	GL5675	5.6	LH	X	X	X	X	X	X	X	X	---	---	---
	GL8176	8.0	LH	X	X	X	X	X	X	X	---	---	---	---
HORIZONTAL SIDEWALL	GL2870§	2.8	LH	X	X	X	X	X	X	X	---	---	---	X
	GL4270§	4.2	LH	X	X	X	X	X	X	X	---	---	---	X
	GL5670§	5.6	LH/OH	X	X	X	X	X	X	X	X	---	---	X
	GL5671¶	5.6	LH/OH	X	X	X	X	X	X	---	---	X	X	---
	GL8171§	8.0	LH/OH	X	X	X	X	X	X	X	---	---	---	---
CONVENTIONAL (OLD STYLE)	GL5668	5.6	LH/OH	X	X	X	X	X	X	---	---	X	X	---
	GL8169	8.0	LH/OH	X	X	X	X	X	X	---	---	---	X	---

¹SPRINKLERS SHALL BE LIMITED AS PER THE REQUIREMENTS OF NFPA13 AND ANY OTHER RELATED DOCUMENTS.

§HORIZONTAL SIDEWALL cULus LISTED FOR DEFLECTOR 4" TO 12" BELOW THE CEILING, FM APPROVED 4" TO 6" BELOW THE CEILING.

¶INSTALL IN ACCORDANCE TO BS5306 AND ANY OTHER RELATED DOCUMENTS.

†PENDENT VERTICAL SIDEWALL cULus LISTED FOR 6' MIN. SPACING.

‡UPRIGHT VERTICAL SIDEWALL cULus LISTED FOR 9' MIN. SPACING.

500°F (260°C) AVAILABLE UPON REQUEST WITH NO APPROVALS.

*1/2"NPT; RETRO-FIT ONLY

²LPCB REF. NO. 147c/04

³BRASS FINISH ONLY WHEN RECESSED

**NO FM APPROVALS FOR RECESSED

§NO FM APPROVALS

OH: ORDINARY HAZARD

LH: LIGHT HAZARD

ALL: ALL HAZARDS

ORDERING INFORMATION SPECIFY

- Quantity • SIN • Style • Orifice
- Thread Size • Temperature • Finish desired
- Quantity - Wrenches/Recessed Wrenches - P/N 325390/325391 (1/2"); P/N 312366/325401 (L.O.)
- Quantity Protective Caps - P/N 327109-CAP (Friction Fit Recessed)



SEPT 2018

GLOBE® PRODUCT WARRANTY

Globe agrees to repair or replace any of its own manufactured products found to be defective in material or workmanship for a period of one year from date of shipment.

For specific details of our warranty please refer to Price List Terms and Conditions of Sale (Our Price List).

4077 AIRPARK DRIVE, STANDISH, MICHIGAN 48658

989-846-4583

FAX 989-846-9231

1-800-248-0278

www.globesprinkler.com

GFS-100b (Formerly A-65)

PRINTED U.S.A.