

4-226

Symmons® **Clear-Flo Shower Heads**

Symmons Clear-Flo 2000 shower head with adjustable spray and standard ball joint connection.

Modifications:

- Suffix M:** Male thread connection (1/2" MIPS)
- Suffix VP:** Vandal resistant
- Suffix 2:** 2.0 gpm (7.6 L/min) flow restrictor
- Suffix 1.5:** 1.5 gpm (5.7 L/min) flow restrictor



**SYMMONS PRODUCTS MEET
ANSI A112.18.1M, EPA '92
AND ALL KNOWN FLOW RATE
REQUIREMENTS.
Shower Heads and Hand Showers
2.5 GPM (9.5 L/min)**

Job/Location

.....
.....

Engineer

.....
.....

Contractor

.....
.....

For ADA compliance (Americans with Disabilities Act) consult ADAAG or your state regulations for proper product choice and mounting locations.

Symmons Industries, Inc. ■ 31 Brooks Drive ■ Braintree, MA 02184
(800) 796-6667, (781) 848-2250 ■ Fax (800) 961-9621, (781) 843-3849
Website: www.symmons.com ■ Email: customerservice@symmons.com

©2003, 2008 Symmons Industries, Inc. Printed in U.S.A. ■ 071008


SYMMONS®
the smart choice™