



Size (in)	L1 (in)	L2 (in)	L3 (in)	D (in)	Pressure (PSIG) 70°F		Approx. Wt (lbs.)
					Operating	Test	
3/4	7	2.925	1.25	0.879	375	562	0.5
1	8	3.675	1.375	1.13	390	585	0.75
1-1/4	8.5	4.175	1.375	1.38	340	510	1
1-1/2	9	4.425	1.5	1.631	320	480	1.25
2	10.5	5.425	1.75	2.131	320	480	2.13

Item	Description	Material	Item	Description	Material
1	Hose Braid	Bronze	3	Braid Band	ASTM B88 Copper
2	Hose	Bronze	4	Female Sweat End	ASTM B88 Copper

FNW™

4120 NE Columbia Blvd
Portland, OR 97211
Phone (503) 287-8383
Fax (503) 281-9677

TITLE/DESCRIPTION: FNW METAL BRAIDED FLEXIBLE CONNECTOR
WITH COPPER TUBE END CONNECTIONS

DATE: 8-8-2005 BY: UNITS: INCHES

SCALE: NONE APP'D: PAGE(S): 1

MODEL: 35S

DWG NO: FNW35S

NOTES:

FILE: 35S.dwg WT: LOC: PORTLAND

PAGE SIZE: 8.5 x 11L REV: 0 R'DATE:

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF FNW VALVE AND IS SUBMITTED TO YOU FOR THE LIMITED PURPOSE OF PROVIDING YOU INFORMATION ON PRODUCTS AND SYSTEMS PURCHASED FROM FNW VALVE. BY RECEIVING THIS DOCUMENT, YOU AGREE NOT TO DISCLOSE SUCH INFORMATION TO OTHERS EXCEPT BY WRITTEN PERMISSION OF FNW VALVE.