



Item	Description	Material
1	Hose Braid	T-304 SS
2	Hose	T-321 SS
3	Braid Band	T-304 SS
4	Flat Faced Flange	CARBON STEEL

Size	L1	L2	D	T	ØN	n	ØB	Pressure (PSIG) 70°F		Approx. Wt (lbs.)
								Operating	Test	
2	9	5.78	2.44	0.625	0.63	4	4.75	450	675	12
2-1/2	9	5.78	2.94	0.625	0.63	4	5.50	390	585	13
3	9	5.78	3.57	0.625	0.63	4	6.00	250	375	14
4	9	5.39	4.57	0.625	0.63	8	7.50	210	315	19
5	11	7.14	5.66	0.75	0.75	8	8.50	210	315	27
6	11	6.74	6.72	0.75	0.75	8	9.50	165	240	32
8	12	7.24	8.72	1	0.75	8	11.75	220	330	50
10	13	7.85	10.88	1	0.88	12	14.25	165	240	76

FNWTM

4120 NE Columbia Blvd
Portland, OR 97211
Phone (503) 287-8383
Fax (503) 281-9677

TITLE/DESCRIPTION: FNW METAL BRAIDED FLEXIBLE CONNECTOR WITH FLAT FACED FLANGE CONNECTIONS

DATE: 8-8-2005 BY: UNITS: INCHES
SCALE: NONE APP'D: PAGE(S): 1

MODEL: 30F
DWG NO: FNW30F

NOTES:

FILE: 30F.dwg WT: LOC: PORTLAND
PAGE SIZE: 8.5 x 11L REV: 0 R'DATE:

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF FNW VALVE AND IS SUBMITTED TO YOU FOR THE LIMITED PURPOSE OF PROVIDING YOU INFORMATION ON PRODUCTS AND SYSTEMS PURCHASED FROM FNW VALVE. BY RECEIVING THIS DOCUMENT, YOU AGREE NOT TO DISCLOSE SUCH INFORMATION TO OTHERS EXCEPT BY WRITTEN PERMISSION OF FNW VALVE.