

Uponor AquaPEX® White, Straight Length

Submittal Information
Revision C: Oct. 7, 2009

Project Information

Job Name:

Location:

Part No. Ordered:

Engineer:

Date Submitted:

Contractor:

Submitted By:

Manufacturer's Representative:


Approved By:

Technical Data

Material: Crosslinked polyethylene
PEX-a Engel Method

Standard Grade
Hydrostatic Ratings (PPI): 200°F (93°C) at 80 psi
180°F (82°C) at 100 psi
73.4°F (23°C) at 160 psi
½" Uponor AquaPEX® tubing only: 120°F (49°C) at 130 psi

Linear Expansion Rate: 1.10"/10°F (12°C)/100'



Product Information and Application Use

Uponor AquaPEX White, straight length tubing, is used primarily in hot and cold potable water distribution systems and AquaSAFE™ Residential Fire Safety systems.

✓	Description	Part Number	A	B	Weight
	½" Uponor AquaPEX White, 20-ft. straight length, 500 ft.	F1930500	0.475"	0.625"	28.0 lbs.
	¾" Uponor AquaPEX White, 20-ft. straight length, 300 ft.	F1930750	0.671"	0.875"	31.0 lbs.
	1" Uponor AquaPEX White, 20-ft. straight length, 200 ft.	F1921000	0.862"	1.125"	35.0 lbs.
	1¼" Uponor AquaPEX White, 20-ft. straight length, 100 ft.	F1921250	1.054"	1.375"	32.0 lbs.
	1½" Uponor AquaPEX White, 20-ft. straight length, 100 ft.	F1921500	1.244"	1.625"	42.0 lbs.
	2" Uponor AquaPEX White, 20-ft. straight length, 100 ft.	F1922000	1.629"	2.125"	68.1 lbs.
	3" Uponor AquaPEX White, 20-ft. straight length, 60 ft.	F1923000	2.400"	3.125"	77.0 lbs.

Installation

Approved fittings are ProPEX® fittings¹ for sizes ¾" through 2" AquaPEX. Use WIPEX™ fittings for 3" AquaPEX. Refer to the AquaPEX Professional Plumbing Installation Handbook or AquaSAFE Fire Safety Installation Guide for additional information.

Standards

CSA B137.5; ASTM F876; ASTM F877; ASTM F1960; ASTM-E84; ASTM-E119/UL 263

Codes

IPC; UPC; NSPC; NPC of Canada

Listings

½", ¾", 1" UL 1821; ULC/ORD - C 199 P; IAPMO; CSA; HUD; WARNOCK HERSEY; NSF; ITS; UL; ICC; PPI; ANSI/NSF 14- and 61-certified; CAN/ULC S102.2; U.S.: ¾" diameter and smaller; Canada: 1" diameter and smaller

Related Applications

PEX-a Plumbing Systems
AquaSAFE Residential Fire Safety Systems

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: (800) 321-4739
Fax: (952) 891-2008
www.uponor-usa.com

Uponor Ltd.
2000 Argentia Rd., Plaza 1, Ste. 200
Mississauga, ON L5N 1W1 CANADA
Phone: (888) 994-7726
Fax: (800) 638-9517
www.uponor.ca

¹ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.