



## T-Cone Combination Cleanout Test Plugs

### SPECIFICATION

Furnish and install reusable combination cleanout test plug, capable of testing up to 50 feet of head pressure. Unit shall be Water-Tite product code checked below as manufactured by IPS Corporation.

### MATERIALS

1 1/2", 2", and 3" uses flexible PVC for the gasket and polypropylene for the threaded plug

4", 6", and 8" uses polyurethane for the gasket and polypropylene for the threaded plug



PRODUCT	MODEL	DESCRIPTION	UNITS/CASE
86375	S 152	Tests 1 1/2" Sch. 40 DWV	10
86385	S 202	Tests 2" Sch 40 DWV & Type "M" Copper Tube	10
86520	CS 202	Flush Mount Recessed Plug, Tests 2" Sch. 40 DWV	10
86390	S 302	Tests 3" Sch. 40 & Copper DWV; 2" Cast Iron Hub	10
86526	CS 302	"Flush Mount Recessed Plug, Tests 3"" Sch. 40 & Copper DWV, Type ""M"" Copper"	50
86455	S 300	Tests 3" Sch. 40 Socket	50
86395	S 401	"Test 4"" Type ""M"" Copper Tube, Cast Iron Closet Bend [SW], VDP Barrel"	10
86400	S 402	"Test 4"" Sch. 40 & Copper DWV, PVC S&D, Cast Iron & VCP Barrel; 3"" Cast Iron Hub"	10
86535	CO 402	"Flush Mount Recessed Plug; Tests 3"" Sch. 40 & Copper DWV, PVC S&D, Cast Iron Barrel"	50
86420	S 601	"Test 6"" Copper DWV, PVC PSM [SDR 35], PVC DR-14, CI & VCP Barrel"	10
86425	S 602	Tests 6" Sch. 40 DWV, PVC DR-18, Cast Iron Barrel [EH]	10
86435	S 802	Tests 8" Sch. 40 DWV, PVC PSM [SDR 35], PVC DR-18, VCP Barrel	20



500 Distribution Parkway, Collierville, TN 38017 • Phone: 800-888-8312 • Fax: 901-853-5008 • [www.ipscorp.com](http://www.ipscorp.com)