NO LEAD Foot Valves - Clayton Mark

- **FOR USE IN WATER WELL SYSTEMS**
- **Third party certified to NSF/ANSI 372.**

CLAYTON MARK®

LOW-LEAD IAPMO R&T

NO LEAD < 0.25% Pb by weighted avg Third Party Certified to NSF / ANSI 372



6340 SERIES No Lead Brass Foot Valves

- 400 PSI rating. (W.O.G.)
- Tapered ABS strainer.
- Corrosion resistant, stainless steel core with exclusive cup shape.
- For cold water applications only.
- Jam proof delrin stem guide.

Part Number	Size	Enters Casing	Ctn Qty
6340-3/4	3/4"	1-1/2"	48
6340-1	1"	2"	35
6340-11/4	1-1/4"	2"	30
6340-11/2	1-1/2"	3"	20
6340-2	2"	3-1/2"	12



5340 SERIES No Lead Brass Foot Valves

- No. 8 perforated stainless steel screen strainer.
- 400 PSI rating.
- Corrosion resistant, stainless steel core with exclusive cup shape.
- For cold water applications only.

Part Number	Size	Enters Casing	Ctn Qty
5340-3/4	3/4"	1 1/4"	48
5340-1	1"	1 1/2"	35
5340-11/4	1 1/4"	2"	24
5340-11/2	1 1/2"	2 1/2"	20
5340-2	2"	3 1/2"	12



5330 Series No Lead Brass Foot Valves

- No 8 perforated stainless steel strainer.
- Heavy hex end.

Part Number	Size	Enters Casing	Ctn Qty
5330-21/2	2-1/2"	5"	1
5330-3	3"	6"	1
5330-4	4"	6"	1

americangranby.com
Ph: 800-776-2266 Fax: 800-729-3299