



Pressure Relief Valves

RV and IRV Series Relief Valve Features:

- Heavy duty bronze, brass, **no lead** brass (CA AB1953 certified) or 304 stainless steel for shallow, deep well and submersible pumps.
- Spring loaded and pre-set under pressure, **NOT ADJUSTABLE**.
- 1/2" or 3/4" (IRV7575) discharge.
- RV Series are made for AGI in an ISO 9001 facility. IRV series imported.

Hamilton Adjustable Safety Relief Valve Features:

- Preset at 75 P.S.I. with concealed adjusting screw to prevent tampering.
- Brass-heavy duty, full-flow design with Buna-N seats.



RV, RV-NL Series


ISO 9001



IRV, IRV-NL Series



IRV SS Series



HRV Series

NOTE: Relief valves on this page are not for use with hot water heaters. Recommended for cold water system installations only.

Preset relief valves are **NOT** intended to be adjusted. Any adjustment to preset relief valves voids warranty.

Part Number	Size	Pressure Setting	Ctn/Case	List Price
Bronze Relief Valves - Made in USA				
RV50	1/2" x 1/2"	Set at 75 psi	50/150	\$ 19.08
RV75	3/4" x 1/2"	Set at 75 psi	50/150	19.93
RV50-100	1/2" x 1/2"	Set at 100 psi	50/150	19.08
RV75-100	3/4" x 1/2"	Set at 100 psi	50/150	19.93
NO LEAD Bronze Relief Valves - Made in USA				
RV50NL	1/2" x 1/2"	Set at 75 psi	50/150	28.16
RV75NL	3/4" x 1/2"	Set at 75 psi	50/150	28.57
RV50-100NL	1/2" x 1/2"	Set at 100 psi	50/150	28.16
RV75-100NL	3/4" x 1/2"	Set at 100 psi	50/150	28.57
Brass Relief Valves - Imported				
IRV50	1/2" x 1/2"	Set at 75 psi	10/100	9.05
IRV75	3/4" x 1/2"	Set at 75 psi	10/100	9.54
IRV7575	3/4" x 3/4"	Set at 75 psi	10/100	10.18
IRV50-100	1/2" x 1/2"	Set at 100 psi	10/100	9.05
IRV75-100	3/4" x 1/2"	Set at 100 psi	10/100	9.54
IRV7575-100	3/4" x 3/4"	Set at 100 psi	10/100	10.18
NO LEAD Brass Relief Valves - Imported				
IRV50NL	1/2" x 1/2"	Set at 75 psi	10/100	12.00
IRV75NL	3/4" x 1/2"	Set at 75 psi	10/100	12.19
IRV50-100NL	1/2" x 1/2"	Set at 100 psi	10/100	12.00
IRV75-100NL	3/4" x 1/2"	Set at 100 psi	10/100	12.19
304 Stainless Steel Relief Valves - Imported				
IRV50SS	1/2" x 1/2"	Set at 75 psi	10/100	21.79
IRV75SS	3/4" x 3/4"	Set at 75 psi	10/100	23.04
IRV50-100SS	1/2" x 1/2"	Set at 100 psi	10/100	21.79
IRV75-100SS	3/4" x 1/2"	Set at 100 psi	10/100	23.04
Hamilton Brass Adjustable Safety Relief Valves				
		Set at Adjustable to	Sold at Preset Only	
HRV50	1/2" mipt x 1/2" fipt	75 psi 150 psi	25	47.72
HRV75	3/4" mipt x 3/4" fipt	75 psi 100 psi	25	70.26
HRV175	1" mipt x 3/4" fipt	75 psi 200 psi	25	115.72
HRV125	1 1/4" mipt x 1 1/4" fipt	75 psi 200 psi	10	218.37

FLOW RATES							
PSI	85	90	95	100	105	110	115
RV Series gpm	.30	7.3	7.7	9.8	17.9	18.9	20.6
IRV Series gpm	2.0	2.7	3.8	4.7	7.0	12.0	12.7
PSI	10	20	30	40	60	80	100
HRV50	.6	1.5	2.5	3.6	6.1	8.8	11.8
HRV75			2.8	5.5	11.0	13.8	17.9
HRV175	6.0	12.6	19.0	24.6	35.6	44.8	52.3
HRV125	12.0	35.0	48.4	69.2	106.5	132.5	150.0



In the United States: Phone (800) 776-2266
In Canada: Phone (866) 503-5523

www.americangranby.com

Fax (800) 729-3299
Fax (888) 562-2095

10/23/12

1.23