


Description

FlangeFit® Kits include everything needed to make-up a flanged assembly. Suitable for use in all flanged connections in fire sprinkler systems including flanged alarm valves and back-flow preventers and other Class 125 flanges. Each kit includes one 1/8" red rubber ring gasket and the correct number of plated hex head bolts and nuts per flange. Each kit is skin-packed to a durable cardboard backing to make sure that all kit components get to the job site. Eliminates the need to carry a separate inventory of loose nuts, bolts and gaskets reducing inventory items and the labor costs associated with providing this solution.



Installation

Install according to specific manufacturers instructions for flanged equipment.

Specifications

Each kit contains one 1/8" thick red rubber ring gasket and the following A307 (Grade 2) plated nuts and bolts according to size:


1 1/4", 1 1/2", 2", 2 1/2", 3"
4 bolts & nuts

4", 5", 6", 8"
8 bolts & nuts

10", 12", 14"
12 bolts & nuts

Fasteners are manufactured to the following standards:

ANSI/ASME B18.2.1
1981 (bolts)
ANSI/ASME B18.2.2
1986 (hex nuts)



3198 LIONSHEAD AVE
CARLSBAD, CA 92010
TEL + 1 760 599-1168
+ 1 800 344-1822
FAX + 1 800 344-3775

© 2015 Fire Protection Products, Inc.