

# McGuire Manufacturing Co., Inc. 60 Grandview Court

Cheshire, Connecticut 06410 (203) 699-1801 Fax (203) 699-1813

customerservice@mcguiremfg.com mcguiremfg.com

### **PRODUCT SPECIFICATION**


Part No.

8872C, 8902C, 8902CNC, 8912C, 8912CNC, 8903C, 8904C

Cast Body P-Trap With or Without Cleanout

#### Job Name:

### **Submittal Number:**



#### **PROFESSIONAL LINE**

ROUGHING MEASUREMENTS					
NO.	TRAP DIMENSIONS				04- 5
	INLET	OUTLET	Α	В	C to E
8872C	1-1/4"	1-1/4"	4-1/2"	4-1/4"	11-1/2"
8902C	1-1/4"	1-1/2"	5"	5-1/2"	11-1/2"
8902CNC	1-1/4"	1-1/2"	4-5/8"	4-3/4"	11-1/2"
8912C	1-1/2"	1-1/2"	5"	5-1/2"	11-1/2"
8912CNC	1-1/2"	1-1/2"	4-5/8"	4-1/8"	11-1/2"
8903C	1-1/2"	2"	5"	6''	13-3/4"
8904C	2"	2"	5"	6"	13-3/4"

FED SPEC W.W.P. 541
CAST BRASS P TRAP
MINIMUM SEAL 2"



See options and accessories section for details on product variations.

ASME A112.18.2/CSA B125-2

## **Specifications:**

P-Trap shall be chrome plated cast brass body (with, without) cleanout, with 17 gauge seamless tubular wall bend, cast brass slip nuts. Reducing washers shall be used with reducing cast brass nut. With (shallow, deep, bell) (steel, brass) or (forged brass with set screw) flange.

P-Trap shall be McGuire "Classic" Professional Line

Trap shall be certified by CSA or other recognized testing authority. Trap shall bear manufacturer and testing marks.



This product can expose you to chemicals including lead, which is known to the State of California to cause cancer, and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.