

Location:

SYMMONS® Ultra-Sense™

Model S-6060-G
with 4 inch deck plate



Sensor Activated Lavatory Faucet S-6060 Series Specification Submittal

Model Numbers

- ☐ S-6060..... Faucet with 6V lithium battery power pack, faucet p/n SF-231
- ☐ S-6060-AC-12V..... Faucet with AC wall plug-in transformer, faucet p/n SF-01257
- ☐ S-6060-ACM-12V.. Faucet for use in multi-faucet applications faucet p/n SF-01257
Requires 12VDC power supply, model S-6240-12V purchased separately

Options / Modifications

Append appropriate -suffix to model number

- ☐ -G Grid strainer drain
- ☐ -OFG Offset grid strainer drain
- ☐ -0.35 0.35 gpm (1.3 L/min) Vandal resistant flow rate restrictor
- ☐ -0.5 0.5 gpm (1.9 L/min) Vandal resistant flow rate restrictor
- ☐ -0.5-NA 0.5 gpm (1.9 L/min) Vandal resistant laminar flow non-aerated spray outlet restrictor
- ☐ -NA 1.5 gpm (5.7 L/min) vandal resistant laminar flow non-aerated spray outlet restrictor
- ☐ -DP 8 inch adapter plate
- ☐ -LST 18 inch copper supply tube and adapter (instead of 20 inch braided hose)
- ☐ -20 20 foot (6096 mm) power supply cord in place of standard 10 foot (3048 mm) cord (Model S-6080-ACM-12V only)
- ☐ -SM Single hole mount only
Deck plate is not included

Finish Options / Modifications

Append appropriate -suffix to model number

- Chrome plated brass (standard finish)

Standards / Certifications


- ASME A112.18.1/CSA B125.1
- NSF/ANSI 61.9, NSF/ANSI 372



Feature Highlights

- Sensor Activated Lavatory Faucet with infrared Position Sensitive Detection (PSD) system
- Electronic components are sealed above deck in cast brass body for easy installation, service and maximum vandal resistance
- 10 second cycle time with automatic shut-off
- Single hole and 3 hole mounting hardware with 4 inch center deck plate
- Aerator, vandal resistant, 1.5 gpm (5.7 L/min) flow rate
- Water supply in-line strainer / adapter
- 20 inch braided supply hose or optional 18 inch copper supply tube (-LST)
- Chrome plated brass (standard finish)
- **Model S-6060** Includes internal 6 volt lithium battery, typical battery life is 3 years at 210 cycles per day
- **Model S-6060-AC-12V** Includes AC wall plug-in transformer with 72 inch (1829 mm) power cord (120VAC/12VDC, class II, UL listed for US/C)
Faucet power specification: 12VDC @ 200 ma, <100 mVpp
- **Model S-6060-ACM-12V** Includes 10 foot (3048 mm) 12VDC power supply cord. Model used with multi-faucet power supply and electrical termination enclosure.
Faucet power specification: 12VDC @ 200 ma, <100 mVpp
The following items are available and purchased separately

S-6240-12V Universal 120 - 240VAC Power Supply with 12VDC output. Supports up to eight (8) faucets. (reference S-6240-12V Specification Submittal for product details)



Note: Using a non-Symmons power supply will void warranty

S-6244 Standard Electrical Termination Enclosure for 12VDC @ 3.33 amps, box size: 6"H (152 mm) x 10"W (254 mm) x 4"D (102 mm)
(reference S-6244 Specification Submittal for product details)




Also available at local electrical supply

Warranty

- Limited Lifetime - to the original end purchaser in residential / consumer installations
- 5 years - for commercial installations

Dimensions Ultra-Sense Lavatory Faucet, S-6060, S-6060-AC-12V/ACM-12V



Visual Guide Multi-Faucet Configuration with S-6240-12V Power Supply

