

103 SERIES OFFSET SHOWER DRAIN WITH RECEPTOR BASE



TECHNICAL SPECIFICATION: Oatey Offset Shower Drains with Receptor Base are designed for use with preformed shower stall bases. The drain is solvent welded to 2" Schedule 40 DWV pipe and allows a 1.5" margin of error. Drain top accommodates 4-¼" Universal Snap-Tite Strainers available in a variety of designer finishes.



PHYSICAL/CHEMICAL PROPERTIES

Material/Color ABS Plastic = Black PVC Plastic = White

COMMON APPLICATIONS

Oatey Offset Shower Drains with Receptor Base are designed for use with preformed shower stall bases. The drain is solvent welded to 2" Schedule 40 DWV pipe and allows a 1.5" margin of error. Drain top accommodates 4-1/4" Universal Snap-Tite Strainers available in a variety of designer finishes.

- · Made of PVC or ABS Plastic
- Offset design allows for margin of error when roughing in a shower base
- Sealing and friction gaskets allow for positive seal to the shower base
- Available with 4-¼" Stainless Steel Snap-Tite Strainer

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
42787	PVC Offset Shower Drain w/Stainless Steel Strainer	12	8 lbs.
42788	ABS Offset Shower Drain w/Stainless Steel Strainer	12	8 lbs.