



4700 W. 160th St.  
Cleveland, OH 44135  
PH:800-321-9532  
FX:800-321-9535  
www.oatey.com

## Versa-Link® Modular Clamp System



### TECHNICAL SPECIFICATION

**TECHNICAL SPECIFICATION:** Oatey Versa-Link Pipe Clamps provide fast and easy installation for all types of PEX, CPVC-CTS, and copper tube. Two-pipe run clamps support hot and cold lines, and come pre-loaded with nails or drill point sheet metal screws. One-pipe clamp easily connects to two-pipe run to accommodate additional runs. The Versa-Link Clamp system positions the pipe in the center of the stud and helps to minimize sound by eliminating the pipe rattling on the stud walls. The Versa-Link Clamp is available in 1/2" size.

### APPROVALS AND LISTINGS



IAPMO Listed

### PHYSICAL/CHEMICAL PROPERTIES

Material High Impact ABS  
Color Dark Gray  
Maximum Temperature Rating 180°F

### DIRECTIONS FOR USE

#### 2-Pipe Run Clamp:

1. Insert fasteners in holes.
2. Connect to wood or metal stud\*.
3. Securely snap-in supply line.

#### 1 Pipe Attaching Clamp\*\*:

1. Align 1 Pipe Attaching Clamp and 2 Pipe Run clamps.
2. Slide clamps together until snap.
3. Additional 1 Pipe Clamps can be secured.
4. Do not exceed 4 pipe run on modular connection.

\* Do not use screws in wood studs.

\*\*Do not use 1 Pipe Attaching Clamp by itself.

Check with local codes to ensure proper spacing requirements for piping support.

### PRECAUTIONS

Read cautions and directions on packaging carefully before using this product. KEEP OUT OF REACH OF CHILDREN.

### COMMON APPLICATIONS

Oatey VERSA-LINK Clamps provide fast and easy installation and support for all types of PEX, CPVC, and copper tube sized piping.

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
33680	1/2" Two-pipe Clamp with nails (20 per bag)	10 BAGS	18 lbs.
33681	1/2" Two-pipe Clamp with screws (20 per bag)	10 BAGS	18 lbs.
33682	1/2" One-Pipe Clamp (10 per bag)	10 BAGS	5 lbs.