

Tercet® 5' Bath K-1161-F



Features

- Integral flange.
- Center drain.
- Integral lumbar support and armrests for comfort.
- 60" (1524 mm) x 60" (1524 mm) x 21" (533 mm)

Material

Acrylic

Installation

Corner flange.

Recommended Accessories

K- 1491 Bath/Whirlpool Pillow K- 11677 Bath Drain



Codes/Standards

CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795 Greenguard UL 2818 - Gold

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond







Tercet® 5' Bath K-1161-F

63" 35" (1600 mm) (889 mm) 29" 35" (737 mm) (889 mm) 60" (1524 mm) (124 mm) 13-1/8" 43-3/4" (333 mm) (1111 mm) (737 mm) 1-1/4" 60" (1524 mm) (32 mm) 2-7/8" ¹(73 mm) 21" 19-1/2" (533 mm) (495 mm)

No change in measurements if connected with drain illustrated. (K-11677)

Recommended faucet area





Technical Information

All product dimensions are nominal.

Installation: Corner Drain location: Center

Basin area, bottom: 52" x 38-3/4" (1321 mm x 984 mm)
Basin area, top: 61" x 46-1/4" (1549 mm x 1175 mm)

Weight: 91 lbs (41.3 kg)

Minimum floor load: 38 lbs/ft² (185.5 kg/m²)

Water depth: 15" (381 mm)
Water capacity: 96 gal (363.4 L)

Notes

1-1/2" Bath Drain

Measure your actual product for rough-in details. Install this product according to the installation

instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

