

TUFLEX® ENDLESS ROUNDSLINGS

The Most Versatile *Tuflex* Roundsling

Features and Benefits

Maintains all the basic *Tuflex* features plus...

Promotes Safety

- Load stability and balance can be achieved by spreading sling legs.
- EN360 and larger Tuflex roundslings feature Tufhide[™] wear-resistant nylon jacket for extra sling life.

Saves Money

- Wear points can be shifted to extend sling life.
- The most flexible style of sling.
- Individual slings can be attached together using appropriate hardware.

How To Measure





Tuflex Endless Roundslings										
		Rated Capacity* (lbs.)					Approximate Measurements			
Part Number	Color	Vertical	Choker	Basket @ 90°	Basket @ 45°	Min. Length (ft.)	Weight (lbs./ft.)	Body Dia. Relaxed (in.)	Contact Width (in.)	Min. Hardware Dia.** (in.)
EN30	Purple	2,600	2,100	5,200	3,600	1.5	0.20	0.63	1.00	0.44
EN60	Green	5,300	4,200	10,600	7,400	1.5	0.30	0.88	1.38	0.63
EN90	Yellow	8,400	6,700	16,800	11,800	1.5	0.52	1.13	1.75	0.75
EN120	Tan	10,600	8,500	21,200	14,000	2.0	0.60	1.13	1.88	0.88
EN150	Red	13,200	10,600	26,400	18,000	2.0	0.76	1.38	2.00	1.00
EN180	White	16,800	13,400	33,600	23,000	3.0	0.87	1.38	2.13	1.13
EN240	Blue	21,200	17,000	42,400	29,000	3.0	1.10	1.75	2.63	1.19
EN280	Orange	25,000	20,000	50,000	35,000	3.0	1.25	1.87	3.00	1.25
EN360	Gray	31,000	24,800	62,000	43,000	3.0	1.70	2.25	3.25	1.50
EN460	Orange	40,000	32,000	80,000	56,000	3.0	2.30	2.50	3.75	1.62
EN600	Brown	53,000	42,400	106,000	74,000	8.0	2.90	2.75	4.00	2.00
EN800	Olive	66,000	52,800	132,000	93,000	8.0	3.40	3.13	4.63	2.13
EN900	Orange	77,000	61,600	154,000	108,000	8.0	3.90	3.42	5.00	2.25
EN1000	Black	90,000	72,000	180,000	127,000	8.0	4.40	3.63	5.25	2.50
EN1100	Orange	100,000	80,000	200,000	140,000	8.0	4.80	4.10	5.50	2.62

^{**} This is the minimum recommended diameter for the connection hardware to be used for a vertical hitch.

^{* ★} WARNING Do not exceed rated capacities. Sling tension increases as the angle from horizontal decreases. Slings should not be used at angles of less than 30°. Refer to the Effect of Angle chart in the General Information section of this catalog. Always protect synthetic slings from being cut by corners and edges. See the Sling Protection section in this catalog.