

Rev. 9-17 Shaded area indicates changes

Tubeing, pipe and liners used with Mueller 110 Compression Connection

Nominal size of connection	Material*	Tubeing or pipe O.D. range - inches	Tubeing or pipe wall thickness range - inches	Tubeing or pipe I.D. range - inches	Liner part number
1/2" CTS	Type "K" copper	0.622 - 0.628	0.045 - 0.053	-	-
3/4" CTS	Type "K" copper	0.872 - 0.878	0.061 - 0.069	-	-
	Polyethylene	0.871 - 0.879	0.097 - 0.107	0.657 - 0.685	504281
1" CTS	Type "K" copper	1.121 - 1.129	0.061 - 0.069	-	-
	Polyethylene	1.120 - 1.130	0.125 - 0.137	0.846 - 0.880	504385
1-1/4" CTS	Type "K" copper	1.371 - 1.379	0.060 - 0.070	-	-
	Polyethylene	1.370 - 1.380	0.153 - 0.168	1.034 - 1.074	505142
1-1/2" CTS	Type "K" copper	1.621 - 1.630	0.067 - 0.077	-	-
	Polyethylene	1.619 - 1.631	0.181 - 0.199	1.221 - 1.269	506139
2" CTS	Type "K" copper	2.120 - 2.130	0.076 - 0.090	-	-
	Polyethylene	2.119 - 2.131	0.236 - 0.260	1.599 - 1.659	506141
3/4" IPS	Polyethylene	1.045 - 1.110	0.118 - 0.138	0.809 - 0.834	505141
1" IPS	Polyethylene	1.329 - 1.399	0.150 - 0.170	1.029 - 1.059	505142

*Type "K" soft copper tubeing per ASTM B88; CTS polyethylene (PE) per ASTM D-2737 - SDR-9; IPS polyethylene (PE) per ASTM D-2239 - PE SDR-7; IPS polyvinylchloride (PVC) per ASTM D1785



Liner

Mueller 110 Compression Connection Replacement Parts

Size	Gasket part number†	Connection nut
1/2" CTS	681516	147542
3/4" CTS	581949	507831
1" CTS	581951	507835
1-1/4" CTS	581953	507843
1-1/2" CTS	581955	507847
2" CTS	581957	507851
3/4" IPS	89599	508826
1" IPS PE	89788	508827



Gasket assembly



Nut

†Gasket and gripper band assembly

Adapter Nut for pre-1976 style Mueller 110 Compression Connection for CTS tubeing

Kit includes one standard Gasket (same used with current style 110 connections) and a special Nut that adapts to the older style connection threads on the fittings. It is installed in the same way as the current style connection (Gasket conductor spring should be toward fitting body).

Size	Connection kit
3/4" CTS	682552
1" CTS	682551



Copper Gasket

Replacement gasket to be used inside Female Copper Service Thread when assembling Fitting onto a Corporation Valve/Stop. Gasket is intended for single use only and must be replaced if Fitting is disassembled or reused. CATALOG NUMBER: **H-15053**



1/2"	5/8"	3/4"	1"	1-1/4"	1-1/2"	2"
------	------	------	----	--------	--------	----