



Pipe Size	B	A Length		C Nominal Wall			
	Pipe O.D.	Close	Space	STD.	XH	160	XXH
1/8	0.405	3/4	1 1/2 - 24	0.068	0.095	N/A	N/A
1/4	0.540	7/8	1 1/2 - 24	0.088	0.119	N/A	N/A
3/8	0.675	1	1 1/2 - 24	0.091	0.126	N/A	N/A
1/2	0.840	1 1/8	1 1/2 - 24	0.109	0.147	0.188	0.294
3/4	1.050	1 3/8	1 1/2 - 24	0.113	0.154	0.219	0.308
1	1.315	1 1/2	2 - 24	0.133	0.179	0.250	0.358
1-1/4	1.660	1 5/8	2 - 24	0.140	0.191	0.250	0.382
1-1/2	1.900	1 3/4	2 - 24	0.145	0.200	0.281	0.400
2	2.375	2	2 1/2 - 24	0.154	0.218	0.344	0.436
2-1/2	2.875	2 1/2	3 - 24	0.203	0.276	0.375	0.552
3	3.500	2 5/8	3 - 24	0.216	0.300	0.438	0.600
3-1/2	4.000	2 3/4	4 - 24	0.226	0.318	N/A	N/A
4	4.500	2 7/8	4 - 24	0.237	0.337	0.531	0.674
5	5.563	3	4 1/2 - 24	0.258	0.375	0.625	0.750
6	6.625	3 1/8	4 1/2 - 24	0.280	0.432	0.719	0.864
8	8.625	3 1/2	5 - 24	0.322	0.500	0.906	0.875

Confirms to:

ASTM A53 Type F—(Continuous Welded).

ASTM A53 Type E, Grade B—(Electric Resistance Welded).

ASTM A106 Grade B, ASTM A53 Type S, Grade B, API 5L, Grade B—Seamless, High Temperature.

ASTM A333 Grade 6 (Available only in XH, 160 and XXH)—Seamless, Low Temperature.

Finish:

Standard Black or Galvanized