



# GoldTop Air Vent

FV180, FV180A, FV183

**PRODUCT DATA**



## FEATURES

- **Male Connection.**
- **Four Sizes Available.**
- **Higher Capacity.**
- **Vents Up To 150 psi (1034 kPa).**

## SPECIFICATIONS

**Maximum Pressure:** 150 psi (1034 kPa).

**Maximum Temperature:** 240 °F (116 °C).

Product Number	Height	Diameter	Connection in inches	Weight in lb (kg)
	in inches (mm)	in inches (mm)		
FV180	3.25 (83)	1.85 (47)	1/8 NPT	0.4 (0.2)
FV180A	3.25 (83)	1.85 (47)	1/4 NPT	0.4 (0.2)
FV183	3.82 (97)	1.85 (47)	3/4 NPT	0.6 (0.3)

## APPLICATION

The GoldTop Air Vent is a spring-loaded, float type air vent. It is used in heating systems to vent air, which has accumulated due to the heating of cold water.

## INSTALLATION

Install GoldTop into the heating system at the high point, or wherever air would accumulate to remove the air. Typical recommended locations are: on boiler top, on top of an air purger, etc. Loosen thumb cap to allow air to vent.



www.resideo.com

Resideo Technologies, Inc.  
 1985 Douglas Drive North, Golden Valley, MN 55422  
 1-800-468-1502  
 62-3086-01 M.S. Rev. 07-21 | Printed in United States

© 2021 Resideo Technologies, Inc. All rights reserved.  
 This product is manufactured by Resideo Technologies, Inc. and its affiliates.



62-3086-01