Residential Products



Application Selection and Cross-Reference Guide

E-mail info@honeywell.com customer.honeywell.com

Learn More

Automation and Control Solutions

In the U.S.: Honeywell 1985 Douglas Drive North Golden Valley, MN 55422-3992

Call toll-free 1-800-328-5111

In Canada: Honeywell Limited 35 Dynamic Drive Toronto, Ontario M1V 4Z9 www.honeywell.com



August 2005 Printed in U.S.A. © 2005 Honeywell International Inc. All rights reserved.

PM/50-9347



Why Honeywell?

Products



Quality Engineering

Honeywell's unwaivering commitment to our customers includes an intense focus on the measurement of product quality to deliver products with the newest available features at the right price.

Exclusive Features and Warranties

Honeywell products feature exclusives you won't find with other brands, like the American Lung Association[®] Health House[®] seal on our Indoor Air Quality products and the industry's best warranties - up to 5 Years.



Brand

Complete Portfolio

From thermostats to indoor air quality, water to combustion controls, only Honeywell provides you with the leading portfolio of residential control products to meet your needs for every application, budget and customer.



Preference

The Honeywell brand is known, trusted and preferred by millions of professional contractors and the customers they serve. Honeywell is the #1 choice of homeowners, and has strong brand recognition.

Support

Free Sales Literature

With Honeywell, you'll have access to sales materials that you can use to help grow your business.



Customer Service

Honeywell provides toll-free access to product application, installation and support experts at 1-800-468-1502.

Training

Honeywell offers a variety of on-site and online training options at customer.honeywell.com



Online Tools

Rewards

Find everything you need to be successful in selling Honeywell products online. Product information, cross-references, demos and more are available at customer.honeywell.com.

Honeywell

ContractorPRO^{**} POWERContractor Program

Honeywell's Contractor PRO Rewards program gives

contractors reward points (\$) back on all Honeywell purchases year round at contractorpro.com.

Thermostats

Honeywell thermostats are the number one choice of both homeowners and contractors. Homeowners appreciate the stylish looks, dependability, ease-of-use and accurate temperature control. Contractors appreciate the reliability, easy installation and the universal compatibility that lets them meet every need with just a few thermostats on the truck. And, of course, both homeowners and contractors trust the Honeywell name, the most recognized thermostat brand in the world.

When selecting a thermostat for your next job, look for these Honeywell features:

- Universal Application
- Largest Backlit Digital Displays in Every Category
- Easy-Access Battery Replacement
- Built-In Instructions
- Real-Time Clock
- FREE Private Labeling
- Precise Temperature Control (+/- 1° F)
- Adaptive Intelligent Recovery[™]
- 5-Year Warranty



Honeywell



- Effortless, menu-driven programming.
- Universal application up to 3H/2C.
- Real-time clock.
- Large 10-square inch touchscreen display.

FocusPRO[™] 6000 5-1-1 Day Programmable

- · Easy-access battery replacement.
- Built-in instructions.
- Up to 2H/2C conventional and heat pump.

FocusPRO[™] 5000 Digital Non-Programmable

- · Easy-access battery replacement.
- Largest display in its class.
- Up to 2H/2C conventional and heat pump.

PRO 4000 5-2 Day Programmable

- Basic slide-switch operation.
- Models available for 2H/1C and 1H/1C applications.
- Dual-powered (battery and hardwire).

PRO 3000 Non-Programmable

- Basic slide-switch operation.
- Models available for 2H/1C and 1H/1C applications.
- Dual-powered (battery and hardwire).

4













Thermostat Selection Guide

	Model		Sche	edule Opti	ions	User Interface	Applica	ation	Power Method		Featu	res and F	unctions		I	Displ nforma		Serv	vice Re	minders	Warranty	Wiring Terminals		Upgrade (Cross-Reference	
		Program Options	© - + C	Energy Star [®] Temporary Override	Permanent Hold Vacation Hold		Stages	Gas, Oil or Electric Heat Pump	Millivolt	-Tin	Permanent Memory Retention Selectable Auto or Manual Changeover	Adaptive Intelligent Recovery TM	Revealed Focker Keypad Locker Idoor Humidity (Dehumidification Control Dual Fuel Heat Pump Operation Outdoor or Indoor Sensor	Display Size (Viewable)	On-Demand Backlighting	Continuous Backlighting Simultaneous Display of Room and Set Temperatures	Filter Reminder	Humidifier Pad Replacement Reminder	UV Lamp Replacement Reminder			Honeywell	White-Rodgers	Robertshaw [®]	Totaline®
BEST	TH8110U1003	7 Day	y .	• Fixed and Adjustable		Touchscreen	1 Heat/1 Cool	• •	Dual Powered (Battery and Hardwire)	•	• •	•	• •		10 sq. in	. •	• •	•	•	•	5 Year	R, Rc, W-0/B, Y, G, C, S1, S2	T8600, T8601, T8602	1F90-371, 1F96- 344, 1F97-371	9700i, 9701i	P274-1300, P374-1100
- 100 - 100 - 100	TH8320U1008	7 Day	y ·	• Fixed and Adjustable	i • •	Touchscreen	Up to 3 Heat/2 Cool	• •	Dual Powered (Battery and Hardwire)	•		•	•••		10 sq. in		•	•	•		5 Year	R, Rc, W-0/B, AUX-W2, Y, Y2, L, E, G, C, S1, S2	T8600, T8601, T8602, T8611, T8624	1F90, 1F92, 1F93, 1F94, 1F95, 1F96, 1F97	9700i, 9701i, 9715i, 9720i	P274-1300, P374-1100, P374-2200, P286-1200, P286-1300
VisionPRO [™] 8000 Touchscreen Programmable	TH8321U1006 with dehumidification	7 Day	y .	 Fixed and Adjustable 		Touchscreen	Up to 3 Heat/2 Cool	• •	Dual Powered (Battery and Hardwire)	•	• •	•	• • •	••••	10 sq. in		• •	•	•	•	5 Year	R, Rc, W-0/B, AUX-W2, Y, Y2, L, E, G, C, S1, S2		1F90, 1F92, 1F93, 1F94, 1F95, 1F96, 1F97	9700i, 9701i, 9715i, 9720i, 9851i, 9865i, 9870i	P274-1300, P374-1100, P374-1600, P374-2200, P286-1200, P286-1300
		5-1-1/	5-2	•	•	Soft Keys	1 Heat/1 Cool	• •	• Dual Powered (Battery and Hardwire)		• •	•	•		3.75 sq. ir	1. •	•				5 Year	R, Rc, W-0/B, Y, G, C	T8000, T8001, T8002, T8112	1F80	8600, 9600, 9610	P474-1050, P474-1035
BETTER	TH6110D1021	5-1-1 / :	5-2	• •	•	Soft Keys	1 Heat/1 Cool	• •	• Dual Powered (Battery and Hardwire)		• •	•	•		5.09 sq. ir	1. •	•				5 Year	R, Rc, W-O/B, Y, G, C	T8000, T8001, T8002, T8112	1F80	8600, 9600, 9610	P474-1050, P474-1035
000		5-1-1 / :	5-2	• •	•	Soft Keys	Up to 2 Heat/2 Cool	• •	• Dual Powered (Battery and Hardwire)		•	•	•		3.75 sq. ir	1. •	•				5 Year	R, Rc, W-0/B, AUX-W2, Y, Y2-E, L, G, C	T8112, T8000, T8001, T8002, T8011, T8024	1F80, 1F81, 1F82, 1F85	8600, 8625, 9600, 9610, 9615, 9620	P474-1050, P474-1035, P374-1000
FocusPRO™ 6000 Programmable	TH6220D1028	5-1-1 /	5-2	• •	•	Soft Keys	Up to 2 Heat/2 Cool	• •	Dual Powered (Battery and Hardwire)		• •	•	•		5.09 sq. ir	1. •	•				5 Year	R, Rc, W-0/B, AUX-W2, Y, Y2-E, L, G, C	T8112, T8000, T8001, T8002, T8011, T8024	1F80, 1F81, 1F82, 1F85	8600, 8625, 9600, 9610, 9615, 9620	P474-1050, P474-1035, P374-1000
	TH5110D1006	Non-Pr	rog			Soft Keys	1 Heat/1 Cool	• •	Dual Powered (Battery and Hardwire)		• •		•		1.95 sq. ir	1. •	•				5 Year	R, Rc, W-0/B, Y, G, C	T8501, T8400, T8401	1F86	8400, 8401, 9400, 9401, 9550	P474-0100, P474-0130
BETTER	TH5110D1022	Non-Pr	rog			Soft Keys	1 Heat/1 Cool	• •	Dual Powered (Battery and Hardwire)		•		•		2.98 sq. ir	1. •	•				5 Year	R, Rc, W-0/B, Y, G, C	T8501, T8400, T8401	1F86	8400, 8401, 9400, 9401, 9550	P474-0100, P474-0130
33	TH5220D1003	Non-Pr	rog			Soft Keys	Up to 2 Heat/2 Cool	• •	• Dual Powered (Battery and Hardwire)		•		•		3.75 sq. ir	1. •	•				5 Year	R, Rc, W-0/B, AUX-W2, Y, Y2-E, L, G, C	T8501, T8511, T8524, T8400, T8401, T8411, T8424	1F73, 1F83, 1F86, 1F89	8400, 8401, 8425, 9400, 9401, 9415, 9420, 9550, 9555, 9560	P474-0100, P474-0130
FocusPRO 5000 Non-Programmable	TH5220D1029	Non-Pr	rog			Soft Keys	Up to 2 Heat/2 Cool	• •	Dual Powered (Battery and Hardwire)		• •		•		5.09 sq. ir	1. •	•				5 Year	R, Rc, W-0/B, AUX-W2, Y, Y2-E, L, G, C	T8501, T8511, T8524, T8400, T8401, T8411, T8424	1F73, 1F83, 1F86, 1F89	8400, 8401, 8425, 9400, 9401, 9415, 9420, 9550, 9555, 9560	P474-0100, P474-0130
GOOD	TH4110D1007	5-2		• •	•	Slide Switches	s 1 Heat/1 Cool	• •	• Dual Powered (Battery and Hardwire)		• Manual	•			1.73 sq. ir	ı. •	•				5 Year	R, Rc, C, W, O, B, Y, G	T8112	1F78-151	8600, 9600	P474-1035
PRO 4000 Programmable	TH4210D1005	5-2			•	Slide Switches	s 2 Heat/1 Cool		Dual Powered (Battery and Hardwire)		• Manual	•			1.73 sq. ir	1. •					5 Year	R, C, Y, Aux, O, B, E, G, L	T8011R	1F72-151	8625	P474-1050
GOD	TH3110D1008	Non-Pr	rog			Slide Switches	s 1 Heat/1 Cool	• •	• Dual Powered (Battery and Hardwire)		• Manual				1.32 sq. ir	1. •	•				5 Year	R, Rc, C, W, O, B, Y, G	T8400, T8401	1F78-144	8400, 9500	P474-0130, P374-0200
PRO 3000 Non-Programmable	TH3210D1004	Non-Pr	rog			Slide Switches	s 2 Heat/1 Cool	•	Dual Powered (Battery and Hardwire)		• Manual				1.32 sq. ir	1. •	•				5 Year	R, C, Y, Aux, O, B, E, G, L	T8411R	1F79-111	8425, 9420	P374-0300/SV300, P474-0100
	T8775A1009	Non-Pr	rog			Dial	1 Heat	•†	Power Stealing		•				.75 sq. in	. •					5 Year	R, W	T87			
The Digital Round**	T8775C1005	Non-Pr	rog			Dial	1 Heat/1 Cool	• •	Power Stealing		• Manual				.75 sq. in	. •					5 Year	R, Rc, W, O, B, Y, G	T87			

† Gas or Oil Heat Only

Zoning Systems

Honeywell developed its first residential temperature zoning systems in 1954. Since then, the market for individual room temperature control has continued to grow, and so has Honeywell's leadership position in the category. For applications from two zones to 32 zones, and for products from panels to dampers to complete system kits, Honeywell is your single-source solution for Zoning.

When selecting a Zoning System for your next job, look for these Honeywell features:

- Universal Compatibility
- Simple Installation
- Networking Protocols
- Wireless Options
- Zoning Kits
- Kevlar[™] Damper Gears
- Meets American Lung Association® Health House® Guidelines
- National Team of Local Zoning Experts
- Dedicated Toll-Free Zoning Hotline (1-800-TAT-TEMP)
- Sales and Installation Training
- System Design and On-Site Diagnostics
- Direct Shipment to Contractor Jobsites
- 5-Year Warranty



Honeywell



EnviraZone[™] Networked Zoning

- Most advanced and easiest-to-install system in the industry.
- Uses exclusive EnviraCOM[™] communications protocol.
- Offers all-zone programming from any thermostat.
- Expandable up to nine zones with additional damper interface modules and thermostats.
- Meets American Lung Association[®] Health House[®] guidelines.

TotalZone[™] 4 System

- Expands from four to 32 zones quickly and easily.
- Patented duel-fuel capacity for add-on heat pump
- Adjustable stage control times.
- all zones during unoccupied periods.

EMM-3 and EMM-3U **Electronic Mini-Zone Systems**

- Panels available in both 1H/1C (EMM-3) and 2H/2C Universal (EMM-3U) options.
- Controls up to three zones.
- Provides auto-changeover by zone with 20-minute changeover timer.
- · Uses virtually any 4-wire thermostat.

Wireless RF Zoning

- · Proven reliability of wireless zoning technology.
- Wireless T8665A Chronotherm® IV thermostat works with both TotalZone and EMM-3 Panels.
- Wireless thermostats can be placed anywhere in the zone.
- Up to 3 zones per W8665E RF Receiver Module.

ZD, ARD and Bypass Dampers

- Wide variety of round and rectangular sizes.
- Rugged gear construction and riveted for extra strength.
- · Built with a gasket to ensure a proper damper seal.
- Adjustable minimum and maximum position stops.
- Built with gears containing DuPont[®] Kevlar[™] fiber, doubling actuator wear life.

- applications up to 3H/2C.
- Zone-A-Lone[™] allows master thermostat to set back

















5-YEAR WARRANTY





Conventional and Networked Zoning Selection Guide

How to pick the right zoning products for every application.

Conventional Zoning

Zoning kits include: (1) control panel (1) 40va transformer

Step 1: Select Control Panel and Accessories

Zoning kits include:		Control Panels
(1) control panel	ЕММЗК	2 or 3 zone 1H/1C panel
(1) 40va transformer	EMM3UK	2 or 3 zone up to 2H/2C
(1) C7735A discharge air		conventional and 2H/1C heat pump
temperature sensor	TZ4K	2 to 4 zones up to 3H/2C universal
		panel expandable to 32 zones with
······		the TAZ4 panels. Also includes
		fossil fuel kit for dual fuel heat
traine sector		pump w/gas backup
	Access	ories for every additional 1-4 zones
	TAZ4	1 to 4 zone adder panel used only
		with the TZ4; requires separate
A STATE OF THE OWNER		40va rated transformer
The second second	AT140A1042	40va rated transformer

Step 2: Select a Thermostat for Each Zone

Any 4-wire Honeywell thermostat will work.

	Thermostats
TH8321U1006	VisionPRO [™] 7-Day Touchscreen Programmable 3H/2C.
	Includes Dehumidification Control.
TH8320U1008	VisionPRO 7-Day Touchscreen Programmable 3H/2C.
TH8110U1003	VisionPRO 7-Day Touchscreen Programmable 1H/1C.
T8611G2051	Chronotherm [®] IV 7-Day Programmable
TH6220D1028	FocusPRO [™] 5-1-1 Day Programmable 2H/2C. Large Display.
TH6220D1002	FocusPRO 5-1-1 Day Programmable 2H/2C. Standard Display.
TH6110D1021	FocusPRO 5-1-1 Day Programmable 1H/1C. Large Display.
TH6110D1005	FocusPRO 5-1-1 Day Programmable 1H/1C. Standard Display.
TH5220D1029	FocusPRO Non-Programmable 2H/2C. Large Display.
TH5220D1003	FocusPRO Non-Programmable 2H/2C. Standard Display.
TH5110D1022	FocusPRO Non-Programmable 1H/1C. Large Display.
TH5110D1006	FocusPRO Non-Programmable 1H/1C. Standard Display.
	RF/Wireless Thermostat
T8665A1002	Wireless thermostat, one for each zone
W8665E1000	One receiver for up to three thermostats

EnviraZone[™] Networked Zoning

Step 1: Select an EnviraZone Zoning Kit



2-zone kits include:

- (2) T8635L thermostats
- (1) W8835A control panel
- (1) C7089 outdoor temperature sensor
- (1) AT140 40va transformer (1) C7835A discharge air
- temperature sensor

3-zone kit includes:

All of the above, plus (1) additional T8635L thermostat

Y8835A1002	2-zone kit
Y8835A1010	3-zone kit

Step 2: Add a Thermostat for Each Additional Zone

		Thermostats
	T8635L1013	7-Day Chronotherm IV —
		1 for each additional zone
		Accessories
68 0	EnviraCOM controls up to	9 zones. Use W8703 to
	add 3 zones to Y8835; up	o to 2 W8703 can be added.
	W8703A1003	3-zone damper interface module
	AT140A1042	40va rated transformer
	W8735A1005	EnviraCOM Serial Port Adapter for PC-Based Control (see vicarworks.com for more info)



Step 3: Select Zoning Dampers

All dampers are 2-wire, spring-open/power closed. Additional dampers available.



Rectar	ngular Supply Dampers —	- common sizes
ZD10x8	ZD18x8	Motor is mounted
ZD12x8	ZD20x8	on 2 nd dimension.
ZD14x8	ZD20x10	For bottom-mounted motor, reverse the
ZD16x8	ZD24x8	dimensions.
Rou	nd Supply Dampers — co	ommon sizes*
ARD6	ARD14	
ARD8	ARD16	
ARD10	ARD18	
ARD12		

*Damper sizes available in 125 variations

=

Step 4: Select Bypass Dampers

-

Calculate Total CFM, Then Choose Supply-To-Return Bypass

Total CFM of system (minus) CFM of smallest zone (equals) Total CFM to bypass (Bypass sized @.25 in. w.c.)

	CFM RANGE
SPRD8	0 to 400 CFM
SPRD10	401 to 750 CFM
SPRD12	751 to 1200 CFM
SPRD14	1201 to 1800 CFM
SPRD16	1801 to 2400 CFM
Destangular Du	

Rectangular Bypass also available.

Whole-House Air Cleaners

Honeywell introduced its first Electronic Air Cleaner nearly 50 years ago - and our history of performance and reliability have made us the #1 preferred consumer brand ever since. Our complete portfolio of product solutions includes Whole-House HEPA Air Cleaners, High-Efficiency Electronic Air Cleaners, Media Air Cleaners, Return Grille Media

Air Cleaners and Replacement Filters

When selecting an Air Cleaning solution for your next job, look for these Honeywell features:

- Sizes Designed to Fit Any Application
- Both Washable and Replaceable Filter Types
- Self-Regulating Power Supply and Test Button (F300)
- Anti-Microbial Coating on Postfilter Materials
- Advanced Airflow Sensor Technology
- AIRWATCH[™] Filter Replacement Indicators
- FREE Private Labeling (F100)
- Meets American Lung Association[®] Health House® Guidelines
- 5-Year Warranty



Honeywell



The American Lung Association and its

F500

Whole-House HEPA Air Cleaner

- Captures 99.97% of 0.3 micron particles.
- Three-stage filtration process includes activated carbon filter to help reduce odors.
- Includes AIRWATCH[™] Filter Replacement Indicator.
- Meets American Lung Association® Health House® guidelines.

F300

Whole-House Electronic Air Cleaner

- Captures up to 98% of airborne particles passing through the system.
- Self-Regulating Power Supply maintains high efficiency as the filter loads.
- Test Button to verify proper installation.
- Optional Anti-Microbial Postfilter to increase efficiency and provide replacement opportunity.
- Also available in a Return Grille Model (F52).
- Meets American Lung Association® Health House® guidelines.

F200

Whole-House Media Air Cleaner

- Captures up to 91% of airborne particles passing through the filter.
- Pressure Sensor in door indicates pressure drop and transmits to wireless receiver.
- Includes Wireless AIRWATCH[™] Filter Replacement Indicator.
- Meets American Lung Association® Health House® guidelines.

F100 Whole-House Media Air Cleaner

- Captures up to 85% of airborne particles passing through the filter
- Six space-saving sizes to fit any application.
- FREE Private Labeling ensures filter replacement calls.
- Meets American Lung Association[®] Health House[®] guidelines.

FC40R

Return Grille Media Air Cleaner

- Captures up to 85% of airborne particles passing through the filter.
- 17 sizes to fit any return grille application.
- Provides four inches of filtration in a one-inch grille, with three times the life of a standard one-inch filter.
- Meets American Lung Association® Health House® guidelines.

Replacement Filters

- Both cartridge and collapsible models.
- · High-efficiency and low pressure drop solutions.
- Sizes that fit Honeywell and competitive units.











5-YEAR

WARRANTY

5-YEAR

WARRANTY

5-YEAR WARRANTY







Air Cleaner Selection Guide

Picture	Model	Туре	OS#	Size	Application					Featur	es and Functions						Warranty			Upgrade Cross-Reference)		
						Rated Airflow	Electric Rating	Efficiency (MERV not applicable to electronic air cleaners)	Initial Pressure Drop at rated airflow	Replacement Filter/ Postfilter	Standard Efficiency Enhancing Postfilter with Anti- Microbial Coating	AIRWATCH [™] Maintenance Reminder	Maintenance Cycle	Self Regulating Power Supply	Dual Voltage Output Efficiency Optimization	Test Button Operating Verification		Aprilaire	Trion	White Rodgers	Carrier	Trane	Lennox
BEST	F500	Нера	F500A1000 F500B1009	Conditioned Space	Bypass or Stand Alone	360 CFM	120V	0.3 microns=99.97%		32006026-001 Carbon 32006027-001 2-inch Prefilter 32006028-001 HEPA Filter		Wireless reminder included	Carbon = up to 4 months 2-inch Prefilter = up to 16 mo. HEPA Filter = up to 5 years.				5 Year						
	F300E		F300E1001 F300E1019 F300E1027	16X20 16X25 20X20	- Inline air filtration	1200 CFM 1400 CFM 1400 CFM	- 120V	0.3 to 1.0 microns=81% 1.0 to 3.0 microns=93% 3.0 to 10.0 microns=99%	0.18 in. w.c.	50000293-001 50000293-002 50000293-003	Yes	Optional	Vacuum prefilter=up to 6 months Wash cells=up to 1 year Replace posfilter=6 months	Yes	Yes	Yes	5 Year		SE 1400 SE 2000 HE1400 HE2002 SE 1400 SE 2000 HE1400 HE2003	SST-1000 SST-1400 SST-1600 SST-2001 SST-1000 SST-1400 SST-1600 SST-2002 SST-1000 SST-1400 SST-1600 SST-2003 SST-1000 SST-1400 SST-1600 SST-2003 SST-1000 SST-1400 SST-1600 SST-2003	EACAAXCC0014 EACAAXCC0023	TFE145A9FR3 TFE175A9FR3 TFE210A9FR3 TFE215A9FR3 TFE235A9FR3 TFE235A9FR3 TFE245A9FR3	PC0-12C PC0-20C
BEST	F300A,B	Electronic	F300E1035 F300A1620 F300A1625 F300A2020 F300A2025 F300A2012	20X25 16X20 16X25 20X20 20X25 20X12.5	- Inline air filtration	2000 CFM 1200 CFM 1400 CFM 1400 CFM 2000 CFM		0.3 to 1.0 microns=73% 1.0 to 3.0 microns=88% 3.0 to 10.0 microns=95%	0.21 in. w.c.	50000293-004 50000293-001 50000293-002 50000293-003 50000293-004 50000293-004	- - - Optional	Optional	Vacuum prefilter=up to 3 months Wash cells=up to 1 year	Yes	Yes	Yes	5 Year	Model 5000	SE 1400 SE 2000 HE1400 HE2000		EACAAXCC0014 EACAAXCC0020	TFE260A9FR4 TFE145A9FR3 TFE175A9FR3 TFE210A9FR3 TFE215A9FR3 TFE235A9FR3 TFE245A9FR3	
	F52F		F300B2012 F52F1048 F52F1055	20X12.5 20X12.5 20X12.5 20X25	Central return grille	1000 CFM 1000 CFM	240V 120V	0.3 to 1.0 microns=73% 1.0 to 3.0 microns=88% 3.0 to 10.0 microns=95%	0.2 in. w.c.	50000293-004		Optional	Vacuum prefilter=up to 3 months Wash cells=up to 1 year	Yes	Yes		5 Year					TFE260A9FR3	
BETTER	F200E	Media	F200E1003 F200E1011 F200E1029 F200E1037	16X20 16X25 20X20 20X25	- Inline air filtration	1200 CFM 1400 CFM 1400 CFM 2000 CFM	-	MERV 11 at 492 FPM 0.3 to 1.0 microns=57% 1.0 to 3.0 microns=82% 3.0 to 10.0 microns=91%	0.22 in. w.c.	FC200E1003 FC200E1011 FC200E1029 FC200E1037	-	Wireless RF with pressure sensor included	Replace filter=up to 1 year				5 Year	Model 2200, 2250, 2400	Air Bear Models: 455602-119 445604- 019 455602-019 447380-002	ACM1000 ACM1400 ACM1600 ACM2000	FILCABCC0016 FILCABCC020 FILCABCC024	Perfect Fit Fami	IV PMAC-12C PMAC-20C
GOOD	F100F	Media	F100F1004 F100F1012 F100F1020 F100F1038 F100F1087 F100F1087 F100F1087 F100F2028 F100F2002 F100F2002 F100F2036 F100F2010 F100F2010 F100F2014 F100F2051	16X20 16X25 20X20 20X25 25X20 25X22 16X25 20X20 25X22 16X25 20X20 25X22 16X25 20X20 20X20 20X25 25X20 25X20 25X20	Inline air filtration	1200 CFM 1400 CFM 2000 CFM 2000 CFM 2000 CFM 1200 CFM 1400 CFM 1400 CFM 2000 CFM 2000 CFM 2000 CFM 2000 CFM		MERV 10 at 492 FPM 0.3 to 1.0 microns=25% 1.0 to 3.0 microns=62% 3.0 to 10.0 microns=85%	0.23 in. w.c.	FC100A1003 FC100A1029 FC100A1011 FC100A1037 FC100A1037		Wireless reminder included	- Replace filter=up to 1 year				5 Year	Model 2200, 2250, 2400	Air Bear Models: 455602-119 445604- 019 455602-019 447380-002	ACM1000 ACM1400 ACM1600 ACM2000	FILCABCC0016 FILCABCC020 FILCABCC024	Perfect Fit Fami	IV PMAC-12C PMAC-20C
GOOD	FC40R	Media	FC40R1094 FC40R1037 FC40R1102 FC40R1102 FC40R1102 FC40R1102 FC40R1102 FC40R1102 FC40R1102 FC40R1045 FC40R1052 FC40R1052 FC40R1060 FC40R103 FC40R1144 FC40R1011 FC40R1059 FC40R1051 FC40R1078 FC40R1078 FC40R1777	12X12 12X24 14X14 14X20 14X24 14X25 14X26 14X27 14X28 14X29 14X24 14X25 14X20 14X24 14X20 16X20 16X25 18X24 20X20 20X24 20X25 20X30 20X36 24X24 24X30	Central return grille	500 CFM 1000 CFM 680 CFM 972CFM 1167 CFM 1215 CFM 1458 CFM 1111 CFM 1389 CFM 1500 CFM 1389 CFM 1667 CFM 2083 CFM 2083 CFM 2500 CFM 2500 CFM		MERV 10 at 492 FPM	0.12 to 0.18 in. w.c.			Optional	Replace filter=up to 1 year				Limited						

Whole-House Humidifiers

Honeywell offers an extensive Whole-House Humidifier product line, including steam, powered and bypass models and replacement pads that are easy to install and built for reliability.

When selecting a Whole-House Humidifier for your next job, look for these Honeywell features:

- Patented PerfectFlo™ Water Distribution Tray
- AgION[™] Anti-Microbial Humidifier Pads
- UV Stabilizer With Carbon Black
- Integrated Damper (Bypass models) • Meets American Lung Association®
- Health House® Guidelines
- 5-Year Warranty



HF440

Clean Steam[™] Power Humidifier

- Up to 12 gallons per day.
- Only steam humidifier with two-stage water treatment.
- Ideal for use in dry climates with mild winters where maximum humidity is needed.
- Offers moisture on-demand with no need for equipment operation. • Safety features include low-water cutoff switch, built-in overflow
- and thermal cutoff switch protection.
- Meets American Lung Association® Health House® guidelines.

HE365

Whole-House Powered Humidifier

- Up to 19 gallons per day.
- Best choice for variable speed and multi-stage systems.
- UV Stabilizer with Carbon Black to help protect from damaging UV exposure.
- PerfectFLO® Tray for even moisture distribution.
- AgION[™] Anti-Microbial Humidifier Pads.
- Meets American Lung Association[®] Health House[®] guidelines.

HE265/225

Whole-House Bypass Humidifier

- 12-17 gallons per day depending on model used.
- Integrated seasonal damper.
- UV Stabilizer with Carbon Black to help protect from damaging UV exposure.
- PerfectFLO[®] Tray for even moisture distribution.
- AgION[™] Anti-Microbial Humidifier Pads.
- Meets American Lung Association[®] Health House[®] guidelines.

Replacement Pads

- Pads feature AgION[™] Anti-Microbial coating to prohibit growth of mold, bacteria and algae.
- Sizes that fit Honeywell and competitive units.

Honeywell



16















Humidifier Selection Guide

	Model	Туре			Features and Functions Humidistat																Warranty		Replacement F	Pads		Upgrade Cro	ss-Reference	
											Humidist	at																
			r Day	e Covered	on Demand	im fan operates	treatment	off switch	istribution Tray		H1008/ Dewpoint Based H	\1008 Iumio	8 dity Co	ontrol		robial Pads	izer	/ Deflector	amper	g Association® Guidelines		nal	robial Pads	ement Pads ire Models	۵	ŋ		-
			Gallons Per Day	Square Footage Covered	Humidity on I	Humidity when system fan operates	Two stage water	Low water cut-off switch	PerfectFlo® Water Distribution Tray	H8908B1002	Dewpoint Control Self Regulates to	Optimize Humidity	Prevent Frost on Windows	Status Indicator LED	Outdoor Sensor Optional	AgION [™] Anti-Microbial Pads	UV Stabilizer	Carbon Black UV Deflector	Integrated Damper	Meets American Lung Association [®] Health House [®] Guidelines		Conventional	AgION [™] Anti-Microbial Pads	Honeywell Replacement Pads Fit These AprilAire Models	Aprilaire	Skuttle	Trion	General
2	HE440A1005	Steam	12	4,000	•		•	•		•										•	5 Year	2 year Filter Pack 32006450-001				Model 60-1		
	HE365A1006	Fan Powered	18	3,000		•			•	•						•	•	•		٠	5 Year	HC26A1008	HC26E1004	350, 360, 560, 568, 600, 700, 760 , 768	Model 700	Model 2002	Model G100	
	HE365AB1004	Flow-Through	18	3,000		•			•		•		•	•	•	•	•	•			5 Year			350, 360, 560, 568, 600, 700, 760 , 768	Model 700	Model 2002	Model G100	
	HE225A1006		12	2,000		•			•	•						•	•	•	•	٠	5 Year	HC22A1007	HC22E1003	110, 220, 550 ,558	Model 550	Model 2000	Model G200	Model 1042
- 0 -	HE225B1004	Bypass	12	2,000		•			•				•	•	•	•	•	•	•		5 Year			110, 220, 550 ,558	Model 550	Model 2000	Model G200	Model 1042
A a	Flow-Through	17	2,800		•			•	•						•	•	•	•		5 Year	HC26A1008	HC26E1004	350, 360, 560, 568, 600, 700, 760 , 768	Model 600	Model 2001	Model G200	Model 1137	
	HE265B1005		17	2,800		•			•		•		•	•	•	•	•	•	•		5 Year			350, 360, 560, 568, 600, 700, 760 , 768	Model 600	Model 2001	Model G200	Model 1137

Ultraviolet Treatment Systems

For one of the most simple and effective ways to improve indoor air quality, Honeywell has a complete offering of both Air (return) and Surface (coil) Ultraviolet Treatment Systems — to zap live airborne particles and surface mold that otherwise thrive in duct systems and on cooling coils.

When choosing a UV Treatment System for your next job, look for these Honeywell features:

- Fastest Installation and Replacement Time Available
- Patented SmartLamp[™] Technology
- Built-in Brownout Protection
- Safety Sealed Design With Multiple Interlocks
- SnapLamp[™] Low-Cost Replacement Bulbs
- Meets American Lung Association® Health House® Guidelines
- 5-Year Warranty



Ultraviolet Air (Return) Treatment Systems

- Kill up to 87% of certain airborne bacteria* passing by the system.
- Available in single and dual-lamp models.
- Optional SmartLamp[™] Technology extends bulb run time and offers LED indication for bulb replacement.
- Meets American Lung Association® Health House® guidelines.

Ultraviolet Surface (Coil) Treatment Systems

- Eliminate up to 99%** of mold spores on cooling coils.
- Optional SmartLamp[™] Technology extends bulb run time and offers LED indication for bulb replacement.
- Sealed design with safety interlocks.
- Meets American Lung Association® Health House® guidelines.

SnapLamp[™] Replacement Bulb

- · Economic lamp replacement solution with separate bulb/handle assembly.
- · Easiest replacement in the industry.



* Test performed shows a single pass kill rate of Serratia marcescens bacteria in a clean metal 12" x 25" duct at an airflow of 2,000 cfm using new lamps.

** Test performed in a test duct showed a 3-log (99.9%) reduction in colony-forming Aspergillus niger mold spores when surface was irradiated at a distance of 18" for three hours in still air using new lamps.

Honeywell







5-YEAR WARRANTY



UV Selection Guide

Model	Appli	cation													Warranty			Upgrade Cr	oss-Referenc	ce		
			tenance	h interlocks	oe in handle	rovides wer cost		SmartL	amp [™] Tecl	hnology			E									
	Air Treatment	Surface Treatment	Quick and Easy install and main	Safety is built into sealed design with interlocks	Check Operation safely with light pipe in handle	SnapLamp [™] replacement bulb provides quick and easy replacement at lower cost	Air Flow Sensor Extends bulb life	Bulb cycles to extend bulb life	Protection from harsh conditions	Bulb life indicator	EnviracCOM [™] communications	Kill Rate*	Recommended Application	Voltage		Ultravation	AprilAire	Field Controls	Sanuvox	Second Wind	Dust Free	Eclipse
UV100E2009	•		•	•	•	•	•	•	•	•	•	87% Air Treatment	Up to 2,000 CFM	120V	5 Year	UVE-1000, UVE-1036, UVE-2000, UVE-2036, UVS-1200 T, UVS-900T	Model 1910, 1930	UV-18X		Model 2181	Nomad, Nomad 2	
 UV100E3007		•	•	•	•	•	•	•	•	•	•	99.9% Surface Treatment	Any Residential System	120V	5 Year	UVE-1000, UVE-1036, UVE-2000, UVE-2036, UVS-1200 T, UVS-900T	Model 1910, 1930	UV-12, UV- 18, UV-28			Triad Flex- Mount,	
UV100E1043	•		•	•	•	•	•	•	•	•	•	70% Air Treatment	Up to 1,600 CFM	120V	5 Year	UVE-1000, UVE-1036, UVE-2000, UVE-2036, UVS-1200 T, UVS-900T	Model 1910, 1930	UV-12, UV- 18, UV-28		Model 2000, 2018	Triad HO, VersaLight	UV Cleanser
 UV100A1059	•	•	•	•	•	•	•	•	•	•	•	75% Air Treatment 99.9% Surface Treatment	Up to 1,725 CFM Air Treatment Surface Treatment – Any Residential System	120V	5 Year	UVE-1000, UVE-1036, UVE-2000, UVE-2036, UVS-1200 T, UVS-900T	Model 1910, 1930	UV-12, UV- 18, UV-28	Saber APR		Triad Flex- Mount,	
UV100A2008	•	•	•	•	•	•	•	•	•	•	•	75% Air Treatment 99.9% Surface Treatment	Up to 1,725 CFM Air Treatment Surface Treatment – Any Residential System	240V	5 Year	UVE-1000, UVE-1036, UVE-2000, UVE-2036, UVS-1200 T, UVS-900T	Model 1910, 1930	UV-12, UV- 18, UV-28	Saber APR		Triad Flex- Mount,	
 Replacement Bulbs			•	•	•	•	•	•	•	•	•				Limited		#90			1068, 1068A, 1076		

* Air treatment test performed shows a single pass kill rate of Serratia marcescens bacteria in a clean metal 12" x 25" duct at an airflow of 2,000 cfm using new lamps. Surface treatment test performed in a test duct showed a 3-log (99.9%) reduction in colony-forming Aspergillus niger mold spores when surface was irradiated at a distance of 18" for three hours in still air using new lamps.

Upgrade Cross-Referen	ice
-----------------------	-----

Whole-House Ventilation Systems

Honeywell offers a variety of Energy-Efficient, Whole-House Ventilation System solutions for both

new construction and retrofit applications. From Heat and Energy Recovery Ventilation to Fresh

Air Supply Ventilation — meet all of your ventilation needs with Honeywell.

When choosing a Ventilation System for your next job, look for these Honeywell features:

- Five Speeds for Specific Demands (HRV/ERV)
- Intelligent Algorithm to Calculate Customized Ventilation Rates (W8150)
- Simple Setup to Meet ASHRAE Ventilation Standards
- Meets American Lung Association[®] Health House[®] Guidelines
- 5-Year Warranty



Proud Partne AMERICAN LUNG ASSOCIATION

The American Lung Association and its

Energy Recovery Ventilation System

- Ultimate in energy-efficient ventilation.
- Best for humid climates unique polymer core helps to reduce humidity.
- Offers five speeds to size for specific demands, or works with W8150 for smart intermittent control.
- Fan timer control options provide opportunity for additional sales.
- Models available with or without frost control

Heat Recovery Ventilation System

- Provides energy-efficient ventilation without security concerns of open windows.
- Offers five speeds to size for specific demands, or works with W8150 for smart intermittent control.
- Best for humidity control in cold climates.
- All models include automatic defrost control.
- Meets American Lung Association® Health House® guidelines.

Fresh Air Ventilation System

- · Economical approach to fresh air ventilation.
- Simple, flexible control helps meet local ventilation codes and ASHRAE standards.
- Easy to wire and troubleshoot.
- Customize ventilation rates for every home environment.
- Meets American Lung Association® Health House® guidelines.

Honeywell

• Meets American Lung Association® Health House® guidelines.















Ventilation Selection Guide

	Model	Туре		Application			Perfor	mance	Features and Functions					Warranty	anty Upgrade Cross-Reference			nce	
			Heat Transfer	Moisture Transfer	Defrost Control	Net Supply Airflow @ 0.2 in. wg	Sensible Recovery Efficiency*	Moisture Transfer Ratio *	Nominal Current @ Max speed (amps)	Fan Speeds	Furnace Fan Interlock	Integral Balancing Dampers	Insulated Cabinet		Venmar	Lifebreath	Broan	Aprilaire	AirCycler
	ER150B2006	Energy Recovery Ventilator	•	•	•	164	79%	26%	1.7	5	Optional	•	•	5 year	AVS Duo 1.4	150 ERVD	ERV100HC		
BEST	ER200B2006	Energy Recovery Ventilator	•	•	•	206	79%	26%	1.7	5	Optional	•	•	5 year	AVS Duo 1.9	200 ERVD	ERV200HC	8100	
	ER150C2004	Energy Recovery Ventilator	•	•		164	79%	26%	1.7	5	Optional	•	•	5 year		150 ERVD			
	ER200C2004	Energy Recovery Ventilator	•	•		206	79%	26%	1.7	5	Optional	•	•	5 year		200 ERV			
BETTER	HR150B1005	Heat Recovery Ventilator	•		•	164	66%		1.7	5	Optional	•	•	5 year	AVS Constructo 1.5 AVS Solo 1.5	155 MAX	HRV100H		
	HR200B1005	Heat Recovery Ventilator	•		•	206	60%		1.7	5	Optional	•	•	5 year	AVS Constructo 2.0 AVS Solo 2.0	200 MAX	HRV200H		
GOOD	Y8150A1009	Economy Ventilation							2.1		•			5 year				8126	
	W8150A1001	Economy Ventilation							2.1		•			5 year				8120	FR-V

* Performance per CAN/CSA-C439-88



Water Solutions

From hydronic heating controls to mixing valves, Honeywell water solutions are built with both customer and contractor satisfaction in mind. All products are engineered for accuracy and safety (key qualities for homeowners) and built for reliability and easy installation (key qualities for your business).

When selecting a potable or hydronic heating product for your next job, look for these Honeywell features:

Application Flexibility

Honeywell

- Single and Dual Certified Thermostatic Mixing Valves
- Teflon[™] Coated Thermostatic Elements
- Industry Leading Zone Valve Technology
- "In-Pipe" Serviceable Air Eliminators
- Customizable Boiler Trim Kits



AMX Series

Thermostatic Mixing Valve

- Patent pending DirectConnect[™] design for fast installation.
- Integrated recirculation port allows for optional recirculation.
- Available in multiple connection types.

AM-1 Series Thermostatic Mixing Valve

- Available in multiple connection types.
- Teflon[®] coating increases product life and reduces callbacks.
- Dual-certification ASSE 1016 and 1017 approved.

UMV Series

UnderSink Thermostatic Mixing Valve

- Designed to prevent scalding at individual faucets.
- Retaining screw provides tamper resistant settings.
- Mounting screw ports for a secure installation.

V8043 5000 Series Zone Valve

- Innovative motor technology reduces call backs.
- Patented Ball Seal Design provides a quality seal.
- "Quick Fit" pushbutton actuator reduces service time.

SuperVent[™] Air Eliminator

- Efficiently removes air from hydronic heating systems.
- Easy "in-pipe" serviceability and maintenance.
- Available in both sweat and NPT connections; sizes 1/2"-2".

Boiler Trim Kits

- All boiler accessories in one convenient kit
- Includes SuperVent™, expansion tank and boiler fill valve/back flow preventer.





















Residential Combustion/Burner/Boiler Controls

Honeywell gas, oil and hydronic controls offer state-of-the-art diagnostic and troubleshooting capabilities that lead to greater productivity. With proven reliability and universal application, you can replace hundreds of Honeywell and competitive models with just a small number of parts.

When selecting a residential combustion/burner/boiler control for your next job, look for these Honeywell features:

- Universal Replacement
- State-Of-The-Art Diagnostics
- Simplified Troubleshooting
- Inventory Reduction
- EnviraCOM[™] Enabled (Oil Primary and Aquastat)



Honeywell

S8610U

Universal Intermittent Pilot Ignition Module

- Provides 24 VAC electronic control for ignition systems used on gas-fired furnaces, boilers and other heating appliances. Single-rod or dual-rod systems. Use with igniter and sensor. Natural or LP Gas.
- Replaces over 300 Honeywell and competitive models.

S8910U

Universal Hot Surface Ignition Module

- Easy field replacement for most hot surface ignition modules.
- Single-rod or dual-rod systems.
- LED diagnostics and field-adjustable ignition timings.
- All adaptation accessories included.
- Replaces over 100 hot surface ignition HSI models.

VR8345M

Universal Electronic Ignition Gas Valve

- Wide-capacity control for almost any IP, HIS, or DSI gas-fired appliances.
- · Compact fit simplifies field replacement.
- Use with 24 VAC heating appliances, using natural, manufactured or LP gas.

VR8200/VR8300 Universal Standing Pilot Gas Valve

- Combination gas controls for use in 24 VAC, gas fired, standing pilot appliances with capacities from 20 to 200 (VR8200) or 30 to 300 (VR8300) cfh.
- Includes safety shutoff (VR8300), manual valve, two automatic operators, pressure regulator and pilot adjustment.
- Universal replacement for virtually all Honeywell and competitive valve models.

R7184U Interrupted Electronic Oil Primary

- Universal replacement for hydronic and forced air systems.
- Features include: interrupted ignition, limited reset and recycle, diagnostic LED, pump priming cycle, displays cad cell resistance, valve-on and blower motor-off delay, disable function and alarm contacts.
- EnviraCOM[™] enabled.

L7224U

Universal Aquastat

- Universal replacement for more than 40+ Honeywell aquastats.
- Improved terminal layout and multiple knockouts make change-outs a snap.
- Vertical, horizontal, and flush-mount options. Configurable for single-function use.
- Multi-function display offers setpoint, temperature and diagnostic information.
- EnviraCOM[™] Enabled.









