



FEATURES & SPECIFICATIONS

INTENDED USE

For use with housings LCP, LC6, L7XPR, L7X, L7XR and L7XF.

CONSTRUCTION

Aluminum one-piece reflector.

White polyester powder coat paint.

Antique bronze, oil-rubbed bronze, brushed nickel and white finishes are one piece aluminum with integral flange.

INSTALLATION

Socket to trim interface.

Retaining clips riveted to top of reflector hold trim inside housing.

LISTING

UL Listed to U.S. and Canadian safety standards.


Damp location listed.

Catalog Number	
Notes	Type

6" Finishing Trim

C01

OPEN SHALLOW
Wide Flange




Specifications

Height: 5-7/8 (14.9)

Lamp opening: 4-1/4 (10.8)

Diameter: 7-3/4 (19.7)



All dimensions are inches (centimeters).

ORDERING INFORMATION

For shortest lead times, configure product using **standard options (shown in bold)**.

Example: **C01**

C01	
Series	Finish
C01	(blank) White BN Brushed nickel ORB Oil-rubbed bronze BZA Antique bronze

Options
TRBL Black integral flange ring

Housing Compatibility

Housing and trim ordered separately.

Application	Source	Maximum wattage	Housing
IC	Incandescent	75 PAR30 <i>short neck</i>	LCP, LC6, L7XPR, L7X, L7XR
		65 BR30	LCP, LC6, L7XPR, L7X, L7XR
		60 A19	LCP, LC6, L7XPR, L7X, L7XR
	Fluorescent	13DTT	L7XF

