

# ElectriFLEX LD™ Commercial Electric Water Heaters

**Bradford White's space saving ElectriFLEX LD™ (Light Duty) Commercial Electric Water Heaters offer superior flexibility with multiple conversion options.**



- Save time and money with ElectriFLEX LD™ models that are ETL Certified for Quick Supply House or Field Conversion to your requirements
- Maximum Flexibility with 16 different wattages (1.5kW - 12kW\*) and factory set voltages that are convertible to or from 120V, 208V, 240V, 277V and 480V
- No kit required for conversion from Three Phase to Single Phase or from Non-Simultaneous to Simultaneous operation saving the installer time
- Voltage and kW input conversion kits allow a maximum number of configurations
- Perfect for multiple applications including Strip Malls, Gas Stations, Fast Food Restaurants, and more

\*Dual element models only. Single element models have ten inputs available from 1.5 kW – 6 kW. LE16U and LE112T have four inputs available from 1.5 kW – 3kW.

Committed to the Professional.

  
**BRADFORD WHITE®**  
WATER HEATERS  
[www.bradfordwhite.com](http://www.bradfordwhite.com)

# With Bradford White's Upright, Utility, Lowboy, and Wall Hung ElectriFLEX LD™ (Light Duty) Commercial Electric models, you'll find a configuration to fit just about anywhere.

## ElectriFLEX LD™ Specifications

### Upright Models

Model Number	Capacity	Recovery at 100°F Rise	Floor to Top of Heater	Jacket Dia.	Approx. Shipping Weight
	U.S. Gal.	U.S. GPH	in.	in.	lbs.
LE230S3-3	30	18	46 <sup>7</sup> / <sub>8</sub>	18	85
LE240S3-3	40	18	46 <sup>7</sup> / <sub>8</sub>	20	103
LE250S3-3	50	18	46 <sup>1</sup> / <sub>2</sub>	22	130
LE265T3-3	65	18	59 <sup>1</sup> / <sub>4</sub>	22	156
LE280T3-3	80	18	59 <sup>1</sup> / <sub>4</sub>	24	183
LE2120T3-3	119	18	62 <sup>3</sup> / <sub>4</sub>	28	305

### Lowboy Models

Model Number	Capacity	Recovery at 100°F Rise	Floor to Top of Heater	Jacket Dia.	Approx. Shipping Weight
	U.S. Gal.	U.S. GPH	in.	in.	lbs.
LE120L3-3	19	18	24 <sup>3</sup> / <sub>4</sub>	18	58
LE130L3-3*	30	18	29 <sup>3</sup> / <sub>4</sub>	20	86
LE140L3-3*	40	18	31 <sup>1</sup> / <sub>4</sub>	22	115
LE150L3-3*	47	18	31 <sup>3</sup> / <sub>4</sub>	24	140

### Utility Models

Model Number	Capacity	Recovery at 100°F Rise	Floor to Top of Heater	Jacket Dia.	Approx. Shipping Weight
	U.S. Gal.	U.S. GPH	in.	in.	lbs.
LE16U3-1	6	6	16 <sup>1</sup> / <sub>2</sub>	14	33
LE110U3-1	10	6	17 <sup>1</sup> / <sub>2</sub>	16	48
LE112T3-1	12	6	27 <sup>3</sup> / <sub>4</sub>	14	48
LE115U3-1	15	6	20 <sup>1</sup> / <sub>4</sub>	18	55
LE120U3-1	19	6	24 <sup>3</sup> / <sub>4</sub>	18	59

### Wall Hung Models

Model Number	Capacity	Recovery at 100°F Rise	Floor to Top of Heater	Jacket Dia.	Approx. Shipping Weight
	U.S. Gal.	U.S. GPH	in.	in.	lbs.
LE16WV3-1	6	6	15 <sup>3</sup> / <sub>4</sub>	14	33
LE112WV3-1	12	6	16 <sup>3</sup> / <sub>8</sub>	18	48
LE120WV3-1	19	6	24 <sup>3</sup> / <sub>8</sub>	18	59

Note: For additional voltage and wattage availability for all models please reference specification sheet or consult factory. These models are not recommended for sanitation purposes.

\* This Lowboy model is provided with an additional insulation blanket.



Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement.

### FEATURES FOR THE SUPPLIER AND INSTALLER:

- Numerous configurations using the conversion kits
- Minimize warehouse space required for storage
- Reduces dollars tied up in inventory
- One model can solve multiple application requirements
- Conversion kits can be shipped FED EX or UPS
- Easy conversion of voltage, phase, and kW input

**All models can be easily converted by a qualified installer at the supply house or in the field.**



Need to compare a competitive model? Download our Cross Reference app! You can also use the RightSpec® Cross Reference guide at [www.bradfordwhite.com](http://www.bradfordwhite.com).



Built to be the Best™ | 800.523.2931

©2017, Bradford White Corporation. All rights reserved.

EFLEXLD-SS 1017

