

PFX146

Stainless Steel and PVC Ice Maker

Reinforced Flexible Connectors



Product Features

- Working Temperature: 40°F to 140°F
- Working Pressure: up to 125 PSI maximum
- Internal Hose: reinforced PVC
- Outer Wire Braid: 304 stainless steel (not applicable to PVC connector – PFX146198)
- Barb: low lead brass alloy
- Metal Nuts: nickel-plated brass alloy
- Ferrule: nickel-plated brass alloy
- Washer: EPDM rubber



PFX146198

Installation Instructions

- For use with water in accessible locations only
- Metal Nuts: hand tighten plus 1/4 turn with wrench
- Do not over tighten nuts
- Check for leaks before leaving job site
- Inspect regularly for general fitness and replace if damaged, corroded or worn
- Do not expose to corrosive chemicals



PFX146205

Models and Product Certifications

Model #	Description	cUPC	UPC	Low Lead Compliant
PFX146198	1/4" COMP X 1/4" COMP X 60" PVC Ice Maker		✓	✓
PFX146202	1/4" COMP X 1/4" COMP X 24" SS Ice Maker	✓	✓	✓
PFX146205	1/4" COMP X 1/4" COMP X 60" SS Ice Maker		✓	✓
PFX146207	1/4" COMP X 1/4" COMP X 84" SS Ice Maker		✓	✓

Warranty and Listing Certification

This PROFLO product carries a 1-year limited warranty.
IAPMO listed to ASME A112.18.6-2009 and CSA B125.6-2009
IAPMO listed to NSF/ANSI 61 and NSF/ANSI 372