

PFX146

Stainless Steel and PVC Toilet

Reinforced Flexible Connectors



Product Features

- Working Temperature: 40°F to 140°F
- Working Pressure: up to 125 PSI maximum
- Internal Hose: reinforced PVC
- Outer Wire Braid: 304 stainless steel (not applicable to PVC connector – PFX146172)
- Barb: low lead brass alloy
- Metal Nuts: nickel-plated brass alloy
- Ferrule: nickel-plated brass alloy
- Washer: Santoprene/EPDM rubber



PFX146172



PFX146463

Installation Instructions

- For use with water in accessible locations only
- Metal Nuts: hand tighten plus 1/4 turn with wrench
- Plastic Nuts: hand tighten only and do not use tools
- Do not over tighten nuts
- Check for leaks before leaving job site
- Inspect regularly for general fitness and replace if damaged, corroded or worn
- Do not expose to corrosive chemicals



PFX146472

Models and Product Certifications

Model #	Description	cUPC	UPC	Low Lead Compliant
PFX146172	3/8" COMP X 7/8" BALLCOCK X 12" PVC Toilet	✓	✓	✓
PFX146462	1/2" FIP X 7/8" BALLCOCK X 12" SS Toilet	✓	✓	✓
PFX146463	1/2" FIP X 7/8" BALLCOCK X 16" SS Toilet	✓	✓	✓
PFX146471	3/8" COMP X 7/8" BALLCOCK X 9" SS Toilet	✓	✓	✓
PFX146472	3/8" COMP X 7/8" BALLCOCK X 12" SS Toilet	✓	✓	✓
PFX146473	3/8" COMP X 7/8" BALLCOCK X 16" SS Toilet	✓	✓	✓
PFX146474	3/8" COMP X 7/8" BALLCOCK X 20" SS Toilet	✓	✓	✓
PFX146492	1/2" COMP X 7/8" BALLCOCK X 12" SS Toilet	✓	✓	✓

Warranty and Listing Certification

This PROFLO product carries a 1-year limited warranty.
IAPMO listed to ASME A112.18.6-2009 and CSA B125.6-2009
IAPMO listed to NSF/ANSI 61 and NSF/ANSI 372