

ADJUSTABLE NOZZLES

For use on Class A and B fires. Commonly used on hose assemblies.

STANDARD EQUIPMENT: Cast Brass Satin Finished nozzle with adjustable Fog, Straight Stream and Shut-Off features.



3460 Series

U/L LISTED

Without Rubber Bumper	
Size	Figure No.
1 1/2"	*3460

Optional Finishes	
Use suffix	For Finish
PB	Pol. Brass
RC	Rgh. Chrome
PC	Pol. Chrome

With Rubber Bumper	
Size	Figure No.
1"	3462
1 1/2"	*3463
2 1/2"	3464




3463 Series

U/L LISTED

SPECIFY: Figure No. - Size - Finish - Thread

ADJUSTABLE "ALL-FOG" NOZZLES FOR ELECTRICAL APPLICATIONS

For use on Class A, B, and C fires and in electrical hazard areas at distances greater than 10 feet, and when voltage level is under 250,000 volts. Adjustable thru varying fog patterns to shut-off. No Straight-stream feature.



3467 Series

STANDARD EQUIPMENT: Red Polycarbonate Plastic Nozzle with Rubber Bumper.

Size	Figure No.
1 1/2"	3467

THREADS AVAILABLE
NYT,NST,NPSH

SPECIFY
THREAD

STANDARD EQUIPMENT: Cast Brass Satin Finish with Rubber Bumper.

Size	Figure No.
1 1/2"	3470
2 1/2"	3471

U/L LISTED

Optional Finishes	
Use suffix	For Finish
PB	Pol. Brass
RC	Rgh. Chrome
PC	Pol. Chrome

SPECIFY
THREAD



3470 Series

POWER FOG NOZZLE

For use on Class A and B fires. Varying fog patterns, adjusts from full cone fog to straight stream. Quick shut-off handle for positive control of water flow. Constant flow maintained at 100 P.S.I. regardless of adjustment.

STANDARD EQUIPMENT: Polished Brass Nozzle with all position indicator stamped on sleeve.



3473 Series

SPECIFY
THREAD

Size	Figure No.
1 1/2"	3473
2 1/2"	3474

Optional Finishes	
Use suffix	For Finish
PC	Pol. Chr.

POLYCARBONATE FOG NOZZLE

For Use on Class A & B Fires. Has adjustable fog, straight stream and shut-off features. **STANDARD EQUIPMENT:** Red Polycarbonate Plastic fog Nozzle with Rubber Bumper.



3478 Series

SPECIFY
THREAD

Size	Figure No.
1"	3477
1 1/2"	3478
2 1/2"	3479

THREADS AVAILABLE
NYT,NST,NPSH