



QUICK TOOL REFERENCE GUIDE

MASONRY/CONCRETE DRILLING

ITEM#	1191VSRK	HD18-2	HD21-2	11250VSR/11250VSRD	GBH2-26
	BULLDOG				
DRIVE SYSTEM					
HAMMER CLASSIFICATION	Hammer Drill	Hammer Drill	Hammer Drill	Rotary	Rotary
AMPERAGE	7.0	8.5	9.2	6.1	8.0
IMPACT ENERGY* (FT.-LBS.)	–	–	–	1.7 EPTA	2.0 EPTA
MAX. CAPACITY—CONCRETE/MASONRY	5/8"	3/4"	7/8" / 1"	7/8"	1"
OPTIMAL RANGE	1/8"–5/16"	1/8"–3/8"	1/8"–1/2"	5/32"–5/8"	3/16"–5/8"
CORE BITS	–	–	–	1-1/2"	2-5/8"
NO LOAD RPM	0–3,000	0–1,200/0–3,200	0–900/0–3,000	0–1,000	0–1,300
NO LOAD BPM	0–48,000	0–19,550/0–51,000	0–15,300/0–51,000	0–4,400	0–5,100
VIBRATION CONTROL	–	–	–	No	No
**VIBRATION LEVELS M/S ²	–	–	–	Drilling: 16.0/15.5	Drilling: 17.5 Chiseling: 9.5
MODES OF OPERATION	Hammer Drill Rotation Only	Hammer Drill Rotation Only	Hammer Drill Rotation Only	Rotary Hammer Rotation Only	Rotary Hammer Hammer Only Rotation Only
LENGTH	11.0"	13.4"	13.5"	14.0"/19.6"	15.0"
WEIGHT	4.1 lbs.	5.8 lbs.	5.9 lbs.	5.5 lbs./7.4 lbs.	6.4 lbs.

*Based on EPTA (European Power Tool Association) guidelines

ITEM#	11255VSR	GBH2-28L	RH328VC/RH328VCQ	RH432VCQ
	BULLDOG Xtreme			
DRIVE SYSTEM				
HAMMER CLASSIFICATION	Rotary	Rotary	Rotary	Rotary
AMPERAGE	8.0	8.5	8.0	8.5
IMPACT ENERGY* (FT.-LBS.)	2.0 EPTA	2.4 EPTA	2.4	3.1 EPTA
MAX. CONCRETE CAPACITY	1"	1-1/8"	1-1/8"	1-1/4"
OPTIMAL RANGE	3/16"–5/8"	3/16"–3/4"	1/4"–7/8"	3/8"–1"
CORE BITS	2-5/8"	2-3/4"	3-1/8"	3-1/2"
NO LOAD RPM	0–1,300	0–1,300	0–900	0–760
NO LOAD BPM	0–5,800	0–5,100	0–4,000	0–3,600
VIBRATION CONTROL	No	Hammer Mechanism and Counter Balance	Hammer Mechanism and Handle	Hammer Mechanism and Handle
**VIBRATION LEVELS M/S ²	Drilling: 15.0 Chiseling: 12.0	Drilling: 11.0 Chiseling: 11.0	Drilling: 14.5/10.0 Chiseling: 13.0/9.5	Drilling: 12.0 Chiseling: 9.0
MODES OF OPERATION	Rotary Hammer Hammer Only Rotation Only			
LENGTH	17.3"	17.4"	12.5"/13.6"	15.75"
WEIGHT	6.7 lbs.	6.9 lbs.	7.7/7.9 lbs.	10.3 lbs.

*Based on EPTA (European Power Tool Association) guidelines

**Per EPTA EN 60745

Cordless Quick Tool Reference Guide available on pages 71–75.



1" SDS-plus® BULLDOG™ XTREME ROTARY HAMMER

GBH2-26



NEW



- ▶ Multi-Function Selector—Three modes of operation: rotary hammer, rotation only and hammer only
- ▶ Vario-Lock Positioning—Rotates and locks chisel into 36 different positions to optimize working angle
- ▶ Variable-Speed Trigger with Reversing—For accurate bit starting as well as removing fasteners or bound bits
- ▶ Integral Clutch—Disengages torque transmission if the bit gets into a bind situation

INCLUDES

Auxiliary Handle **1612025057**
 Depth Gauge **1613001010**
 Carrying Case **2605438294**

SPECIFICATIONS

RATING	120V
AMPERAGE	8.0
NO LOAD RPM	0–1,300
NO LOAD BPM	0–5,100
IMPACT ENERGY (FT.-LBS.)	2.0 EPTA
MAXIMUM CAPACITIES: CONCRETE	1"
MAXIMUM CAPACITIES: STEEL	1/2"
MAXIMUM CAPACITIES: WOOD	1"–1-1/4"
MAXIMUM CAPACITIES: CONCRETE-THIN WALL CORE BIT	2-5/8"
LENGTH	15.0"
WEIGHT	6.4 lbs.

Dust collection attachments available on pages 15, 23, 320 and 324.

MASONRY/CONCRETE DRILLING
SDS-plus® ROTARY HAMMERS

1" SDS-plus® BULLDOG™ XTREME ROTARY HAMMER

11255VSR



- ▶ Multi-Function Selector—Three modes of operation: rotary hammer, rotation only and hammer only
- ▶ Vario-Lock Positioning—Rotates and locks chisel into 36 different positions to optimize working angle
- ▶ Integral Clutch—Disengages torque transmission if the bit gets into a bind situation
- ▶ Variable-Speed Trigger with Reversing—For accurate bit starting as well as removing fasteners or bound bits

INCLUDES

Auxiliary Handle **1612025057**
 Depth Gauge **1613001010**
 Carrying Case **2610958165**



Cordless option available on pages 106–107.

SPECIFICATIONS

RATING	120V
AMPERAGE	8.0
NO LOAD RPM	0–1,300
NO LOAD BPM	0–5,800
IMPACT ENERGY (FT.-LBS.)	2.0 EPTA
MAXIMUM CAPACITIES: CONCRETE	1"
MAXIMUM CAPACITIES: STEEL	1/2"
MAXIMUM CAPACITIES: WOOD	3/4"–1"
MAXIMUM CAPACITIES: CONCRETE-THIN WALL CORE BIT	2-5/8"
LENGTH	17.3"
WEIGHT	6.7 lbs.

Dust collection attachments available on pages 15, 23, 320 and 324.

1-1/8" SDS-plus® BULLDOG™ XTREME MAX ROTARY HAMMER

GBH2-28L



NEW



- ▶ Multi-Function Selector—Three modes of operation: rotary hammer, rotation only and hammer only
- ▶ Counter Balance Vibration—Vibration reduction in the hammer mechanism for lowest vibration levels in its class
- ▶ KickBack Control—Limits rotation of tool in a bind situation
- ▶ Integral Clutch—Disengages torque transmission if the bit gets into a bind situation
- ▶ Variable-Speed Trigger with Reversing—For accurate bit starting as well as removing fasteners or bound bits

INCLUDES

Auxiliary Handle **1612025057**
 Depth Gauge **1613001010**
 Carrying Case **2610958165**

HammerHook for quick on-the-job storage



SPECIFICATIONS

RATING	120V
AMPERAGE	8.5
NO LOAD RPM	0–1,300
NO LOAD BPM	0–5,100
IMPACT ENERGY (FT.-LBS.)	2.4 EPTA
MAXIMUM CAPACITIES: CONCRETE	1-1/8"
MAXIMUM CAPACITIES: STEEL	1/2"
MAXIMUM CAPACITIES: WOOD	1-1/4"
MAXIMUM CAPACITIES: CONCRETE-THIN WALL CORE BIT	2-3/4"
LENGTH	17.4"
WEIGHT	6.9 lbs.

Dust collection attachments available on pages 15, 23, 320 and 324.

SDS-plus® CHUCKS AND ADAPTERS



SDS-plus® RIGHT-ANGLE ATTACHMENT



- ▶ Easily drill into concrete in hard-to-reach spots. Pivots 360° ensuring correct positioning for any application
- ▶ Impact strength of tool is reduced by approximately 40%
- ▶ Replacement spacer rings sold separately (2916660015, 2916660016)

ITEM #	DESCRIPTION
RHA-50	Right-angle attachment compatible with 11253VSR, 11255VSR, RH228VSR, RH328VSR, 11536VSR and RH328VC-36
1618580000	Right-angle attachment compatible with 11224VSR and 11250VSR (only)

KEYLESS THREE-JAW CHUCK WITH SDS-plus® SHANK


- ▶ 1/2 In. capacity three-jaw chuck with SDS-plus® shank
- ▶ Keyless ratcheting to quickly lock bits in place
- ▶ For use with straight shank drill bits
- ▶ Can be used in the drill-only mode



ITEM #	DESCRIPTION
HA3JAW	Keyless three-jaw chuck with SDS-plus® shank

THREE-JAW CHUCK WITH INTEGRAL SDS-plus® SHANK

- ▶ 1/2 In. capacity chuck with integral SDS-plus® shank
- ▶ Use for straight shank drill bits
- ▶ Can be used in the drill-only mode
- ▶ For all Bosch SDS-plus® rotary hammers



ITEM #	DESCRIPTION
1618571014	Keyed three-jaw chuck with SDS-plus® shank

MASONRY/CONCRETE DRILLING
SDS-plus® ROTARY HAMMER ACCESSORIES

DUST COLLECTION ATTACHMENTS



DUST EXTRACTION ATTACHMENT

- ▶ Attaches to tool and vacuum cleaner hose to provide excellent dust collection when drilling in dust-sensitive areas, such as computer rooms and medical facilities
- ▶ For use with bits up to 3/4 In. in diameter for extracting fine dust
- ▶ Built-in depth gauge
- ▶ For use with most Bosch SDS-plus® rotary hammers
- ▶ Compatible with 11253VSR, 11255VSR, RH228VC, RH328VC, 11536VSR, 11536C, RHH181-01 and RH328VC-36 (see page 128).

ITEM #	DESCRIPTION
HDC100	SDS-plus® depth control dust extraction unit



HDC200

HDC250

HAMMER DRILLING DUST EXTRACTION ATTACHMENTS

- ▶ Dust extraction attachments for drilling holes in concrete and masonry
- ▶ Can be used with a wide variety of drill bit diameters and bit lengths
- ▶ For use with Bosch SDS-max® or SDS-plus® combination/rotary hammer
- ▶ Includes adapter VAC020

ITEM #	DESCRIPTION
HDC200	Optimized for 1/4"-1-3/8" diameter. Maximum hole diameter is 2-5/8"*
HDC250	Optimized for 2-1/4"-5" diameter. Maximum hole diameter is 6"*

*Brush ring needs to be removed



BOSCH
Invented for life