






SUBSURFACE DRAINAGE & INFILTRATION



THE NDS SOLUTION

Whether you need a dry well, French drain or infiltration trench, NDS has you covered with innovative and proven subsurface drainage and stormwater infiltration products. EZflow® French drain system, NDS® StormChamber® and Flo-Well® dry well provide trusted performance for multiple applications and are lightweight and easy to install. These engineered solutions are proven time-and-labor savers that outperform traditional systems in flow through and storage capacity. When performance and sustainability matter, NDS solutions are the preferred choice of contractors, engineers and landscape architects. EZflow®, NDS® StormChamber® and Flo-Well® are made in the USA and each contribute to project LEED credits when used as part of the stormwater management design and by contributing to the proportion of recycled materials.







EZflow®

EZflow® offers an engineered and gravel-free alternative to a traditional French Drain system. EZflow® can be used to lower subsurface groundwater elevations; protecting property and improving the health of playing fields and planted areas. It can also be used as an infiltration trench for managing stormwater runoff. Available in multiple diameters with or without pipe, this versatile product is an effective component of subsurface drainage and infiltration systems.

- · Installs in half the time of traditional gravel systems
- Better flow capacity than traditional stone-and-pipe systems
- Up to H-10 load rating with 12" of compacted soil cover
- · Over 100 million linear feet installed

NDS® StormChamber®

Stormwater chambers provide a lower cost alternative to drainage pipes for conveyance, with added benefits of groundwater recharge and water quality enhancement. Stronger and easier to maintain, NDS® StormChamber® is the ideal solution for stormwater detention and/or infiltration, providing easy installation and design flexibility to meet target stormwater runoff rates, volume control and water quality requirements.

- Thermo-formed high density weight polyethylene HMWPE material won't crack
- 100-year life expectancy Longest on the market
- Saves time and money offers the lowest installed cost
- Proprietary SedimenTrap[™] offers centralized sediment control, gathering sediment and pollutants in one place for quick removal by vacuum truck.

Flo-Well®

Flo-Well® engineered dry well presents an easy to install and sustainable solution for managing stormwater runoff. Flo-Well® is a gravel-free alternative to a traditional dry well with up to 250% more detention volume. Used independently or as part of a larger system, Flo-Well® units collect and detain stormwater allowing for groundwater recharge. Units are modular and can be connected in series or stacked to meet a variety of project needs.

- Up to 50 gallons of detention volume per unit
- · Connect units in series for larger volumes or stack for reduced footprint
- Fast and easy installation with no heavy equipment or gravel needed
- Manufactured from 100% recycled materials



EZFLOW®: A BETTER FRENCH DRAIN



Gravel-free installation provides up to 50% labor savings over traditional systems


Better flow through and detention volume than traditional systems

Durable with a 100-year lifespan


Projects qualify for LEED credits

EZflow® Drainage Bundles


EZflow® drainage bundles are 10 feet in length with a slotted pipe surrounded by expanded polystyrene aggregate and enclosed in geotextile mesh. Configurations are available in 7-inch bundles with or without a 3-inch pipe, 10-inch bundles with or without a 4-inch pipe, and 15-inch bundles with or without a 6-inch pipe. Accessories include 3-inch, 4-inch, and 6-inch internal couplers and end caps. EZflow® bundles can also be used with internal tees, and internal wyes. The 15-inch bundles are available with the pipe located in the center or bottom of the bundle for varying applications. Unless specifically required by code or other requirement, the pipe can be either centered or at the bottom of the bundle.




Applications




French/Interceptor Drains



Planter/Retaining Walls



Foundation Drains



Basement/Crawlspace

EZflow® drainage systems are appropriate for a wide range of applications and are a convenient alternative to traditional stone and pipe drainage, storage and infiltration systems. EZflow® drainage systems can be used as a substitute for stone in most applications where the stone is not utilized for structural support. A professional engineer, landscape architect or other qualified design professional should be consulted for complex applications.

Product selection is relative to the desired application and benefits from establishing anticipated flow into, through and out of a proposed drainage system configuration. Selection considerations include: bundle sizing and storage volume, the presence or absence of pipe, pipe size and location within the bundle, and arrangement of bundles. Design factors may include: length of system, watershed area, soil type and permeability, groundwater levels and system discharge opportunities. EZflow® drainage storage volumes and pipe discharge rates are listed on the next page.

EZFLOW® ENGINEERED FRENCH DRAIN

EZflow® Gravel-Free French Drain





Part No.	Description	Color	Bundle size/ Linear Feet	Wt. per Bundle (lbs.)	Product Class	Specifications	
EZ-0701F	7" mesh with 3" slotted pipe (center)	Black	90	32.4	11RP	10 ft. polyethylene slotted drain pipe surrounded by	
EZ-1001F	10" mesh with 4" slotted pipe (center)	Black	50	29.5	11RP	100% recycled polystyrene aggregate and enclosed	
EZ-1501F	15" mesh with 6" slotted pipe (center)	Black	20	26.0	11RP	in 30-sieve polyethylene geotextile mesh.	
EZ-0701A	7" mesh without pipe – aggregate only	Black	90	18.0	11RP	10 ft. segment of 100% recycled polystyrene	
EZ-1001A	10" mesh without pipe – aggregate only	Black	50	13.5	11RP	aggregate only, enclosed in 30-sieve polyethylene	
EZ-1501A	15" mesh without pipe – aggregate only	Black	20	12.4	11RP	geotextile mesh.	

EZflow® Internal Couplings & End Caps





Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class
3C05	3" Corrugated Internal Coupling	Black	60/box	0.30	11RP
4007	4" Corrugated Internal Coupling	Black	36/box	0.30	11RP
6007	6" Corrugated Internal Coupling	Black	12/box	0.80	11RP
3C06	3" Corrugated End Cap	Black	33/box	0.30	11RP
4C06	4" Corrugated End Cap	Black	21/box	0.50	11RP
6006	6" Corrugated End Cap	Black	15/box	0.50	11RP

Storage & Flow for EZflow® Drainage Bundles (45% void space among consolidated EPS aggregate)

Pipe Bundles									
Product	Storage Volume (gallons/10 ft. bundle)	Flow Capacity (gpm @ 1% slope)							
EZ-0701F	11.4	80.8							
EZ-1001F	21.5	130.9							
EZ-1501F	45.8	345.0							



EZ-1501	
15"	
6" PIPE (CENTERED)	

Aggregate-Only Bundles									
Product	Storage Volume (gallons/10 ft. bundle)	Flow Capacity (gpm @ 1% slope)							
EZ-0701A	8.8	37.1							
EZ-1001A	17.2	75.7							
EZ-1501A	36.5	170.3							





NDS® STORMCHAMBER®: THE MOST COST-EFFECTIVE CHAMBER SOLUTION



NDS® StormChambers® are subsurface structures that are used to collect, retain and discharge stormwater on commercial and residential sites. They provide a lower cost alternative to drainage pipes for conveyance, with the added benefits of groundwater recharge and water quality enhancement.

Stronger & Easier to Maintain - High Volume Stormwater Retention

NDS® StormChamber® is the most cost-effective chamber solution on the market. Thermo-formed from high density weight polyethylene HMWPE material, it offers superior strength that won't crack even under the most extreme environments. Designed for fast installation and simple maintenance, NDS® StormChamber® is ideal for roadways, parking lots and fields and can stack, allowing for deeper installation and a smaller footprint.

Key Benefits:




Strong, Flexible & Durable

- Meets H-20 standards
- Up to 16' cover when deep installs are required for the 34". Up to 12' for the 44"
- 100-Year Life Expectancy
- Withstands the most extreme environments
- Material bends instead of breaks, giving it a brittleness temperature of -107° F vs. industry average of -2° F



Fast Installation

- Built-in end walls
- No header pipe manifold system required
- Flexible design
- · Lowest installed cost



Simple Maintenance

- Differentiated and centralized sediment control
- SedimenTrap™ gathers sediments and other pollutants in one place for quick, easy and inexpensive removal by vacuum truck



Stacks


- 34" Chambers: Capable of 3-layer stacking
- 44" Chambers: Contact NDS DesignWorx for any projects that may need stacking
- We offer expert site-specific design guidance based on 20 years of successful completion of projects

NDS® STORMCHAMBER®


NDS® StormChamber®



						Weight		Product
Part No.	Description	Color	Length	Width	Height	(lbs.)	Per Pallet	Class
SC-3475W-S-0	75CUFT START CHAMBER100X60X34	Orange	100"	60"	34"	90	40	10SC
SC-3475W-E-0	75CUFT END CHAMBER100X60X34	Orange	100"	60"	34"	90	40	10SC
SC-3475W-M-0	75CUFT MIDDLE CHAMBER100X60X34	Orange	100"	60"	34"	90	40	10SC
SC-3475W-C-0	75CUFT CLOSED CHAMBER100X60X34	Orange	100"	60"	34"	90	40	10SC
SC-3475-S-0	75CUFT START CHAMBER102X60X34	Orange	102"	60"	34"	100	30	10SC
SC-3475-E-0	75CUFT END CHAMBER102X60X34	Orange	102"	60"	34"	100	30	10SC
SC-3475-M-0	75CUFT MIDDLE CHAMBER102X60X34	Orange	102"	60"	34"	100	30	10SC
SC-3475-C-0	75CUFT CLOSE CHAMBER102X60X34	Orange	102"	60"	34"	100	30	10SC
SC-44105-S-0	105CUFT START CHAMBER90X78X44	Orange	90"	78"	44"	120	20	10SC
SC-44105-E-0	105CUFT END CHAMBER90X78X44	Orange	90"	78"	44"	12	20	10SC
SC-44105-M-0	105CUFT MID CHAMBER90X78X44	Orange	90"	78"	44"	12	20	10SC
SC-44105-C-0	105CUFT CLOSE CHAMBER90X78X44	Orange	90"	78"	44"	12	20	10SC
SC-1820-S-0	20CUFT START CHAMBER 18"	Orange	100"	37"	18"		45	10SC
SC-1820-E-0	20CUFT END CHAMBER 18"	Orange	100"	37"	18"		45	10SC
SC-1820-M-0	20CUFT MIDDLE CHAMBER 18"	Orange	100"	37"	18"		45	10SC
SC-1820-C-0	20CUFT CLOSED CHAMBER 18"	Orange	100"	37"	18"		45	10SC
SC-ST	SEDIMENT TRAP	Orange	47" OD	_	2'	3	4	10SC
SC-NWFF-500	FILTER FABRIC NON-WOVEN LIGHT	Orange	360'	12.5'	1.5' OD roll	220	3	10SC
SC-WFF-75	STABILIZATION FABRIC WOVEN MEDIUM	Orange	75'	7.5'	0.75' OD roll	75	16	10SC
SC-CF-E	CINTOFLEX NETTING	Orange	330'	6.5'	0.75' OD roll	7	12	10SC
SC-FL-8	8" FRAME AND LID	Orange	10" OD	-	3"	20	-	10SC
SC-FL-10	10" FRAME AND LID	Orange	20" OD	_	3"	24	-	10SC
SC-3020P	30" X 20" HDPE PIPE	Orange	36" OD	-	20"	45	4	10SC



NDS® StormChamber® Elevated View





FLO-WELL®: A BETTER DRY WELL



With the Flo-Well®, water can now be infiltrated into the subsoil rapidly and easily. Unlike competitive systems, there is no need for piping systems to transport stormwater to a far-off discharge point, large heavy equipment, considerable excavation of current landscaped areas, nor large labor costs that those systems incur. With Flo-Well, water infiltration is now easier than ever.

Options

Larger 9" or 12" grates can be added to Flo-Well to manage surface water.

This option is ideal for draining:
Golf course areas prone to puddling

Playground areas under slides and swings

Outdoor drinking fountain runoff

Outdoor showers at beaches

Wash-down areas

Ideal as a stand-alone drain:

Disturbs only 4 square feet of turf to install

Requires less than 10 cubic feet of soil removed to bury

Measures only 24" in diameter by 28.75" high

Weighs only 22 pounds

Holds over 48 gallons. Or, connect to existing system for increased drainage capabilities

Ideal as a stand-alone reservoir:

Collect and hold rainwater for lawn and garden irrigation (used with a pump connected to a garden hose)

Connect Flo-Well to rain gutters using a catch basin & grate below each downspout (see drawing)


Ideal solution for arid areas impacted by drought

Reservoir for pond and waterfall recirculation pumps




Stackable & Expandable

Flo-Well® can be used individually, connected in series or in any array, and can be stacked up to 4 units high (with center support pipe).








Stacked


Applications




For gutters and downspouts



Install with sump pumps



Eliminates puddles



Backwash tank


FLO-WELL® ENGINEERED DRY WELL



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
FWAS24WH	24" diam. x 28.75"H Flo-Well® Stormwater Leaching System	Black	1	18.96	10FW	NDS #FWAS24WH structural foam polyolefin round drywell system
	Includes 3 side panels, 1 top component	with UV inhibitors. 50 gal. storage capacity.				
	Fits 4" Sch. 40 Pipe and 4" DWV Pipe.	oupuoity.				



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
FWAS24CWH	24" diam. Flo-Well® Cover	Black	2	5.92	10FW	Structural foam polyolefin round
	Use with #FWAS24.					drywell system cover with UV inhibitors. 24-1/4" dia., 4-1/2" height, 3/4" outer lip, 4.5" center knockout fits NDS #FWSD69, std pipe and 4" Sch. 40 pipe.



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
FWSPS3WH	Flo-Well® Side Panels/Extension Only Includes 3 side panels; makes 1 round d (May also be used as a durable compost bin)	Black rywell.	1	4.35	10FW	Structural foam polyolefin side panels with UV inhibitors with 22 1-1/2" knockout leaching ports and 4 4.5" knockout inlet/outlet ports per panel. 0.75" lip for firm stacking.



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications	
FWBP24	24" diam. Flo-Well® Bottom	Black	5	3.41	10FW	Structural foam polyolefin round	
	Fits #FWAS24. (Not included in #FWAS24 kit)					Flo-Well® bottom with UV inhibitors. 24" diameter with six 1-1/2" leaching ports. Collects debris for easy cleanout.	



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications			
FWSD69	4" Sch. 40 Surface Drain Inlet with Grate	Black	8	1.85	10FW	Structural foam polyolefin 6" grate with 4" inlet with UV inhibitors. 6"			
	Fits #FWAS24 and #FWAS24C. ADA Compliant.					diameter at inlet. 9" high. 4.5" OD fits Sch. 40 PVC fittings. Open surface area 8.22 square inches. 25.15 GPM.			



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications		
FWFF67	Porous Filter Fabric Wrap for Flo-Well®	Black	1	0.35	10FW	7' long x 2' wide to surround Flo-Well®		
	Use with #FWAS24.					Drywell System. Non-woven fabric. Weight 1 oz. Mullen burst 175 psi. 200 GPM flow-through.		





NDS catch basins and grates collect surface water while minimizing the amount of debris entering the system

Available in a range of sizes from 6" round to 24" square, and with various grating and filter options for commercial and residential systems.

NDS Drainage Solutions

NDS offers a complete line of catch basins and grates for residential and commercial stormwater management solutions. NDS catch basins have sump areas that collect debris and prevent clogging of the pipeline, and grates are available in a variety of patterns and colors to blend in with surrounding surfaces. Depending on the size of the round, square, or atrium grates, they may fit directly into a riser of pipe, sewer and drain fitting, or our catch basins.










Small Grates


Spee-D® Basin


Large Catch Basin Adapter

Spee-D® Basins

Use our compact 6" round Spee-D Basins with grates to collect runoff water while its sump area collects debris and prevents clogging. Also use Spee-D Basins with 6" Pop-Up Emitters to provide a point of discharge or overflow in a drainage system.







Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
101	1 - 3" and 4" Locking Outlet	Black	10	1.60	10ND	6" styrene catch basin
101ATBLKIT	Spee-D Basin with 6" Black Atrium Grate	Black Grate	8	n/a	10ND	with locking outlet. 68 GPM per outlet capacit
101GRKIT	Spee-D Basin with 6" Green Round Grate	Green Grate	6	n/a	10ND	
101SQGRKIT	Spee-D Basin with 9" x 9" Green Square Grate	Green Grate	8	n/a	10ND	
201	3" and 4" Locking Outlets*	Black	10	1.83	10ND	101 201
	Spee-D Basins and kits fit 3" or 4" Sewer & Drain Pipe, Pipe. Use new Spee-D Riser or 6" Sewer and Drain Pipe silicone to make water-tight connections. Locking Outle	Kits contain 1-outlet Spee-D Basin & Grate as described.				


Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications			
101R	Spee-D Basin Riser	Black	12	1.07	10ND	6" Riser for Spee-D Basin.			
	Use with any Spee-D Basin to add from 2" to 6" to to	Styrene.							

Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
250	2 - 3" and 4" 90° Outlets	Black	12	1.64	10ND	6" styrene catch basin
300	3 - 3" and 4" Outlets	Black	12	1.82	10ND	with locking outlet. 83 GPM per outlet capacity.
350	3" and 4" Outlets	Black	12	2.00	10ND	
	Fit 3" or 4" Sewer & Drain Pipe, 3" or 4" Corrugated Pipe, 4" Sch. 40 and 3" & 4" Triple Wall Pipe. Use 6" Sewer and					


9" Catch Basin Series




Part No.	Description		Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications		
900FF	9" Catch Basin Filter	Blue Frame/ Black Bag	8	0.06	10ND	Polypropylene Frame Fabric is non-woven geotextile 956 PM/SF.		
	Compatible with these basins: 900, 900-4 and 916	s: 900, 900-4 and 916 NDS Catch Basins, Risers and Kits						



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
900BLKIT	9" x 9" Catch Basin Kit	Black Grate	4	4.90	10ND	9" x 9" tapered Catch
900GRKIT	9" x 9" Catch Basin Kit	Green Grate	4	4.90	10ND	Basin. Polypropylene.
900KITDISP	9" x 9" Catch Basin Kit	Black Grate	8	39.2	10ND	Kits include 2-opening Catch Basin, Grate,
900	9" x 9" Catch Basin 2-opening	Black	4	2.18	10ND	Screws, 2 Outlets and
900-4	9" x 9" Catch Basin 4-opening	Black	4	2.00	10ND	1 Plug.
	DISP includes display box.					




Part No.	Description	Color	Pkg. Qty.		Product Class	Specifications			
916	9" x 9" Catch Basin Riser	Black	4	1.75	10ND	6" Riser for 9" x 9 Catch Basin, Styrene.			
	Use with 9" x 9" Catch Basin Series. Stacks on top of 9" catch basins to add up to 6" to top of basin. Can be cut to size.								




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications			
981	9" x 9" Atrium Grate	Black	6	0.87	10ND	9" Structural Foam Polyolefin Dome Atrium Grate with UV inhibitor.			
991	9" x 9" Atrium Grate	Green	6	0.87	10ND				
	Use with 9" x 9" Catch Basin Series.					Open surface area 31.50 square inches. 96.36 GPM.			



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
980	9" Square Grate	Black	8	1.50	10ND	9" Square Structural Foam
990	9" Square Grate	Green	8	1.50	10ND	Polyolefin Grate with UV inhibitor. Open surface area 37.49 square inches.
999	9" Square Grate	Gray	8	1.50	10ND	
9998	9" Square Grate	Sand	8	1.50	10ND	
~						




Part No.	Description	Color		Wt. Ea. Ibs.	Product Class	Specifications			
930B	9" Square Brass Grate	Brass	1	5.11	15BR	Open surface area 34.00 square inches. 104.01 GPM.			
	(see page 79). ADA Compliant.					Includes SS Screws.			



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications		
913	9" Square Ductile Iron Grate	Black	4	7.89	10ND	9" Square Heavy-Duty		
	Use with 9" x 9" Catch Basin Series.		Ductile Iron Grate. Open surface area 21.70 square					
•• ••	(see page 79)	inches. 66.38 GPM.						




9" Catch Basin Series (continued)




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications			
915	9" Square Galvanized Steel Grate	Galvanized Steel	4	3.80	10ND	9" Square Heavy-Duty			
	Use with 9" x 9" Catch Basin Series. (see page 79)					Galvanized Steel Bar Grate. Open surface area 61.94 square inches. 189.48 GPM.			




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
930	9" x 9" Low-Profile Adapter	Black	8	0.75	10ND	9" x 9 Low-Profile Adapter.
930ATBLKIT 930GRKIT	9" x 9" Low-Profile Adapter with Black Atrium Grate and 3" & 4" Universal Locking Outlet 9" x 9" Low-Profile Adapter with Flat Green Grate and 3" & 4" Universal Locking Outlet	Black Grate Green Grate	8	n/a n/a	10ND 10ND	Styrene. Kits contain Low-Profile Adapter, 3" & 4" Universal Locking Outlet and Grate as described.
	Adapter alone requires #1242, #1243, #1245, #1260 Sewer and Drain or Corrugated Pipes (see page 35).					



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications		
931	9" x 9" Deep Housing Spigot Adapter	Black	10	2.40	10ND	9" x 9" Square Deep		
	Fits 4" Corrugated Pipe.		Housing Spigot Adapter. Styrene.					
	Use #933 to adapt to 4" Sewer and Drain Pipe.							



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
933	Adapter Bushing	Black	20	0.30	10ND	Styrene.
	Fits 4" Sewer and Drain Pipe.					
	Use Housing Adapter Bushing with #931.					




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
932	9" x 9" Low-Profile Housing Adapter	Black	8	1.13	10ND	NDS #932, 9" x 9" Square
	Fits 6" Spee-D® Basin and 6" Sewer and Drain Pipe	Low-Profile Housing Adapter with 6" Outlet. Styrene.				

12" Catch Basin Series





Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications	
1200FF	12" Catch Basin Filter	Blue Frame/ Black Bag	8	0.10	10ND	Polypropylene Frame Fabric is non-woven geotextile 956 PM/SF.	
	Compatible with these basins: 1200, 1200NGB, 1203, 1204, 1216, 1217, 1225 NDS Catch Basins & Kits.						








Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications	
1200NGBKIT	12" x 12" Catch Basin, 2 Open Slides	Black	4	4.65	10ND	Adjustable Outlet Catch	
1200NGB	12" x 12" Catch Basin	Black	4	3.45	10ND	Basin. Sides adjust to 3 different outlet elevations.	
1207	Open Slide for 1200NGB	Black	8	0.60	10ND	Polypropylene basin and styrene sides.	
1208	Plug Slide for 1200NGB	Black	8	0.76	10ND		
	Compatible with 12" x 12" Catch Basin Risers and Grates.						











Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications	
1200BLKIT	12" x 12" Catch Basin, 2 Open Sides	Black Grate	4	7.59	10ND	12" x 12" Tapered Catch	
1200GRKIT	12" x 12" Catch Basin, 2 Open Sides	Green Grate	4	7.59	10ND	Basin. Polypropylene.	
1200KITDISP	12" x 12" Catch Basin, 2 Open Sides	Black Grate	8	7.59	10ND	Kits include 2-opening Catch Basin, Grate,	
1200DGBLKITWH	12" Basin with Wave Decorative Grate	Black Grate	4	7.59	10ND	2 Outlets and 1 Plug.	
1200DGGKITWH	12" Basin with Botanical Decorative Grate	Green Grate	4	7.59	10ND	DISP includes display box.	
1200	12" x 12" Catch Basin, 2 Openings	Black	4	4.25	10ND		
1203	12" x 12" Catch Basin, 3 Openings	Black	4	3.75	10ND		
1204	12" x 12" Catch Basin, 4 Openings	Black	4	3.75	10ND		
	Requires either #1206, #1242, #1243, #1245, # (see page 35). Bottom cutout can be removed.						
Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications	
1216	12" x 12" Catch Basin Riser	Black	8	2.75	10ND	6" Riser for 12" Catch Basin. Styrene.	
	Use with 12" x 12" Catch Basin Series.						


Part No	0.	Description		Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications			
1217		12" x 12" Riser with 2 Openings	Black	4	4.00	10ND	12" Riser with Two			
Nests on top of 12" Catch Basin Series for shallow outlets and 12" Sump Box for more sump area. Requires either #1206, #1242, #1243, #1245, #1266 or #1889 Universal Outlet to connect pipe to riser.							Openings. Styrene.			

Stacks on top of 12" catch basins to add up to 6" to top of basin. Can be cut to size.


Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications			
1225	12" x 12" Sump Box	Black	4	6.75	10ND	One-piece 12" Sump Box.			
	Use with 12" x 12" Grate or #1220 Valve Box Co		Styrene.						




12" Catch Basin Series (continued)




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications		
1200DSG	12" x 12" Downspout Grate	Black	8	n/a	10ND	12" x 12" Downspout Grate.		
	Receives downspouts from 2" to 6" round or squa	Structural Foam Polyolefin with UV inhibitor.						
	Fits all NDS 12" square Catch Basins, Risers and L							




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications		
1280 1290	12" x 12" Atrium Grate 12" x 12" Atrium Grate	Green Black	8	1.74 1.74	10ND 10ND	12" Structural Foam Polyolefin Dome Atrium Grate with UV inhibitor.		
	Use with 12" x 12" Catch Basin Series.					Open surface area 50.60 square inches. 154.79 GPM.		



Part No.	Description	Color	Qty.	(lbs.)	Class	Specifications
1210	12" x 12" Square Grate	Gray	8	2.33	10ND	12" Square Structural
1211	12" x 12" Square Grate	Black	8	2.33	10ND	Foam Polyolefin Grate with UV inhibitor. Open surface area 50.76 square inches. 155.28 GPM.
1212	12" x 12" Square Grate	Green	8	2.33	10ND	
1212S	12" x 12" Square Grate	Sand	8	2.33	10ND	
	Use with 12" x 12" Catch Basin Series.					
	(see page 79). ADA Compliant.					



Part No.	Description			Wt. Ea. lbs.	Product Class	Specifications		
1230B	12" Square Brass Grate	Brass	1	9.24	15BR	Open surface area 42.87		
	(see page 79). ADA Compliant.					square inches. 131.14 GPM. Includes SS Screws.		




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
1218S	12" x 12" Square Botanical Grate	Sand	8	3.27	10ND	12" Square Structural
1218GR	12" x 12" Square Botanical Grate	Green	8	3.27	10ND	Foam Polyolefin Botanical Grate with UV inhibitor.
1218GY	12" x 12" Square Botanical Grate	Gray	8	3.27	10ND	Open surface area 24.44 square inches. 74.77 GPM.
1218	12" x 12" Square Botanical Grate	Black	8	3.27	10ND	Class B load rated.
839	Stainless Steel Screws, FH #6 x 1-3/4"	Metal	40	n/a	10ND	
	(see page 79). ADA Compliant.					



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
1218CI	12" x 12" Square Botanical Cast Iron Grate	Raw Iron	1	12.67	10ND	12" Square Cast Iron Botanical Grate. Open surface area 24.44 square
629	Stainless Steel Screws, FH #20 x 1-1/2"	Metal	40	n/a	10ND	inches. 74.77 GPM. Class B
-	(see page 79). ADA Compliant.	load rated.				


12" Catch Basin Series (continued)




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
1224S	12" x 12" Square Wave Grate	Sand	8	2.68	10ND	12" Square Structural
1224GR	12" x 12" Square Wave Grate	Green	8	2.68	10ND	Foam Polyolefin Wave Grate with UV inhibitor.
1224GY	12" x 12" Square Wave Grate	Gray	8	2.68	10ND	Open surface area 25.67
1224	12" x 12" Square Wave Grate	Black	8	2.68	10ND	square inches. 78.53 GPM. Class B load rated.
839	Stainless Steel Screws, FH #6 x 1-3/4"	Metal	40	n/a	10ND	
	(see page 79). ADA Compliant.					




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
1224Cl	12" x 12" Square Wave Cast Iron Grate	Raw Iron	1	13.90	10ND	12" Square Cast Iron Wave Grate. Open surface
629	Stainless Steel Screws, FH #20 x 1-1/2"	Metal	40	n/a	10ND	area 25.60 square inches
	(see page 79). ADA Compliant/Heel-proof.					78.31 GPM. Class B load rated.




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications		
1213	12" x 12" Square Ductile Iron Grate	Black	1	15.30	10ND	12" Square Heavy-Duty		
	Use with 12" x 12" Catch Basin Series. (see page 79). ADA Compliant.					Ductile Iron Grate. Open surface area 37.20 square inches. 113.80 GPM.		




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications		
1215	12" x 12" Square Galvanized Steel Grate	Galvanized Steel	1	5.85	10ND	12" Square Heavy-Duty		
	Use with 12" x 12" Catch Basin Series. (see page 79)					Galvanized Steel Bar Grate. Open surface area 113.78 square inches. 348.07 GPM.		



Part No.	Description		Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
1220	12" x 12" Sump Pump Box	Black	8	2.23	10ND	NDS #1220, 12" Square
	Use with NDS 12" x 12" Catch Basin Series and NDS #	Structural Foam Polyolefin Solid Cover.				




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
1230	12" x 12" Low-Profile Adapter	Black	8	1.25	10ND	12" x 12" Low-Profile Adapter. Styrene. Kits contain Low-Profile Adapter, 3" & 4" Universal Locking Outlet and Grate as described.
1230ATBLKIT 1230GRKIT	12" x 12" Low-Profile Adapter with Black Atrium Grate and 3" & 4" Universal Locking Outlet 12" x 12" Low-Profile Adapter with Flat Green Grate and 3" & 4" Universal Locking Outlet	Black Grate Green Grate	8	n/a n/a	10ND 10ND	
	Adapter alone requires #1242, #1243, #1245, #1266 or #1889 Universal Outlets to connect to 3", 4", 6" or 8" Sewer and Drain or Corrupated Pipes (see page 35). Kits contain #1243 Outlet.					




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
1221	12" x 12" Square, Low-Profile Adapter – Fits 8" Sewer & Drain Pipe	Black	12	1.92	10ND	12" x 12" Low-Profile Adapter. Styrene.
1222	12" x 12" Square, Low-Profile Spigot Adapter – Fits 8" Corrugated Pipe	Black	12	1.92	10ND	
	Fits 8" Sch 40, Corrugated Spigot, S&D Hub.					




18" Catch Basin Series




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications	
1882	18" One-Piece Catch Basin 2 Openings	Black	1	10.00	10ND	18"x18" One-Piece	
1882BLKIT	18" Catch Basin Kit with Black Plastic Grate, Outlet Adapters for 6" & 8" Pipe, Basin Plug & Outlet Reducer Ring	Black/Black		21.00	10ND	Tapered Catch Basin. Structural Foam Polyolefin.	
1882GRKIT	18" Catch Basin Kit with Green Plastic Grate, Outlet Adapters for 6" & 8" Pipe, Basin Plug & Outlet Reducer Ring	Black/Green	1	21.00	10ND		
1884	18" One-Piece Catch Basin 4 Openings	Black	1	9.65	10ND		
	Requires either $\#1206$, $\#1242$, $\#1243$, $\#1245$, $\#1266$, $\#1888$ or $\#1889$ Universal Outlet to connect pipe to basin. Includes 2 or $4 \#1890$ Reducer Rings.						




	Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications			
	1800	18" x 18" Expandable Catch Basin 2 Openings*	Black	1	16.00	10ND	18" x 18" Modular Cato			
1	1804	18" x 18" Expandable Catch Basin 4 Openings*	Black	1	16.00	10ND	Basin with Locking Tabs Styrene.			
		Assembly Required. #1800 includes: 2 #1822, 2 #1820, 1 Use #1800 and #1804 with #1206, #1243, #1245, #1266		Styrene.						




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications			
1816	8" Riser for 18" Catch Basin	Black	1	6.00	10ND	8" Riser for 18" x 18"			
	Riser package includes 4 sides. Use with #1800, #1804, #1882 or #1884.		Catch Basin. Styrene.						




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications		
1881	18" x 18" Atrium Grate	Black	2	6.51	10ND	18" Structural Foam Polyolefin Dome Atrium Grate with UV inhibitor. Open surface area 89.40 square inches. 273.49 GPM.		
1891	18" x 18" Atrium Grate Use with 18" x 18" Catch Basin Series.	Green	2	6.51	10ND			



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications		
1810	18" x 18" Square Grate	Gray	4	7.72	10ND	18" Square Structural Foam Polyolefin Grate		
1811	18" x 18" Square Grate	Black	4	7.72	10ND			
1812	18" x 18" Square Grate	Green	4	7.72	10ND	with UV inhibitor. Open		
	Use with 18" x 18" Catch Basin Series. (see page 79). ADA Compliant.					surface area 86.31 square inches. 264.03 GPM.		




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications		
1813	18" x 18" Cast Iron Square Grate	Black	1	46.00	10ND	18" Square Heavy-Duty		
	Use with 18" x 18" Catch Basin Series.					Cast Iron Grate. Open surface area 110.70 square inches. 338.65 GPM. H-20 Load Rating.		




Pai	rt No.	Description	Color	9		Product Class	Specifications
189	90	Universal Outlet Reducer Ring	Styrene.				
		Required on #1821 basin side when using 3", 4" or 6" p #1206, #1243, #1245, #1266 or #1889 Universal Outlets					


18" Catch Basin Series (continued)



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications	
1815	18" Square Galvanized Steel Grate	Galvanized Steel	1	10.78	10ND	18" Square Heavy-Duty Galvanized Steel Bar Grate.	
	Use with 18" x 18" Catch Basin Series.		Open surface area 239.00 square inches. 731.13 GPM.				
	(see page 79)						




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
1840	Frame to adapt 18" x 18" grate to concrete catch basin	Black	4	2.00	10ND	18" x 18" Frame. Styrene.
	Use with 18" x 18" Grates.					




Part No.	Description		Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications	
1830	18" x 18" Low-Profile Adapter	18" x 18" Low-Profile Adapter, Styrene,					
	Includes NDS #1890 Reducer Ring. Requires either an NDS #1243, #1245, #1266 or #1888 Universal Outlet to connect to pipe.						


18" Component Parts




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications		
1820	Basin Side – No Opening	Black	4	4.00	10ND	18" x 18" Catch Basin Side,		
						No Opening. Styrene.		



	Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
I	1821	Basin Side – 8" Opening	18" x 18" Catch Basin Side,				
		Reducer Ring not included. Requires #1888 Universal Outlet to fit 8" Corrugated #1889 Universal Outlet does not fit this #1821 Basin	8" Opening. Styrene.				




Part No.	Description		Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
1822	Basin Side – 6" or 8" Opening	10ND	18" x 18" Catch Basin Side,			
Opening using Universal Outlet. Includes #1890 Reducer Ring. Use with #1206, #1242, #1243, #1245, #1266 or #1888 Universal Outlets.						6" or 8" Opening. Styrene.




Part No.	Description	Color	Pkg. Qty.		Product Class	Specifications
1828	Basin Bottom	Black	4	2.50	10ND	18" x 18" Catch Basin
				Bottom. Styrene.		




24" Catch Basin Series



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
2400	24" x 24" Catch Basin, 2 Openings	Black	1	18.00	10ND	24" x 24" One-Piece Tapered Catch Basin. HDPE with Structural Foam.
2400BLKIT	24" Catch Basin Kit with Black Plastic Grate, Outlet Adapters for 8", 10" & 12" Pipe, Basin Plug, Outlet Reducer Rings	Black/Black		50.00	10ND	
2400GRKIT	24" Catch Basin Kit with Green Plastic Grate, Outlet Adapters for 8", 10" & 12" Pipe, Basin Plug, Outlet Reducer Rings	Black/Green	1	50.00	10ND	
2404	24" x 24" Catch Basin, 4 Openings	Black	1	15.00	10ND	
	#2400 & #2404 Require 2 or 4 #2410 Universal Outlets.					




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
2418	24" x 24" Catch Basin Extension (No Bottom)	Black	1	14.60	10ND	8" Extension for 24" x 24" Catch Basin. HDPE with
	Use with 24" x 24" Catch Basin Series.					Structural Foam.




۳ <i>%</i>	Grate	Openings	
/8	Grate	Operings	

Par	t No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
241	11	24" x 24" Square Grate	Black	1	19.75	10ND	24" Square HDPE with
241	12	24" x 24" Square Grate	Green	1	19.75	10ND	Structural Foam Grate with UV inhibitor. Open surface
		Use with 24" x 24" Catch Basin Series.					area 231.69 square inches. 708.77 GPM.
h		(see page 79)					




Part No.	Description	Color	, ,	Wt. Ea. (lbs.)	Product Class	Specifications	
2413	24" x 24" Square Cast Iron Grate	Black	1	147.00	10ND	24" Square Heavy-Duty	
	Use with 24" x 24" Catch Basin Series. (see page 79)					Cast Iron Grate. Open surface area 197.00 square inches. 602.65 GPM. Structural Foam.	




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications		
2415	24" x 24" Square Galvanized Steel Grate	Galvanized Steel	1	62.88	10ND	24" Square Heavy-Duty Galvanized Steel Bar Grate. Open surface area 422.45		
	Use with 24" x 24" Catch Basin Series. (see page 79)							
Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications		
Part No. 2410	Description 10" & 12" Universal Adapter	Color Black				Specifications 10"/12" Universal Adapter. HDPE.		

Catch Basin Universal Outlets


Universal Outlets and Adapters allow you to quickly connect to 3"-12" drain pipes to accommodate the needs of any job. They offer greater flexibility during install saving time and money.




Pai	rt No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
124	42	3" & 4" Universal Outlet w/4" Spigot	Black	20	0.74	10ND	3" & 4" Universal Outlet.
		Fits 3" & 4" Corrugated Pipe, 3" & 4" Sewer and Dr Allows for adjusting inlet height. Use with 9", 12", 1 Use with 24" Catch Basin also requires #2410 Adap	8" and 24" Catch Basi	· .	/all Pipe.		Styrene.




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications	
1243	3" & 4" Universal Locking Outlet*	Black	20	0.60	10ND	3" & 4" Patented Universal	
	Fits 3" & 4" Corrugated Pipe, 3" & 4" Sewer and Dri Use with 9", 12", 18" and 24" Catch Basin Series ar Use with 24" Catch Basin also requires #2410 Adap *New Locking Outlet snaps on to most 3" and 4" co	nd #930, #1230, #1830 ter.			ipe.	Locking Outlet. Styrene.	



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications		
1245	3" & 4" Offset Universal Outlet	Black	20	0.50	10ND	3" & 4" Offset Universal		
	Fits 3" & 4" Corrugated Pipe, 3" & 4" Sewer and Dr Allows for adjusting inlet height. Use with 9", 12", 1 Use with 24" Catch Basin also requires #2410 Adar	8" and 24" Catch Basi		/all Pipe.		Outlet. Styrene.		



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
1266	6" Universal Locking Outlet*	Black	20	0.55	10ND	6" Universal Locking Outlet.
	Fits 6" Sewer and Drain Pipe, 6" Corrugated Pipe. U #1230 and #1830 Low-Profile Adapters. Use with 24 *New, improved Locking Outlet snaps on to most 6"	4" Catch Basin also rec			and #930,	Styrene.



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
1888	8" Universal Outlet	Black	8	1.05	10ND	8" Universal Outlet.
	Fits 8" Sewer and Drain Pipe, 8" Corrugated Pipe. U Use with 24" Catch Basin also requires #2410 Adap		atch Basin Se	ries.		Styrene.



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications	
1889	8" Offset Universal Adapter	Black	10	0.74	10ND	8" Offset Universal Adapter.	
	Fits 8" Sewer and Drain Pipe, 8" Corrugated Pipe. Use (except 1800 and 1804).	se with 12" and most	18" Catch Bas	sin Series		Styrene.	



Part No.	Description	Color	Qty.	(lbs.)	Class	Specifications
2410	10" & 12" Universal Adapter	10"/12" Universal Adapter.				
	Includes #1890 (comes pre-inserted). Fits 10" and 'Pipe; 12" Single Wall Corrugated Pipe (does not fit 1 3" to 8" adapters above (all except #1889) for use v 8" Corrugated Pipe; and 4" Sch. 40 Pipe (select cor	10" Single Wall Corruga with 3", 4", 6" and 8" S	ted Pipe). Red Sewer and Dra	duces opening ain Pipe; 3", 4	to fit most ", 6" and	HDPE.
Don't No.	Product	Currifications				

Black

00	
5/8"	

1206

6" Universal Adapter Plug


Universal Plug. Styrene.

Wt. Ea. Product

10ND




POP-UP DRAINAGE EMITTERS




The Pop-up Drainage Emitter is an easy, safe and efficient solution that allows water to be diverted and released to water-safe areas away from structures, erosion-prone landscapes and poor drainage areas.

Pop-up Drainage Emitters allow water captured by grates, catch basins, channel drains, Flo-Well, EZflow, downspouts and roof gutter systems to flow through drainage pipe and away from structural foundations to safe or useful areas. For example, water can be routed from a low area next to a foundation to a water-safe area in the landscape, or a curbside drainage system where allowed. The emitter opens under minimal hydrostatic pressure from water through upstream drainage pipes; the emitter closes as flow diminishes. The special patented design allows the Emitter to open with even the smallest flows. Since the Emitter is closed during dry weather, debris and rodents cannot enter the drain pipes. Spring automatically retracts – closes and prevents damage from lawn mowers. It's flat profile blends discreetly into the surrounding landscapes.


3" & 4" Pop-up Drainage Emitter



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
420	3" & 4" Pop-up Drainage Emitter		Green 20 C		10ND	3" and 4" polyolefin spring-loaded
	Fits 3" and 4" Sewer and Drain Fittings. Ideal for discharging excess water from stormwa Spring automatically retracts.	ter managem	ent system.			Pop-up Drainage Emitter with UV inhibitor. 40 GPM capacity. 0.04 psi or 1" of head to raise top.




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications	
321	Emitter with 3" Elbow		Green 25 0.6		10ND	NDS #420 polyolefin spring-loaded	
	Fits 3" Sewer and Drain Pipe. Ideal for discharging excess water from stormwa Spring automatically retracts.	ter managem	ent system.			Pop-up Drainage Emitter with UV inhibitor, 3" styrene 90 degree elbow with 1/4" drain hole. 40 GPM. 0.04 psi or 1" of head to raise top.	



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
421	Emitter with 4" Elbow	Green	20	0.85	10ND	NDS #420 polyolefin spring-loaded
	Fits 4" Sewer and Drain Pipe.					Pop-up Drainage Emitter with UV inhibitor, 4" styrene 90 degree
	Ideal for discharging excess water from stormwa Spring automatically retracts.	ter managem	ent system.			elbow with 1/4" drain hole. 40 GPM. 0.04 psi or 1" of head to raise top.


POP-UP DRAINAGE EMITTERS

3" & 4" Pop-up Drainage Emitter (continued)




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications			
430	Pop-up Drainage Emitter with 3" Elbow and Universal Adapter	Green	20	1.00	10ND	NDS #420 polyolefin spring-loaded Pop-up Drainage Emitter with UV			
	Universal Adapter fits 3" and 4" corrugated pipe, 4" Sch. 40 pipe, and 3" and 4" triple wall pipe. Ideal for discharging excess water from stormwater	inhibitor, 3" styrene 90 degree elbow with 1/4" drain hole and universal pipe adapter. 40 GPM. 0.04 psi or 1" of head to raise top.							
1241	3" & 4" Universal Adapter w/4" Spigot	Black	20	0.70	10ND	3" & 4" Patented Universal Adapter.			
Connects 3" & 4" Sewer and Drain Fittings with 3" & 4" Corrugated Pipe, 3" & 4" Sewer and Drain Pipe, 4" Sch. 40 Pipe and 3" & 4" Triple Wall Pipe.						Styrene.			


6" Pop-up Drainage Emitter



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications	
620	620 6" Pop-up Drainage Emitter		Green 15		10ND	6" polyolefin spring-loaded Pop-up	
	Can be used with Flo-Well to relieve overflow.					Drainage Emitter with UV inhibitor. 88 GPM capacity. 0.04 psi or 1" of head to raise top.	



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
624	6" Pop-up Emitter with Elbow and Corrugated Pipe Adapter	Green	10	3.45	10ND	NDS #620 polyolefin spring-loaded Pop-up Drainage Emitter with UV inhibitor, 6" styrene 90 degree elbow with 1/4" drain hole and corrugated pipe adapter. 88 GPM. 0.04 psi or 1" of head to raise top.



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
625	6" Pop-up Emitter wih Spee-D® Basin	Green	8	2.21	10ND	NDS #620 polyolefin spring-loaded Pop-up Drainage Emitter with UV inhibitor and Spee-D basin. 88 GPM. 0.04 psi or 1" of head to raise top.



COMMOM DRAINAGE FITTINGS

90 Degree PVC Elbow



	Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class
PVC	3P02	3" PVC 90 Degree Elbow (HUB x HUB)	White	40	0.40	30PV
	4P02	4" PVC 90 Degree Elbow (HUB x HUB)	White	25	0.68	30PV
	6P02	6" PVC 90 Degree Elbow (HUB x HUB)	White	12	3.00	30PV

Corrugated Adapter



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class
351	3" Polyethylene Corrugated Adapter (CORR HUB x S&D SPT or HUB)	Black	50	0.10	30ST
451	4" Polyethylene Corrugated Adapter (CORR HUB x S&D SPT or HUB)	Black	25	0.20	30ST
651	6" Polyethylene Corrugated Adapter (CORR HUB x S&D SPT or HUB)	Black	12	0.25	30ST

Corrugated Internal Couplings



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class
3C05	3" Corrugated Coupling	Black	60	0.07	30PE
4C07	4" Corrugated Coupling	Black	36	0.08	30PE
6C07	6" Corrugated Coupling	Black	12	0.08	30PE

Corrugate End Caps



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class
3006	3" Corrugated Endcap	Black	33	0.05	30PE
4C06	4" Corrugated Endcap	Black	30	0.06	30PE
6006	6" Corrugated Endcap	Black	15	0.50	30PE

Note: See Fittings section (pages 170-189) for additional fitting options.



NDS offers a variety of grates in sizes, patterns, colors and design options to fit all products and enhance any landscape.

Brass & Chrome Grates





Strong - Practical - Functional

Our solid cast brass grates are secured to a PVC collar with solid brass screws for aesthetics and reliability. The PVC collar can be solvent welded into sewer and drain fittings or pipe where permanent, anti-theft installation is desired. The grate can still be removed for easy cleanout.


- A unique mix of beauty and function
- · Recommended for highly-visible entry areas in hotels, malls, office buildings, country clubs and estates
- Exceptional construction and fine finish also make these grates ideal for deck areas, walkways, swimming pools and spas

Materials & Standards

- Made with the highest-quality solid brass
- Brushed Satin and Polished Chrome finishes are protected by a clear plastic film that prevents damage to the finish during shipping and installation



Brass & Chrome Grates




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. lbs.	Product Class	Specifications
552B	1 ft. Brass Channel Grate	Satin Brass	12	1.21	25PF	1 foot Mini Channel Solid
553PB	1 ft. Brass Channel Grate	Polished Brass	12	1.21	25PF	Brass Grate with brass screws. Open surface area
†	Fits #500 and #550 Mini Channels. (see pages 50).		9.20 square inches per foot. 28.14 GPM per foot.			
Λ	(see page 79). ADA Compliant/Heel-proof.					




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications			
909B	3" Round Brass Grate w/PVC Collar	Satin Brass	20	0.40	15BR	3" Round Solid Brass Grate and brass screws with PVC collar. Open			
905PB	3" Round Brass Grate w/PVC Collar	Polished Brass	20	0.40	15BR				
i	Fits 2" SCH-40 Pipe and 3" Sewer and Drain Fittings		surface area 2.68 square inches. 8.20 GPM.						
Λ	(see page 79). ADA Compliant/Heel-proof.								



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. lbs.	Product Class	Specifications		
915SC	3" Round Chrome Grate w/PVC Collar	Satin Chrome	20	0.40	15BR	3" Round Solid Chrome Grate and screws with		
907PC	3" Round Chrome Grate w/PVC Collar	Polished Chrome	20	0.40	15BR	PVC collar. Open surface area 2.68 square inches.		
注	Fits 3" Sewer and Drain Fittings and 2" SCH-40 Pipe. (see page 79). ADA Compliant/Heel-proof.							



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications			
910B	4" Round Brass Grate w/PVC Collar	Satin Brass	20	0.64	15BR	4" Round Solid Brass Grate and brass screws			
906PB	4" Round Brass Grate w/PVC Collar	Polished Brass	20	0.64	15BR	with PVC collar. Open			
汴	Fits 3" Sewer & Drain Pipe, 4" Sewer & Drain Fitting (see page 79). ADA Compliant/Heel-proof.	surface area 5.25 square inches. 16.06 GPM.							




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. lbs.	Product Class	Specifications			
917SC	4" Round Chrome Grate w/PVC Collar	Satin Chrome	20	0.66	15BR	4" Round Chrome Grate and screws with PVC			
908PC	4" Round Chrome Grate w/PVC Collar	Polished Chrome	20	0.66	15BR	collar. Open surface area			
广	Fits 3" Sewer & Drain Pipe, 4" Sewer & Drain Fitting (see page 79). ADA Compliant/Heel-proof.	5.25 square inches. 16.06 GPM.							




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. lbs.	Product Class	Specifications
918B	6" Round Brass Grate w/Styrene Collar	Satin Brass	8	1.38	15BR	6" Round Solid Brass Grate and brass screws with styrene collar. Open
919PB	6" Round Brass Grate w/Styrene Collar	Polished Brass	8	1.38	15BR	
*	Fits Spee-D® Basin, 6" Sewer & Drain Fittings.					surface area 13.10 square inches. 40.07 GPM.
$\mathbf{\Lambda}$	(see page 79). ADA Compliant.					


Brass & Chrome Grates (continued)




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications	
913B	5" Square Brass Grate w/PVC Collar	Satin Brass	10	1.21	15BR	5" Square Solid Brass Grate with brass screws	
914PB	5" Square Brass Grate w/PVC Collar	Polished Brass	10	1.21	15BR	and PVC collar. Open surface area 2.5 square	
大	Fits 4" Sewer and Drain Fittings, 3" Sewer and Drain Pipe, and 3" Triple Wall Pipe. (see page 79). ADA Compliant.						




F	art No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications
	20B 23PB	6" Square Brass Grate w/Styrene Adapter 6" Square Brass Grate w/Styrene Adapter	Satin Brass Polished Brass	8	1.65 1.65	15BR 15BR	6" Square Solid Brass Grate with brass-colored styrene low-profile adapter and brass screws. Open
	†	Fits 3" or 4" Sewer and Drain Pipe or Fittings, 3" or (see page 79). ADA Compliant.	wer and Drain Pipe or Fittings, 3" or 4" Corrugated Pipe, and 3" or 4" Triple Wall Pipe. A Compliant.				




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications			
921B 922PB	6" Square Brass Grate w/Styrene Adapter 6" Square Brass Grate w/Styrene Adapter	Satin Brass Polished Brass	8	1.71 1.70	15BR 15BR	6" Square Solid Brass Grate with brass-colored styrene low-profile adapter			
术	Fits Spee-D® Basin, 6" Sewer and Drain Pipe & Fitti (see page 79). ADA Compliant.	ings.				and brass screws. Open surface area 11.60 square inches. 35.49 GPM.			




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications			
78B	4" Atrium Brass Grate	Brass	1	2.00	15BR	Open surface area 10.20 square inches. 31.20 GPM.			
	Fits 4" Sewer and Drain Pipe & Fittings.	n Pipe & Fittings.							



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications		
90B	6" Atrium Brass Grate	Brass	1	5.30	15BR	Open surface area 22.50 square inches. 68.83 GPM.		
	Fits 6" Sewer and Drain Pipe & Fittings.	Square mones. 00.05 drivi.						



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications
930B	9" Square Brass Grate	Brass	1	5.11	15BR	Open surface area 34.00 square inches. 104.01 GPM.
	(see page 79). ADA Compliant.	Includes SS Screws.				



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications
1230B	12" Square Brass Grate	Brass	1	9.24	15BR	Open surface area 42.87 square inches. 131.14 GPM.
*	(see page 79). ADA Compliant.					Includes SS Screws.



Decorative Grates

Designed to meet today's demand for products that are as beautiful as they are functional. NDS decorative grates feature consumer-tested designs and offer a range of colors and materials ideal for any application or setting.



Part No.

1224S



Catch Basin Plastic & Metal Decorative Grates

Fits 12" Catch Basins. Available in Botanical and Wave designs, in multiple colors or in cast iron. Plastic grates are "T-top" and overlap basin edge. Iron grates sit flush.



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
1218S	12" x 12" Square Botanical Grate	Sand	8	3.27	10ND	12" Square Structural
1218GR	12" x 12" Square Botanical Grate	Green	8	3.27	10ND	Foam Polyolefin Botanical Grate with UV inhibitor.
1218GY	12" x 12" Square Botanical Grate	Gray	8	3.27	10ND	Open surface area 24.44
1218	12" x 12" Square Botanical Grate	Black	8	3.27	10ND	square inches. 74.77 GPM.
839	#6 x 1-3/4 FH Phillips Screw	Metal	40	n/a	10ND	Class B load rated.
	Use Screw # 839, FH#6 x 1-3/4". (see page 79). ADA Compliant.					

Pkg.

Pkg.

Qty.

8

8

8

8

40

Wt. Ea.

Wt. Ea.

10ND

10ND

10ND

10ND

10ND

(lbs.)

2.68

2.68

2.68

2.68

n/a



** * *				()	
1218CI	12" x 12" Square Botanical Cast Iron Grate	Raw Iron	1	12.67	10ND
629	#20 x 1-1/2 FH Phillips Screw	Metal	40	n/a	10ND
	Use Screw # 629, FH#20 x 1-1/2".				

Color

Sand

Green

Gray

Black

Metal


Product Class	Specifications					
10ND	12" Square Cast Iron Botanical Grate. Open					
10ND	surface area 24.44 square inches. 74.77 GPM. Class B					
	load rated.					
Product Class	Specifications					

12" Square Structural Foam Polyolefin Wave

Grate with UV inhibitor.

Open surface area 25.67

square inches. 78.53 GPM. Class B load rated.



1224GR	12" x 12" Square Wave Grate
1224GY	12" x 12" Square Wave Grate
1224	12" x 12" Square Wave Grate
839	#6 x 1-3/4 FH Phillips Screw
	Use Screw # 839, FH#6 x 1-3/4".

12" x 12" Square Wave Grate


Description

	(600 pago 10). HBM Oomphant.					
Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
1224Cl 629	12" x 12" Square Wave Cast Iron Grate #20 x 1-1/2 FH Phillips Screw	Raw Iron Metal	1 40	13.90 n/a	10ND 10ND	12" Square Cast Iron Wave Grate. Open surface area
	Use Screw # 629, FH#20 x 1-1/2". (see page 79). ADA Compliant.					25.60 square inches. 78.31 GPM. Class B load rated.

11	13/16
*	delining this
1 1/8"	A Children of the Control of the Con
1 %"	3/" Grata Opaninga
	%" Grate Openings

Mini Channel Plastic & Metal Decorative Grates

Fits 500 Series Mini Channel. Available in Botanical and Wave designs, in multiple colors or in cast iron. Plastic grates are "T-top" and overlap basin edge. Iron grates sit flush.



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Sp
846	Stainless Steel Screws, FH #4 x 5/8"	Steel	64	0.10	25PF	3 ft
554S	3' Botanical Channel Grate	Sand	16	0.89		bota
554GR	3' Botanical Channel Grate	Green	16	0.89		are
554GY	3' Botanical Channel Grate	Gray	16	0.89		foo
554	3' Botanical Channel Grate	Black	16	0.89		1 ft
554CI	1' Botanical Cast Iron Channel Grate	Raw Iron	1	1.82		Cas
629	#20 x 1-1/2 FH Phillips Screw	Metal	40	n/a	10ND	sur
	(see page 79). ADA Compliant.					Cla

Specifications


3 ft. Structural Foam Polyolefin
botanical pattern Channel Grate
with UV inhibitor. Open surface
area 5.44 square inches per
foot. 16.64 GPM per foot.

1 ft. Mini Channel botanical Cast Iron Channel Grate. Open surface area 5.39 square inches per foot. 16.49 GPM per foot. Class B load rated.

3 ft. Structural Foam Polyolefin wave pattern Channel Grate with UV inhibitor. Open surface area 5.73 square inches per foot. 17.54 GPM per foot.

1 ft. Mini Channel Wave Cast Iron Channel Grate. Open surface area 4.11 square inches per foot. 12.56 GPM per foot. Class B load rated.


Specifications




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class
846	Stainless Steel Screws, FH #4 x 5/8"	Steel	64	0.10	25PF
555S	3' Wave Channel Grate	Sand	16	0.88	25PF
555GR	3' Wave Channel Grate	Green	16	0.88	
555GY	3' Wave Channel Grate	Gray	16	0.88	
555	3' Wave Channel Grate	Black	16	0.88	
555CI	1' Wave Cast Iron Channel Grate	Raw Iron	1	1.30	
629	#20 x 1-1/2 FH Phillips Screw	Metal	40	n/a	10ND
*	(see page 79). ADA Compliant.				

Spee-D® Channel Plastic & Metal Decorative Grates

Fits Spee-D® Channel. Available in Botanical and Wave designs, in multiple colors or in cast iron. Plastic grates are "T-top" and overlap basin edge. Iron grates sit flush.



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
829	Stainless Steel Screws, FH #8 x 1"	Steel	48	0.06	25PF	2 ft. Structural Foam Polyolefin
252S	2' Channel Botanical Grate	Sand	24 ft.	1.74	25PF	decorative botanincal Channel Grate with UV inhibitor. Open
252GR	2' Channel Botanical Grate	Green	24 ft.	1.74	25PF	surface area 7.78 square inches
252GY	2' Channel Botanical Grate	Gray	24 ft.	1.74	25PF	per foot. 23.80 GPM per foot.
252	2' Channel Botanical Grate	Black	24 ft.	1.74	25PF	2 ft. Cast Iron decorative
252CI	2' Cast Iron Channel Botanical Grate	Raw Iron	1 ft.	7.06	25PF	botanincal Channel Grate. Open
629	#20 x 1-1/2 FH Phillips Screw	Metal	40	n/a	10ND	surface area 8.99 square inches per foot. 27.50 GPM per foot.
	(see page 79). ADA Compliant.	Class B load rated.				



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
829	Stainless Steel Screws, FH #8 x 1"	Steel	48	0.06	25PF	2 ft. Structural Foam Polyolefin
253S	2' Channel Wave Grate	Sand	24 ft.	1.84	25PF	decorative wave Channel Grate with UV inhibitor. Open surface
253GR	2' Channel Wave Grate	Green	24 ft.	1.84	25PF	area 7.78 square inches per
253GY	2' Channel Wave Grate	Gray	24 ft.	1.84	25PF	foot. 23.80 GPM per foot.
253	2' Channel Wave Grate	Black	24 ft.	1.84	25PF	2 ft. Cast Iron decorative wave
253Cl	2' Cast Iron Channel Wave Grate	Raw Iron	2 ft.	7.52	25PF	Channel Grate. Open surface
629	#20 x 1-1/2 FH Phillips Screw	Metal	40	n/a	10ND	area 7.41 square inches per foot. 22.67 GPM per foot. Class
	(see page 79). ADA Compliant.	B load rated.				




Dura Slope Metal Decorative Grates

Fits all Dura Slope channels. Available in five designs: Weave, Tile, Brick, Diamond and Slot. Ductile iron material, rated Class D and ADA compliant.




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications				
DS-601	Weave Pattern	Raw Iron	1	14.50	25DS	Decorative grates are made of ductile iron.				
DS-602	Diamond Pattern	Raw Iron	1	14.30	25DS	Weave: open area 6.75 square inches per foot;				
DS-603	Tile Pattern	Raw Iron	1	14.70	25DS	20.65 GPM. Diamond: open area 9.55 square				
DS-604	Brick Pattern	Raw Iron	1	14.30	25DS	inches per foot; 29.21 GPM. Tile: open area 7.95 square inches per foot; 24.32 GPM. Brick: open area 11.35 square				
DS-609	Deco Slot	Raw Iron	1	14.50	25DS					
85400401	DS DUCTL KIARO HP/ADA "B", 2FT	Ductile Iron	120	14.99	25DS	inches per foot; 34.725 GPM. Deco slot : open area				
85400402	DS DUCTL VIA HP/ADA "B", 2FT	Ductile Iron	120	10.36	25DS	16.75 square inches per foot; 51.24 GPM.				
85400403	DS DUCTL VILLE HP/ADA "B", 2FT	Ductile Iron	120	11.68	25DS					
	Use with Dura Slope Drains (page 72), Dura Slope C	Catch Basins (page 74).								
	Decorative grates are made of ductile iron. Uncoate Additional powder-coat colors available: Black (K), V Orange (O), Gray (Y), Brown (N)									
	MTO 6-7 week lead time.									
	(see page 79). ADA Compliant/Heelproof. Must be use	(see page 79). ADA Compliant/Heelproof. Must be used with DS-200H to acheive Class D Load Rating.								

Round Grates



3/16" Grate Opening

Part No.	Description	Color	Pkg. Qty.	Wt. Ea. lbs.	Product Class	Specifications
14	3" Round Grate	Black	40	0.13	10ND	3" Round Structural Foam Polyolefin Grate with UV inhibitor. Open surface area 2.60 square inches. 7.95 GPM.
15	3" Round Grate	Gray	40	0.13	10ND	
16	3" Round Grate	Green	40	0.13	10ND	
16P	3" Round Grate	Purple	40	0.13	10ND	
16S	3" Round Grate	Sand	40	0.13	10ND	
广	Fits 3" Sewer and Drain Pipe & Fittings, 3" Corruga (see page 79). ADA Compliant/Heel-proof.					



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications				
11	4" Round Grate	Black	25	0.17	10ND	4" Round Structural Foam				
12	4" Round Grate	Gray	25	0.17	10ND	Polyolefin Grate with UV inhibitor. Open suraface area 3.85 square inches. 11.78 GPM.				
13	4" Round Grate	Green	25	0.17	10ND					
13P	4" Round Grate	Purple	25	0.17	10ND					
13S	4" Round Grate	Sand	25	0.17	10ND					
†	Fits 4" Sewer and Drain Pipe & Fittings, 4" Corruga (see page 79). ADA Compliant/Heel-proof.									


Round Grates



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. lbs.	Product Class	Specifications
40	6" Round Grate	Black	10	0.49	10ND	6" Round Structural Foam
50	6" Round Grate	Green	10	0.49	10ND	Polyolefin Grate with UV inhibitor. Open surface area 9.10 square inches. 27.84 GPM.
60	6" Round Grate	Gray	10	0.49	10ND	
60S	6" Round Grate	Sand	10	0.49	10ND	
×	Fits Spee-D® Basin, 6" Sewer and Drain Pipe & Fitti (see page 79). ADA Compliant/Heel-proof.					



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. lbs.	Product Class	Specifications
10	8" Round Grate	Black	10	0.60	10ND	8" Round Structural Foam Polyolefin Grate with UV inhibitor. Open surface area 11.50 square inches. 35.18 GPM.
20	8" Round Grate	Green	10	0.60	10ND	
30	8" Round Grate	Gray	10	0.60	10ND	
30S	8" Round Grate	Sand	10	0.60	10ND	
*	Fits Spee-D® Basin, 6" Sewer and Drain Pipe & Fitti					
\(\)	(see page 79). ADA Compliant.					




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications
1040	10" Round Grate	Black	10	1.01	10ND	10" Round Structural Foam Polyolefin Grate with UV inhibitor. Open surface area 21.57 square inches. 65.99 GPM.
1050	10" Round Grate	Green	10	1.01	10ND	
1060	10" Round Grate	Gray	10	1.01	10ND	
1060S	10" Round Grate	Sand	10	1.01	10ND	
j.	Fits 8" Sewer and Drain Pipe & Fittings, 8" Corruç					
Ķ	(see page 79). ADA Compliant.					



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications
1240	12" Round Grate	Black	6	2.44	10ND	12" Round Structural Foam Polyolefin Grate with UV inhibitor. Open surface area 46.00 square inches. 140.72 GPM.
1250	12" Round Grate	Green	6	2.44	10ND	
1260	12" Round Grate	Gray	6	2.44	10ND	
	Fits 12" Sewer and Drain Pipe, 12" Corrugated Pipe					110.72 01 111.
	(see page 79)					




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications
1511	15" Round Grate	Black	6	6.89	10ND	15" Round Structural Foam Polyolefin Grate with
1512	15" Round Grate	Green	6	6.89	10ND	UV inhibitor. Open surface
	Fits 15" Sewer and Drain Fittings, 15" Corrugated P (see page 79)	area 85.60 square inches. 261.86 GPM.				




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications		
1801SDG	18" Round Grate	Green	1	7.50	28ND	Round Polypropylene		
~	Fits 18" Sewer and Drain Fittings, 18" Corrugated P (see page 79)	ipe, includes Lag Bolts.				Grate. Open surface area 75.55 square inches. 231.12 GPM. Includes lag bolts.		




Atrium Grates




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications		
270	2" Atrium Grate	Gray	20	0.10	10ND	Flat-Top PVC Atrium Grate		
	Fits 2" Schedule 40 Fittings.					with UV inhibitor. Open surface area 4.00 square inches. 12.24 GPM.		



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications
70	3" Atrium Grate	Green	20	0.16	10ND	Flat-Top Structural Foam Polyolefin Atrium Grate with UV inhibitor. Open surface area 9.40 square inches. 28.76 GPM.
72	3" Atrium Grate	Gray	20	0.16	10ND	
74	3" Atrium Grate	Black	20	0.16	10ND	
74S	3" Atrium Grate	Sand	20	0.16	10ND	
	Fits 3" Sewer and Drain Pipe & Fittings, 3" Corrugat					




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications
75	4" Atrium Grate	Green	20	0.21	10ND	Flat-Top Structural Foam Polyolefin Atrium Grate with UV inhibitor. Open surface area 17.00 square inches. 52,01 GPM.
76	4" Atrium Grate	Gray	20	0.21	10ND	
78	4" Atrium Grate	Black	20	0.21	10ND	
78S	4" Atrium Grate	Sand	20	0.21	10ND	
	Fits 4" Sewer and Drain Pipe & Fittings, 4" Corruga					




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications
80	6" Atrium Grate	Green	10	0.62	10ND	Flat-Top Structural Foam
81	6" Atrium Grate	Gray	10	0.62	10ND	Polyolefin Atrium Grate with UV inhibitor. Open
90	6" Atrium Grate	Black	10	0.62	10ND	surface area 28.40 square inches, 86.88 GPM.
90S	6" Atrium Grate	Sand	10	0.62	10ND	
	Fits Spee-D® Basin, 6" Sewer and Drain Pipe & Fitting	ngs, 6" Corrugated Pipe	э.			


Square Grates



Part N	lo.	Description	Color	Pkg. Qty.	Wt. Ea. lbs.	Product Class	Specifications
1		4" Square Grate	Green	40	0.11	10ND	4" Square Structural Foam
2		4" Square Grate	Black	40	0.11	10ND	Polyolefin Grate with diagonally converging
3		4" Square Grate	Gray	40	0.11	10ND	pattern with UV inhibitor. Open surface area 3.45
1	•	Fits 3" Sewer and Drain Pipe & Fittings, 3" Corrugat	ed Pipe, and 3" Triple V	Vall Pipe.			square inches. 10.55 GPM.
/)	(see page 79). ADA Compliant/Heel-proof.					



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications			
7	5" Square Grate	Green	25	0.20	10ND	5" Square Structural Foam			
8	5" Square Grate	Black	25	0.20	10ND	Polyolefin Grate with diagonally converging			
9	5" Square Grate	Gray	25	0.20	10ND	pattern with UV inhibitor. Open surface area 4.25			
*	Fits 4" Sewer and Drain Pipe & Fittings, 4" Corrugated Pipe, and 4" Triple Wall Pipe.								
\wedge	(see page 79). ADA Compliant/Heel-proof.								




4"	Grate	Open	ina
7	G. G.O	O P 0	ອ

Part No.	Description	Color	Pkg. Qty.	Wt. Ea. lbs.	Product Class	Specifications
4	6" Square Grate	Black	10	0.40	10ND	6" Square Structural Foam
5	6" Square Grate	Green	10	0.40	10ND	Polyolefin Grate with diagonally converging
6	6" Square Grate	Gray	10	0.40	10ND	pattern with UV inhibitor. Open surface area 10.40
06S	6" Square Grate	Sand	10	0.40	10ND	square inches. 31.81 GPM.
广	Fits 3" or 4" Sewer and Drain Pipe, 3" or 4" Corruga (see page 79). ADA Compliant/Heel-proof.	ated Pipe, and 3" or 4"	Triple Wall Pi	De.		



1/4" Grate Opening

Part No.	Description	Color	Pkg. Qty.	Wt. Ea. lbs.	Product Class	Specifications
640	6" x 6" x 4" Square Grate & Adapter	Black	8	0.83	10ND	6"x6" Low-Profile Adapter
641	6" x 6" x 4" Square Grate & Adapter	Green	8	0.83	10ND	and Structural Foam Polyolefin Removable
642	6" x 6" x 4" Square Grate & Adapter	Gray	8	0.83	10ND	Grate with UV inhibitor and stainless steel screws.
*	Fits 3" or 4" Sewer and Drain Pipe & Fittings, 3" or (see page 79). ADA Compliant/Heel-proof.	4" Corrugated Pipe, an	d 3" or 4" Trip	ole Wall Pipe.		Open surface area 14.44 square inches. 44.17 GPM.




1/,11	Grate	Openi	n

Part No.	Description	Color	Pkg. Qty.	Wt. Ea. lbs.	Product Class	Specifications
637 639	6" x 6" x 6" Square Grate & Adapter 6" x 6" x 6" Square Grate & Adapter	Black Gray	8	0.88 0.88	10ND 10ND	6"x6" Low-Profile Adapter and Structural Foam Polyolefin Removable
Ķ	Fits Spee-D® Basin, 6" Sewer and Drain Pipe & Fitti (see page 79). ADA Compliant/Heel-proof.	ngs.				Grate with UV inhibitor and stainless steel screws. Open surface area 14.44 square inches. 44.17 GPM.




GRATES: STANDARD, DECORATIVE & METAL / SPEE-D® BASINS

Square Grates (continued)




Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications
771	7" Square Grate	Black	10	0.65	10ND	7" Square Structural Foam
772	7" Square Grate	Green	10	0.65	10ND	Polyolefin Grate with UV inhibitor. Open surface
773	7" Square Grate	Gray	10	0.65	10ND	area 13.60 square inches. 41.60 GPM.
773S	7" Square Grate	Sand	10	0.65	10ND	
大	Fits Spee-D® Basin, 6" Sewer and Drain Pipe & Fitti (see page 79). ADA Compliant/Heel-proof.	ngs, 6" Corrugated Pip	e.			



1/4"	Grate	Opening


Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications
881	8" Square Grate	Black	10	0.79	10ND	8" Square Structural Foam
882	8" Square Grate	Green	10	0.79	10ND	Polyolefin Grate with UV inhibitor. Open surface
883	8" Square Grate	Gray	10	0.79	10ND	area 17.16 square inches. 52.49 GPM.
883S	8" Square Grate	Sand	10	0.79	10ND	<u> </u>
*	Fits Spee-D® Basin, 6" Sewer and Drain Pipe & Fitti					
\wedge	(see page 79). ADA Compliant/Heel-proof.					




5/16" Grate Opening

Part No.	Description	Color	Pkg. Qty.	Wt. Ea. Ibs.	Product Class	Specifications		
950	9" Square Grate	Green	10	1.11	10ND	9" Square Structural Foam		
960	9" Square Grate	Gray	10	1.11	10ND	Polyolefin Grate with UV inhibitor. Open surface		
970	9" Square Grate	Black	10	1.11	10ND	area 28.40 square inches. 86.88 GPM.		
970S	9" Square Grate	Sand	10	1.11	10ND	00.00 u		
*	Fits Spee-D® Basin, 6" Sewer and Drain Pipe & Fittings, 6" Corrugated Pipe.							
济	(see page 79). ADA Compliant.							


Duracast™ In-Line Grates



Р	art No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications	
D	6	6" Round Grate	10ND	6" Round Heavy-Duty				
		Fits 6" Corrugated and Sewer and Drain Pipe. D6 is not a custom grate and qualifies for normal N0 Fits SPEE-D® Basin.	Ductile Grate with Black Paint. Open surface area 7.05 square inches. 21.57 GPM. H-20 load rating.					
		(see page 79)					G 20 1000 10001g.	



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
D8	8" Round Grate	1	14.59	10ND	8" Round Heavy-Duty	
	Fits 8" Corrugated and Sewer and Drain Pipe. D8 is not a custom grate and qualifies for normal NDS freight terms. (see page 79)					Ductile Iron Grate with Black Paint. Open surface area 13.98 square inches. 42.77 GPM. Bolt holes for added security. H-20 load rating.



Part No.	Description	Pkg. Color Qty.		Wt. Ea. (lbs.)	Product Class	Specifications	
D10	10" Round Grate	Black	1	20.60	10ND	10" Round Heavy-Duty	
	Fits 10" Corrugated and Sewer and Drain Pipe. D10 is not a custom grate and qualifies for normal NDS freight terms. (see page 79)				Ductile Iron Grate with Black Paint. Open surface area 26.82 square inches. 82.05 GPM. Bolt holes for added security. H-20 load rating.		



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications	
D12H-W0	12" Square Hinged Cast Iron Grate without Adapter	Black	1	48.00	10ND	H-20 load rating. Open surface area 48.30 square inches. 147.76 GPM.	
D12	12" Round Grate	Black	1	16.00	10ND		
	Fits 12" Corrugated and Sewer and Drain Pipe. (see page 79)					H-20 load rating. Open surface area 55.16 square inches. 169.74 GPM.	



DRAINAGE PRODUCTS INDEX

Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page
1	47	252GR	43	908PC	40	1218	30, 42	2411	34
2	47	252GY	43	909B	40	1218CI	30, 42	2412	34
3	47	252S	43	910B	40	1218GR	30, 42	2413	34
3C05	21, 38	253	43	913	27	1218GY	30, 42	2415	34
3C06	21, 38	253Cl	43	913B	41	1218S	30, 42	2418	34
3p02	38	253GR	43	914PB	41	1220	31	85400401	44
4	47	253GY	43	915	28	1221	31	85400402	44
4C06	21, 38	253S	43	915SC	40	1222	31	85400403	44
4C07	21, 38	270	46	916	27	1224	31, 42	D6	49
4p02	38	300	26	917SC	40	1224Cl	31, 42	D8	49
5	47	321	36	918B	40	1224GR	31, 42	D10	49
6	47	350	26	919PB	40	1224GY	31, 42	D12	49
6C06	21, 38	351	38	920B	41	1224S	31, 42	D12H-W0	49
6C07	21, 38	420	36	921B	41	1225	29	DS-601	44
6P02	38	421	36	922PB	41	1230	31	DS-602	44
06S	47	430	37	923PB	41	1230ATBLKIT	31	DS-603	44
7	47	451	38	930	28	1230B	30, 41	DS-604	44
8	47	552B	40	930ATBLKIT	28	1230GRKIT	31	DS-609	44
9	47	553	43	930B	27, 41	1240	45	EZ-101F	21
10	45	553PB	40	930GRKIT	28	1241	37	EZ-0701A	21
11	44	554Cl	43	931	28	1242	35	EZ-0701F	21
12	44	554GR	43	932	28	1243	35	EZ-1001A	21
13	44	554GY	43	933	28	1245	35	EZ-1001F	21
13P	44	554S	43	950	48	1250	45	EZ-1501A	21
13S	44	555	43	960	48	1260	45	EZ-1501F	21
14	44	555CI	43	970	48	1266	35	EZ-1501F/EZ-1501FB	21
15	44	555GR	43	970S	48	1280	30	FWAS24CWH	25
16	44	555GY	43	980	27	1290	30	FWAS24WH	25
16P	44	555S	43	981	27	1511	45	FWBP24	25
16S	44	620	37	990	27	1512	45	FWFF67	25
20	45	624	37	991	27	1800	32	FWSD69	25
30	45	625	37	999	27	1801SDG	45	FWSPS3WH	25
30S	45	629	30, 31, 42, 43	999S	27	1804	32	pvc	38
40	45	637	47	1040	45	1810	32	SC-1820-C-0	23
50	45	639	47	1050	45	1811	32	SC-1820-E-0	23
60	45	640	47	1060	45	1812	32	SC-1820-M-0	23
60S	45	641	47	1060S	45	1813	32	SC-1820-S-0	23
70	46	642	47	1200	29	1815	33	SC-3020P	23
72	46	651	38	1200BLKIT	29	1816	32	SC-3475-C-0	23
74	46	771	48	1200DGBLKITWH	29	1820	33	SC-3475-E-0	23
74S	46	772	48	1200DGGKITWH	29	1821	33	SC-3475-M-0	23
75	46	773	48	1200FF	29	1822	33	SC-3475-S-0	23
76	46	773S	48	1200GRKIT	29	1828	33	SC-3475W-C-0	23
78	46	829	43	1200KITDISP	29	1830	33	SC-3475W-E-0	23
78B	41	839	30, 31, 42	1200NGB	29	1840	33	SC-3475W-M-0	23
78S	46	846	43	1200NGBKIT	29	1881	32	SC-3475W-S-0	23
80	46	881	48	1203	29	1882	32	SC-44105-C-0	23
81	46	882	48	1204	29	1882BLKIT	32	SC-44105-E-0	23
90	46	883	48	1206	35	1882GRKIT	32	SC-44105-M-0	23
90B	41	883S	48	1207	29	1884	32	SC-44105-S-0	23
90S	46	900	27	1208	29	1888	35	SC-CF-E	23
101	26	900-4	27	1210	30	1889	35	SC-FL-8	23
101ATBLKIT	26	900BLKIT	27	1211	30	1890	32	SC-FL-10	23
101GRKIT	26	900FF	27	1212	30	1891	32	SC-NWFF-500	23
101SQGRKIT	26	900GRKIT	27	1212S	30	2400	34	SC-ST	23
201	26	900KITDISP	27	1213	31	2400BLKIT	34	SC-WFF-75	23
250	26	905PB	40	1215	31	2400GRKIT	34		
252	43 43	906PB	40	1216	29	2404	34		
252Cl	43	907PB	40	1217	29	2410	34, 35		

NOTES						



Your knowledgeable and trusted partner for the best in water management solutions









ndspro.com

NDS Customer Service 851 N. Harvard Ave., Lindsay, CA 93247 Phone: 800.726.1994 · 559.562.9888 Fax: 800.726.1998 · 559.562.4488 Se Habla Español

Download our Mobile App - Search for NDS Drainage







A Proud Member of

