


Kuriyama of America, Inc.

360 E. State Parkway
Schaumburg, IL 60173-5335 USA

Phone: (847) 755-0360

Toll-Free FAX: (800) 800-0320

International FAX: (847) 885-0996 **Email:** sales@kuriyama.com

Series F52MCRX100, "Spa Hose" FMCR™ Series 2 in. ID and 100 ft Standard Length PVC Suction Hose

Made in the USA



[General Applications](#) | [Construction](#) | [Service Temperature Range](#) | [Features and Advantages](#) | [Nominal Specifications](#) | [Specifications](#) | [Warning](#) | [Product Warning](#) | [Note](#) | [Compliance Footnotes](#)

 General Applications -
General Applications

- Commonly referred to as "flex pipe"
- Drain lines
- Spa, pool and hot tub plumbing

 Construction -
Construction

PVC Tube With Rigid PVC Helix.

 Service Temperature Range -
Service Temperature [Min]

-20 °C
4 °F

-4 ~r

Service Temperature [Max]65 °C
150 °F

Features and Advantages

Features and Advantages

- **Precision Controlled OD** - Designed to be glued into Schedule 40 PVC fittings.
- **Easy Installation** - Ideal for working in confined areas. Permits installers to make smooth, tight turns. Requires fewer fittings than rigid pipe when plumbing a normal spa or hot tub application.

Nominal Specifications

IPS Size	2 in
OD	2.381 in 60.48 mm
Working Pressure at 68°F	70 psi
Working Pressure at 104°F	50 psi
Vacuum Rating at 68°F	28 inHg
Vacuum Rating at 104°F	24 inHg
Min. Bend Radius at 68°F	6 in
Standard Length	100 ft
Weight	0.58 lbs/ft

Specifications

Brand	Tigerflex®
Type	Precision Controlled OD

Style Commonly Referred to as "Flex Pipe"

Color Cream

Performance Easy Installation

Industry Standards/Certifications EU 2002/95/EC

Warning

Warning



WARNING

This product can expose you to DINP, which is known to the State of California to cause cancer or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Product Warning

Product Warning

Like other materials, Spa Hoses can be damaged by rodents or insects, including termites. Our warranty does not cover damages caused by them. Spa Hose should not be used underground in areas infested by termites. This product warning shall be given to every purchaser of Spa Hose. (Rev. 7/98)

Note

Note

Use with recommended primers and PVC cements; consult with glue supplier for recommendations. Coils of Tigerflex® Spa Hose should not be stacked more than five coils high. Hose which has been stacked high may be damaged over time.

Black color available upon request. Minimum order quantity may apply. Contact Kuriyama customer service for details.

Compliance Footnotes

Compliance Footnotes

RoHS - The product complies with the requirements of the EU directive 2002/95/EC which is on the restriction of the use of certain hazardous substances in electrical and electronic

equipment.