

SUPERSTOR GLASS LINED STORAGE

Storage Tanks



Features

- **DURABLE GLASS LINED STEEL TANK** constructed of thick steel
- **FULLY AUTOMATIC SURFACE MOUNTED THERMOSTAT** for controlling the temperature

Performance

- MEET OR EXCEED THE EFFICIENCY REQUIREMENTS OF ASHRAE STANDARD 90.1B-2001.
- ENVIRONMENTALLY SAFE CFC FOAM 1.5+ INCHES OF SUPER FOAM INSULATION FOR LOW STANDBY LOSS

Quality

- DURABLE GLASS LINED TANK
- DUAL MAGNESIUM ANODE ROD to prolong tank life
- 5 YEAR TANK WARRANTY FOR RESIDENTIAL USE



SPECIFICATIONS AND APPLICATION DATA

MODELS	NOMINAL CAPACITY (GAL)	WORKING PRESSURE (PSI)	HOT OUTLET (TOP)	FRONT CONNECTIONS
GL-50	50	150	3/4" NPT MALE	3/4" NPT MALE
GL-80	80	150	2" NPT MALE	2" NPT MALE
GL-119	119	150	2" NPT MALE	2" NPT MALE

DIMENSIONS & WEIGHT

MODEL	PRODUCT HEIGHT	PRODUCT DIAMETER	CIRCULATING PORT TOP	IRCULATING PORT BOTTOM	T&P HEIGHT	SHIPPING WEIGHT LBS
	A	B	C	D	E	
GL-50	19-1/4"	52"	14"	7"	45"	120
GL-80	23-1/4"	59"	13"	7"	51-1/4"	165
GL-119	28"	64"	13"	4"	55"	250

