



CONNECTIONS
 L - LOW SPEED
 C - COMMON
 H - HIGH SPEED

MODEL	REF.	CUSTOMER	HP.	VOLTS	AMPS	HZ.	R.P.M.	BEARING	PROTECTOR		
S63NXSSD-7946		STANDARD	1/2 / 1/8	115	7.5/4.0	60	1725/1140	SLEEVE	AUTOMATIC		
								ROTATION	CUST. PT. NO.		
								C.C.W. LEAD END	EC6765		
PAGE 1 OF 1	REVISION RECORD FOR: E.C.O. 212810			INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF EMERSON ELECTRIC COMPANY.							
REVISION DATE	E-NOTCH REMOVED FROM ENDSHIELDS ALL VIEWS										
	STATOR SCREWS AND NUTS ADDED										
	NOTES ABOUT MANUFACTURING OPTION REMOVED			ALL DIMENSIONS ARE FOR REFERENCE ONLY UNLESS TOLERANCE IS GIVEN.				TITLE	CODE	ITEM NO.	SIZE
ISSUED BY	REVIEWED BY	ENGINEER APPROVED	ASSEMBLED VIEW				VO1	730512	A		
E. TREJO	V. LOREDO	T. BOSSALLER									