



# RECTORSEAL® HI-TEMP

## Silicone Caulk

### DESCRIPTION:

---

RectorSeal® HI-TEMP 100% RTV silicone caulk is a one component sealant which cures to a strong durable resilient elastomer. It will adhere to glass, clean metal, most types of non-oily woods, vulcanized silicone rubber, silicone resins, natural and synthetic fibers, ceramic, paper, as well as many painted and plastic surfaces.

Meets the following specifications: USDA for use in federally inspected meat and poultry plants. F.D.A. reg. #21 CFR 177.2600, TT-S-001543A (COM-NBS) Class A, TT-S00230C (COM-NBS) Class A MIL-A-46106B Amend 3, Type 1, and Canadian 19-GP-9MA, Type 1.

### CHARACTERISTICS:

---

- -75½ to +650½ F Service Temp
- Insulates
- Vibration Resistant
- Bonds
- Remains Flexible
- Seals
- USDA Approved

### APPLICATIONS:

---

RectorSeal® HI-TEMP caulk can be used for bonding gaskets in heating and refrigeration units, filleting and caulking joints in sheetmetal stacks, ductwork and equipment housing, sealing windows in oven doors and flues on gas appliances, flanged pipe joints and access doors, glaze windows, and anywhere a tight leakproof seal is required to weatherproof, protect and insulate. RectorSeal® HI-TEMP can be used to control noise and vibration and as a pipe and tank sealer.

### PACKAGING:

---

Code	Size	Qty. Per Case	Lbs. Per Case	Cu. Ft. Per Case
57500	10.1 Fl. Oz. Tube	24	22	0.65

# RECTORSEAL® HI-TEMP

## Silicone Caulk

### INSTRUCTIONS:

---

#### READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING

1. Clean and dry all surfaces. Completely remove all dirt, grease and soap.
2. Cut nozzle at desired bead size, apply bead of silicone.
3. Most paint will not adhere to silicone. Surface should be painted first, then seal.
4. Silicone "skins over" and becomes tack-free in 15 minutes, cures in 1 hour. Allow 24 hours for full cure and strength.

For additional technical information, call Toll Free 1-800-231-3345.

### PRECAUTIONS:

---

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,  
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

#### CAUTION!

Uncured caulk causes irritation

**Caulk releases acetic acid (vinegar-like odor) during cure. PRECAUTIONS:** Avoid contact with eyes and skin. Contact lens wearers take appropriate precautions. **FIRST AID: Eyes** - Flush eyes with water. Call physician. **Skin** - Remove from skin with a dry cloth or paper towel. **Ingestion** - DO NOT INDUCE VOMITING. Only if conscious, give large amounts of water. **FIRE AND SPILLS:** For fire, use water fog, CO<sub>2</sub>, foam, or dry chemicals. Wipe up spills to prevent footing hazard. **STORAGE AND HANDLING:** Store in cool area. Keep container tightly closed. Do not reuse empty container. **KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Material Safety Data Sheet.

### SPECIFICATIONS:

---

Wt/Gal @ 77° F	8.9 ± .5 lbs./gal.
Flash Point SETA CC	N/A
Color	Red
Shelf Life	1 year minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

### LIMITED WARRANTY:

---

RectorSeal makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal shall not be liable for incidental or consequential damages.

MANUFACTURED IN U.S.A.

RectorSeal • 2601 Spenwick Drive • Houston, Texas 77055-1035

Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051

[www.rectorseal.com](http://www.rectorseal.com)