

THICK WALL SDS MAX AND SPLINE TWO-PIECE CORE BITS

Size	Depth	Core Body with Guide Plate and Centering Pin Part No.	12" SDS Max Adapter Shank Part No.	18" SDS Max Adapter Shank Part No.	12" Spline Adapter Shank Part No.	18" Spline Adapter Shank Part No.	7-1/2" Extension Part No.	Replacement Guide Plate Part No.	Replacement Centering Pin Part No.
4"	4-1/16"	48-20-5155	48-03-3572	48-03-3573	48-03-3564	48-03-3565	48-95-6085	48-20-5174	48-20-5199
5"	4-1/16"	48-20-5160	48-03-3572	48-03-3573	48-03-3564	48-03-3565	48-95-6085	48-20-5175	48-20-5199
6"	4-1/16"	48-20-5165	48-03-3572	48-03-3573	48-03-3564	48-03-3565	48-95-6085	48-20-5176	48-20-5199

THIN WALL SDS MAX AND SPLINE TWO-PIECE CORE BITS

Size	Depth	Core Body with Guide Plate and Centering Pin Part No.	12" SDS Max Adapter Shank Part No.	18" SDS Max Adapter Shank Part No.	12" Spline Adapter Shank Part No.	18" Spline Adapter Shank Part No.	7-1/2" Extension Part No.	Replacement Guide Plate Part No.	Replacement Centering Pin Part No.
5"	2-13/16"	48-20-5060	48-03-3574	-	48-03-3540	-	48-95-6075	48-20-6162	48-20-6155
6"	2-13/16"	48-20-5065	48-03-3574	-	48-03-3540	-	48-95-6075	48-20-6163	48-20-6155

2-CUTTER SPLINE DRILL BITS

OVERVIEW

MILWAUKEE's Spline 2-Cutter Rotary Hammer-Drill Bits are used for drilling into brick, block, and concrete.


FEATURES

- Highest Quality Carbide maximizes material pulverization
- 2-Cutter Head
- Spline Shank



2-CUTTER SPLINE DRILL BITS

Diameter	Usable Length	Length	Part No.	Diameter	Usable Length	Length	Part No.	Diameter	Usable Length	Length	Part No.
3/8"	5"	10"	48-20-4037	5/8"	17"	22"	48-20-4064	1-1/8"	11"	16"	48-20-4112
1/2"	5"	10"	48-20-4050	11/16"	11"	16"	48-20-4068	1-1/8"	17"	22"	48-20-4113
1/2"	11"	16"	48-20-4051	3/4"	5"	10"	48-20-4075	1-1/4"	11"	16"	48-20-4125
1/2"	17"	22"	48-20-4052	3/4"	11"	16"	48-20-4076	1-1/4"	17"	22"	48-20-4126
1/2"	22"	27"	48-20-4053	3/4"	17"	22"	48-20-4078	1-3/8"	11"	16"	48-20-4137
1/2"	31"	36"	48-20-4054	13/16"	11"	16"	48-20-4081	1-3/8"	17"	22"	48-20-4138
9/16"	5"	10"	48-20-4056	7/8"	11"	16"	48-20-4087	1-1/2"	11"	16"	48-20-4150
9/16"	18"	23"	48-20-4057	7/8"	17"	22"	48-20-4088	1-1/2"	17"	22"	48-20-4151
5/8"	5"	10"	48-20-4062	1"	11"	16"	48-20-4100				
5/8"	11"	16"	48-20-4063	1"	17"	22"	48-20-4101				



4-CUTTER SPLINE DRILL BITS

OVERVIEW

MILWAUKEE's Spline 4-Cutter Rotary Hammer-Drill Bits features a 4-Cutter 4x90° tip geometry to avoid lock up in rebar, patented rebar chamfers for increased durability, and a high-volume flute for fast debris removal. Used for drilling holes in brick, block, concrete, and reinforced concrete.



FEATURES

- 4-Cutter 4x90° Geometry to avoid lock up in rebar
- Patented Rebar Chamfers for increased durability
- High-Volume Flute for fast debris removal

4-CUTTER SPLINE DRILL BITS

Diameter	Usable Length	Length	Part No.	Diameter	Usable Length	Length	Part No.
5/8"	5"	10"	48-20-4300	7/8"	31"	36"	48-20-4367
5/8"	11"	16"	48-20-4305	1"	11"	16"	48-20-4370
5/8"	17"	22"	48-20-4310	1"	17"	22"	48-20-4375
5/8"	24"	29"	48-20-4315	1"	31"	36"	48-20-4380
5/8"	31"	36"	48-20-4320	1-1/8"	11"	16"	48-20-4385
11/16"	11"	16"	48-20-4325	1-1/8"	17"	22"	48-20-4390
3/4"	5"	10"	48-20-4330	1-1/4"	11"	16"	48-20-4395
3/4"	11"	16"	48-20-4335	1-1/4"	17"	22"	48-20-4400
3/4"	17"	22"	48-20-4340	1-1/4"	31"	36"	48-20-4405
3/4"	24"	29"	48-20-4345	1-3/8"	17"	22"	48-20-4410
3/4"	31"	36"	48-20-4350	1-1/2"	17"	22"	48-20-4415
7/8"	11"	16"	48-20-4360	1-3/4"	18"	23"	48-20-4418
7/8"	17"	22"	48-20-4365	2"	18"	23"	48-20-4419

