



4700 W. 160th St.
Cleveland, OH 44135
PH:800-321-9532
FX:800-321-9535
www.oatey.com

TECHNICAL SPECIFICATION

CLEAR THREAD CUTTING OIL



TECHNICAL SPECIFICATION: Oatey Clear Thread Cutting Oil is formulated with activated sulfur to wet, lubricate and cool dies during threading process. Clear Cutting Oil is designed for use with hand threading tools or low rpm threading machine operations for threading steel and brass pipe.



COMMON APPLICATIONS

Oatey Clear Thread Cutting Oil is designed for use with hand threading tools or low-rpm pipe threading machines.

Consult Oatey Technical Department for applications not specifically referenced above.

INGREDIENTS

Petroleum Hydrocarbon Mixture

PHYSICAL/CHEMICAL PROPERTIES

Specific Gravity	0.91
Solubility in Water	Insoluble
Flash Point	325° F (minimum)
Shelf Life	1 year from manufacture date
Appearance	Transparent Amber Liquid
Odor	Petroleum odor
Viscosity	175 Saybolt Univ. @ 100° F

DIRECTIONS FOR USE

Cover the surface with oil before the dies come into contact with the pipe. Oil flow should hit the point of friction for best results.

PRECAUTIONS

Read all cautions and directions carefully before using this product. Wear safety glasses with side shields to protect eyes from metal shavings. Do not wear loose gloves or clothing around rotating equipment. Avoid contact with eyes or skin. Prolonged or repeated skin contact may cause irritation. Avoid breathing vapor, mist or fumes. Use with adequate ventilation. Wash thoroughly after handling. NOT FOR USE ON STAINLESS STEEL OR SOFT METALS SUCH AS ALUMINUM. Keep container closed when not in use. DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN.

Refer to material safety data sheet for more information.
For emergency first aid help, call 1-303-623-5716 COLLECT.

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
30200	16 oz. Clear Cutting Oil	12	13 lbs.
30201	32 oz. Clear Cutting Oil	12	26 lbs.
30202	Gallon Clear Cutting Oil	6	50 lbs.