

## 00® Timers/Aquastat

Effective: December 10, 2015

Supersedes: June 18, 2014

Job: \_\_\_\_\_ Engineer: \_\_\_\_\_ Contractor: \_\_\_\_\_ Rep: \_\_\_\_\_

| ITEM NO. | MODEL NO. |  |
|----------|-----------|--|
|          |           |  |

**24 Hour Analog Clock Timer**  
**Performance Data — #265-1**

Electrical Characteristics: 115/60/1  
 Timer Switch: 16A @115V  
 Timer Interval: 15 Minutes  
 Clock face: Hour and Minute Hands  
 Manual Switch: **I** Permanently ON  
                   ⌚ Automatic Operation  
                   **O** Permanently OFF

**7 Day Digital Timer**  
**Performance Data — #265-3**

Electrical Characteristics: 115/60/1  
 Timer Switch: 16A @115V  
 Timer Interval: 1 Minute (+) Adjustable  
 Clock face: Digital with  
 Circulator Programming  
 Capacitor Backup: 2,500 hours

**Temperature Aquastat — Snap**  
**Action Temperature Switch — #563-2**

Electrical Characteristics: 115/60/1  
 Connections: 1/2" (Snap on circ. body)  
                   3/4" Copper pipe  
 Temperature Setting: ON @ 95°F  
                                   OFF @ 115°F  
 Contacts: 7 amp SPDT Switch  
 Wire Leads: 18" – Type 18-2,  
                   Round Premium Cable

**Application**

The Taco Clock Timers and Temperature Aquastat are designed to control the operation of Taco circulators on Domestic Hot Water Recirculation Systems for maximum comfort and energy efficiency. They are adaptable to any 00® Series circulator by attaching the enclosure or wiring to the electrical box.

**24 Hour Analog Timer**

Operates the circulator at the same pre-set times every day. Time intervals are in 15 minute increments. This user friendly clock has a raised minute hand for easy adjustments, quick-set trippers and an operation switch for Manual ON/OFF or Automatic modes.

**7 Day Digital Programmable Timer**

Digital Timer can be programmed to operate at different times on different days, weekdays or weekends, for maximum comfort and convenience to match family schedules. Easy circular programming clock face and LCD readout screen. Run time intervals as short as 1 minute provides maximum energy efficiency. A capacitor backup saves settings for up to 2,500 hours during power outages.

**Temperature Aquastat**

Controls pump operation to maintain system temperature between 95°F and 115°F. Easy clip-on Aquastat attaches directly to 3/4" pipe or a 1/2" sweat pump casing.

**Shipping Weight**

| Model | Item          | Lbs. | Kg  |
|-------|---------------|------|-----|
| 265-1 | Analog Timer  | .75  | .35 |
| 265-3 | Digital Timer | .75  | .35 |
| 563-2 | Aquastat      | .25  | .11 |



**FOR INDOOR USE ONLY**

