


AHEAD OF THE FLOW®

## **Quarter-Turn Boiler Drains**

125 lb. CWP to 100°F Maximum Temperature 180°F


## QUARTER-TURN BOILER DRAINS MATERIAL LIST

PART	SPECIFICATION			
Screw	Steel			
I.D. Tag	Aluminum			
Handle	Zinc			
Stem	Brass ASTM B 16 UNS C36000			
0-Ring	Nitrile			
Seat	PTFE			
Ball	Brass ASTM B 16 UNS C36000			
Adapter	Brass ASTM B 283 UNS C37700			
Body	Brass ASTM B 283 UNS C37700			



DESCRIPTION	NOM. SIZE	DIMENSIONS		APPROX.
		Α	В	NET WT.
BOILER DRAIN	1/2	2.64"	1.57"	.42 lb
FIP to Hose	3/4	2.72"	1.65"	.46 lb

IAPMO Listed to cUPC®



DESCRIPTION	NOM. SIZE	DIMENSIONS		APPROX.
		Α	В	NET WT.
<b>BOILER DRAIN</b> Cup or MIP  Threads to Hose	1/2"	2.64"	1.57"	.40 lb
	3/4"*	2.72"	1.65"	.42 lb

IAPMO Listed to cUPC®

<sup>\* 3/4&</sup>quot; furnished in male threads only