



TSGB1624S


Snap-To-Stud Telescoping Box Support



TSGB1624S




1. Separate




2. Assemble

Standard width
stud




3a. Fold ends up
for 2-1/8" box
depth




4a. Snap to stud

nVent CADDY
SMS8




5a. Install single
screw per side
(required)


Wider than standard
width stud



3b. Fold 1st
end up for
2-1/8" box
depth




4b. Fold 2nd
end up for
wider than
standard stud



5b. Position to wider
than standard stud

nVent CADDY
SMS8



6. Install single
screw per side
(required)

WARNING:

1. nVent products shall be installed and used only as indicated in nVent product instruction sheets and training materials. Instruction sheets are available at www.nVent.com and from your nVent customer service representative.
2. nVent products must never be used for a purpose other than the purpose for which they were designed or in a manner that exceeds specified load ratings.
3. All instructions must be completely followed to ensure proper and safe installation and performance.
4. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and/or death, and void your warranty.
5. Products that are manufactured using spring steel components shall be used only in a non-corrosive indoor environment.
6. All pipe supports, hangers, intermediate components and structural attachments must ONLY be used as described herein and are NEVER to be used for any other purpose.

NOTE: All load ratings are for static conditions and do not account for dynamic loading such as wind, water or seismic loads, unless otherwise noted.

The customer is responsible for:

- a. Conformance to all governing codes.
- b. The integrity of structures to which the products are attached, including their capability of safely accepting the loads imposed, as evaluated by a qualified engineer.
- c. Using appropriate industry standard hardware as noted above.

SAFETY INSTRUCTIONS:

All governing codes and regulations and those required by the job site must be observed. Always use appropriate safety equipment such as eye protection, hard hat, and gloves as appropriate to the application.


nVent, nVent CADDY, nVent ERICO Cadweld, nVent ERICO Critec, nVent ERICO, nVent ERIFLEX, and nVent LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

TECHNICAL SUPPORT:
www.nVent.com



CFS559_C

1 OF 2


© 2017-2019 nVent All Rights Reserved




Bends for 1-1/2" deep box




TSGB1624S




1. Separate




2. Assemble



3. Fold snap-on end back




4. Bend forward across 1-1/2" bend line (see top image)




Retaining Tab

5. Fold retaining tab to secure


Example Applications



Single/Multiple Box



Conduit Support



Pipe Support