











1/2" VSR DRILLS

1/2" (12.7 mm) VSR Mid-Handle Grip Drill with VSR Mid Handle Drill **Keyless Chuck**

1/2" (12.7 mm) Keyed

1/2" (12.7 mm) VSR **Pistol Grip Drill**

1/2" (12.7 mm) VSR Drill with Keyless Chuck

1/2" (12.7 mm) VSR Drill

1/2" (12.7 mm) VSR Drill

SPECIFICATIONS	DWD215G	DWD216G	DWD210G	DW246	DW245	DW235G
Chuck Size	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Amps	10 Amps	10.5 Amps	10 Amps	7.8 Amps	7.8 Amps	7.8 Amps
No Load Speed	0 - 1,200 rpm	0 - 1,200 rpm	0 - 1,200 rpm	0 - 600 rpm	0 - 600 rpm	0 - 850 rpm
Max Watts Out	980 W	1100 W	980 W	600 W	600 W	600 W
Keyless Chuck	Yes	No	No	Yes	No	No
Capacity In Wood (Spade Bit)	1-1/2"	1-1/2"	1-1/2"	1-1/2"	1-1/2"	1-1/2"
Capacity In Wood (Auger Bit)	1-1/2"	1-1/2"	1-1/2"	1-1/2"	1-1/2"	1-1/8"
Capacity In Steel (Twist Bit)	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Capacity In Steel (Hole Saw)	2"	2"	2"	2-3/4"	2-3/4"	1-1/2"
Tool Weight	5.2 lbs	5.2 lbs	4.9 lbs	4.4 lbs	4.4 lbs	4.2 lbs
Includes	360° locking side handle	360° locking side handle	360° locking side handle and chuck key with holder	360° side handle	360° side handle and chuck key with holder	360° side handle and chuck key with holder

DWD460



Multi-Position Adjustable Bail Handle Provides maximum leverage and control

Improved Chuck Jaws Protects flat shank bits and holds them more securely



0-330 / 0-1, 300 rpm

To match rpm / torque

variety of applications

requirements to a

Gear Casing & Handle Provides additional comfort

Variable Speed Trigger Gives user increased control when starting a hole



Bind-Up Control® System Stall sensing technology that provides increased user control

Knuckle Guard Provides increased hand protection



1/2" (12.7 mm) VSR Pistol Grip Drill with E-Clutch™ **Anti-Lock Control**

SPECIFICATIONS	DWD220
Chuck Size	1/2"
Amps	10.5 Amps
No Load Speed	0 - 1,200 rpm
Max Watts Out	1100 W
Keyless Chuck	No
E-Clutch	Yes
Capacity In Wood (Spade Bit)	1-1/2"
Capacity In Wood (Auger Bit)	1-1/2"
Capacity In Steel (Twist Bit)	1/2"
Capacity In Steel (Hole Saw)	2"
Tool Weight	4.9 lbs
Includes	360° side handle and chuck key with holder









handle and chuck key

with holder









1/2" (12.7 mm) VSR Stud & Joist Drill w/ Clutch and Bind-Up Control® System Bind-Up Control® System

handle and chuck key

with holder

1/2" (12.7 mm) VSR Stud & Joist Drill w/ Clutch and

1/2" (12.7 mm) Right 1/2" (12.7 mm) Stud & Angle Drill Kit Joist Drill

1/2" (12.7 mm) Spade 1/2" (12.7 mm) End **Handle Drill** Handle Drill

SPECIFICATIONS	DWD460/K*	DWD450/K*	DW124/K*	DW120K	DW130V	DW140
31 EUII IUATIUNS						
Chuck Size	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Amps	11 Amps	11 Amps	11.5 Amps	7.0 Amps	9.0 Amps	7.0 Amps
No Load Speed	0-330 / 0-1,300 rpm	0-330 / 0-1,300 rpm	300 / 1,200 rpm	400 / 600 / 900 rpm	0 - 550 rpm	600 rpm
Max Watts Out	1015 W	1100 W	850 W	580 W	600 W	580 W
Kit Box	No/Yes	No/Yes	No/Yes	Yes	No	No
Mechanical Clutch	Yes and Bind-Up Control® System	Yes and Bind-Up Control® System	Yes	No	No	No
Capacity In Wood (Aug	er Bit) 1-1/2"	1-1/2"	1-1/2"	1-1/2"	1-1/2"	1-1/2"
Capacity In Steel (Twis	st Bit) 1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Capacity In Steel (Hole	Saw) 5"	5"	5"	5"	3"	1-1/2"
Tool Weight	11.7 lbs	11.2 lbs	13.5 lbs	9.7 lbs	7.5 lbs	7.0 lbs
Includes	2-position side handle, bail	2-position side handle, bail 2	2-position side handle,	5-position side handle, allen	3-position side handle,	3-position side handle

bail handle and chuck

key with holder

wrench and chuck key 2-position rear spade handle

and chuck key with holder

with holder

^{* (}K) Includes Kitbox