



CONNECTIONS

- L - LOW SPEED
- C - COMMON
- H - HIGH SPD
- 5 - BLACK, 2 - RED

MODEL		REF.	CUSTOMER	HP.	VOLTS	AMPS	HZ.	R.P.M.	ROTATION	CAT. NO.
C63CXSSH-4583			STANDARD	1.0/1/3	115	12.4/6.1	60	1725/1140	REVERSIBLE	CAT. NO. 2574
PAGE 1		REVISION RECORD FOR: E.C.O. 203503			INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF EMERSON ELECTRIC COMPANY.					
OF 1		AUTOMATIC THERMAL PROTECTOR ADDED.								
REVISION DATE		NOTE FOR CONNECTIONS, AND DIMENSION FOR SHAFT KEY WAY ADDED.								
27AP00		CUSTOMER, H.P., APMS AND CAT. NO. ADDED.			ALL DIMENSIONS ARE FOR REFERENCE ONLY UNLESS TOLERANCE IS GIVEN.				CUST. PT. NO.	
ISSUED BY	REVIEWED BY	ENGINEER APPROVED	TITLE		CODE	ITEM NO.	SIZE			
S. MAYORGA	V. LOREDO	T. BOSSALLER	ASSEMBLED VIEW		VO1	301568	A			