

# Adapters

In the over 100 years Elkhart has been a fire service manufacturer, we have created a wide assortment of standardized adapters to meet the varied needs of the fire industry. This extensive selection includes thread adapters to suit any need — whether for a male to female; a suction adapter with built-in strainer, NHT, NPT or custom order; or even for a universal adapter — you can find the perfect fit here.

- A selection of rocker lug and pin lug options
- Aluminum, Brass, and Chrome finishes available

Adapter  
Mo. M-327



High Rise Elbow  
Mo. 105A



Several material options — lightweight Elk-O-Lite® or durable cast brass (including some with chrome-plated finish)

# ADAPTERS, CAPS & PLUGS



## HOSE TO HOSE ADAPTERS

# ADAPTERS, CAPS & PLUGS

11-3

What kind of adapter do you need?																						
Step 1: Select Material	Step 2: Choose Connection Type  (Inlet to Outlet)	Step 3: Determine Gender  (Inlet to Outlet)	Step 4: Select from available options														Step 5: Pick Model					
			Inlet	Size (Inches)										Constru- tion		Type				Model	Figure	
				1	1.5	2	2.5	3	3.5	4	4.5	5	6	Solid	Swivel	Hex	Internal Lug	Long Handle	Rocker			
Brass	Hose Thread to Hose Thread	NHT (M) to NHT (F)	1	•											•				s	A-327	9	
			1.5		•										•					s	D-327	8
			1.5	•		•									•					s	A-327*	9
			1.5			•									•		s			s	S-327	11
			2												•					s	A-327	9
			2.5	•		•	•								•					s	S-327	11
			2.5			•	•								•		s			s	105	3
			2.5			•	•								•					s	A-327	9
			3			•	•								•					s	S-327	11
			3			•	•								•		s			s	105	3
		3			•	•								•					s	A-327	9	
		3			•	•								•		s			s	S-327	11	
		3			•	•								•					s	105	3	
		3.5						•						•					s	A-327	9	
		3.5												•					s	D-327	8	
		3.5												•					s	A-327*	9	
		NHT (F) to NHT (M)	2.5	•		•										•				s	S-327	11
			2.5			•	•								•					s	105	3
			2.5			•	•								•		s			s	A-327	9
			2.5			•	•								•					s	S-327	11
3				•	•								•					s	105	3		
3				•	•								•		s			s	A-327	9		
3				•	•								•					s	S-327	11		
3				•	•								•					s	105	3		
3.5								•					•					s	A-327	9		
3.5													•					s	D-327	8		
NHT (M) to NHT (M)	1.5		•											•				s	M-327	6		
	2.5			•										•				s				
	1.5		•											•				s	F-327	1		
	2.5			•										•				s	F-327	1		
	3				•									•				s	S-319	3		
	4.5									•	•	•				s						
Aluminum	Hose Thread to Hose Thread	NHT (M) to NHT (F)	1.5			•								•				s	D-327A	7		
			1.5		•		•							•				s	A-327A	10		
		2.5			•									•				s	A-327A	10		
		2.5			•		•							•				s	D-327A	7		
		2.5			•									•				s	M-327A	4		
		2.5			•		•							•				s	M-327ABI	5		
		2.5			•									•				s	F-327A	2		
		1.5		•										•				s				
		2.5			•									•				s				

Key s = standard o = option

\* A327 has optional pin lug and chrome finish in the 2.5F by 1.5M/1.5M by 2.5F size.

### OPTIONS THREADS

NHT can also be called NST. See T-13 for optional threads.

### MEASUREMENTS

Length measurements shown on page T-15.

### UNIVERSAL ADAPTER



435










- Cast brass construction with chrome-plated finish
- Adapts any 2.5" hose thread to 2.5" NHT
- Positive ratchet lock with thumb release
- Weight: 6.42 lbs.

	FEMALE/FEMALE	MALE/MALE	MIXED
<b>Figure 1</b>	 <p><b>F-327</b></p> <ul style="list-style-type: none"> <li>• Double swivel female</li> <li>• Cast brass finish (chrome optional)</li> </ul> <p><i>Fig. 1</i></p>	 <p><b>M-327A</b></p> <ul style="list-style-type: none"> <li>• Double male</li> </ul> <p><i>Fig. 4</i></p>	 <p><b>D-327A</b></p> <ul style="list-style-type: none"> <li>• Direct connect adapter</li> </ul> <p><i>Fig. 7</i></p>
<b>Figure 2</b>	 <p><b>F-327A</b></p> <ul style="list-style-type: none"> <li>• Double swivel female</li> </ul> <p><i>Fig. 2</i></p>	 <p><b>M-327ABI</b></p> <ul style="list-style-type: none"> <li>• Double male British Instantaneous</li> </ul> <p><i>Fig. 5</i></p>	 <p><b>D-327</b></p> <ul style="list-style-type: none"> <li>• Direct connect adapter</li> <li>• Chrome finish (cast brass optional)</li> </ul> <p><i>Fig. 8</i></p>
<b>Figure 3</b>	 <p><b>105</b></p> <ul style="list-style-type: none"> <li>• 45° discharge elbow</li> <li>• Female rocker lug</li> <li>• Chrome finish</li> </ul> <p><i>Fig. 3</i></p>	 <p><b>M-327</b></p> <ul style="list-style-type: none"> <li>• Double male</li> <li>• Cast brass finish (chrome optional)</li> </ul> <p><i>Fig. 6</i></p>	 <p><b>A-327</b></p> <ul style="list-style-type: none"> <li>• Female rocker lug</li> </ul> <p><i>Fig. 9</i></p>
<p><b>ADDITIONAL INFORMATION</b></p> <p><i>When ordering, specify: model number; inlet size, gender, and thread; outlet size, gender, and thread; as well as any optional type or finish information.</i></p>			
<p><b>105A High Rise Elbow</b></p> <ul style="list-style-type: none"> <li>• 45° drain elbow</li> <li>• 2.5" Female free swivel</li> <li>• 2.5" Male discharge</li> <li>• Integrated Model 114 drain valve</li> <li>• 250 GPM flow</li> <li>• 200 PSI operating pressure</li> <li>• 1 lb. 3 oz.</li> </ul> 			
<b>Figure 10</b>			 <p><b>A-327A</b></p> <ul style="list-style-type: none"> <li>• Female rocker lug</li> </ul> <p><i>Fig. 10</i></p>
<b>Figure 11</b>			 <p><b>S-327</b></p> <ul style="list-style-type: none"> <li>• Internal lug body</li> <li>• External female rocker lug</li> <li>• Cast brass finish (chrome optional)</li> </ul> <p><i>Fig. 11</i></p>



# ADAPTERS, CAPS & PLUGS

## HOSE TO PIPE / PIPE TO HOSE ADAPTERS

	FEMALE/FEMALE	MALE/MALE	MIXED
<b>Figure 14</b>	 <p><b>160</b></p> <ul style="list-style-type: none"> <li>• Swivel female to female</li> <li>• Cast brass finish (chrome optional)</li> </ul> <p><i>Fig. 14</i></p>	 <p><b>306</b></p> <ul style="list-style-type: none"> <li>• Double male</li> <li>• Cast brass finish (chrome optional)</li> </ul> <p><i>Fig. 17</i></p>	 <p><b>307</b></p> <ul style="list-style-type: none"> <li>• Cast brass finish (chrome optional)</li> </ul> <p><i>Fig. 18</i></p>
<b>Figure 15</b>	 <p><b>3060</b></p> <ul style="list-style-type: none"> <li>• Double female</li> <li>• Cast brass finish (chrome optional)</li> </ul> <p><i>Fig. 15</i></p>		 <p><b>418</b></p> <ul style="list-style-type: none"> <li>• Suction adapter</li> <li>• Removable strainer</li> <li>• Chrome finish</li> </ul> <p><i>Fig. 19</i></p>
<b>Figure 16</b>	 <p><b>419</b></p> <ul style="list-style-type: none"> <li>• Swivel female to female suction adapter</li> <li>• Built-in strainer</li> <li>• Chrome finish</li> </ul> <p><i>Fig. 16</i></p>		 <p><b>418-L</b></p> <ul style="list-style-type: none"> <li>• Long discharge adapter</li> <li>• Chrome finish</li> </ul> <p><i>Fig. 20</i></p>
			 <p><b>418-S</b></p> <ul style="list-style-type: none"> <li>• Short discharge adapter</li> <li>• Chrome finish</li> </ul> <p><i>Fig. 21</i></p>
			 <p><b>418-SA</b></p> <ul style="list-style-type: none"> <li>• Short discharge adapter</li> <li>• Female rocker lug</li> </ul> <p><i>Fig. 22</i></p>

### ADDITIONAL INFORMATION

*When ordering, specify: model number; inlet size, gender and thread; outlet size, gender and thread; as well as any optional type or finish information.*