




Position	Count	Description	Unit price
	-1	<p data-bbox="354 338 516 359"><b>15 SQE15-290</b></p> <div data-bbox="354 369 732 703" style="border: 1px solid black; padding: 5px;">  </div> <p data-bbox="737 674 1232 699">Product photo could vary from the actual product</p> <p data-bbox="354 732 862 898">Product No.: 96160195                      3" multi-stage, submersible pump designed for domestic water supply, liquid transfer in tanks, irrigation and environmental applications. The pump has "floating" impellers, each with its own tungsten carbide/ceramic bearing.</p> <p data-bbox="354 932 846 1014">The pump features soft starting and protection against dry-running, upthrust, overvoltage, undervoltage, overload and overtemperature.</p> <p data-bbox="354 1047 886 1186">The motor is a one-phase motor of the permanent magnet rotor type ensuring optimum efficiency within a wide load range.                      The motor is fitted with a replaceable cable plug.</p> <p data-bbox="354 1220 821 1329">Liquid:                      Maximum liquid temperature: 95 °F                      Max liquid temperature at 0.15 m/sec: 95 °F                      Density: 62.4 lb/ft³</p> <p data-bbox="354 1362 854 1530"><b>Technical:</b>                      Speed for pump data: 10700 rpm                      Rated flow: 13.2 US gpm                      Rated head: 371 ft                      Approvals on nameplate: UL, cUL                      Approvals on motor nameplate: CE,UL,CUL</p> <p data-bbox="354 1564 1027 1732"><b>Materials:</b>                      Pump: Polyethylene / Stainless steel                      DIN W.-Nr. 1.4301                      Motor: Stainless steel                      DIN W.-Nr. 1.4301                      AISI 304</p> <p data-bbox="354 1766 821 1848"><b>Installation:</b>                      Pump outlet: NPT 1 1/4                      Minimum borehole diameter: 2.99 in</p>	On request

Position	Count	Description	Unit price
		<p><b>Electrical data:</b></p> <p>Motor type: MSE3</p> <p>Power input - P1: 2.54 kW</p> <p>Rated power - P2: 2.48 HP</p> <p>Main frequency: 60 Hz</p> <p>Rated voltage: 1 x 200-240 V</p> <p>Start. method: direct-on-line</p> <p>Service factor: 1,65</p> <p>Rated current: 12.3 A</p> <p>Power factor: 1,00</p> <p>Rated speed: 10700 rpm</p> <p>Enclosure class (IEC 34-5): 58</p> <p>Insulation class (IEC 85): F</p> <p>Length of cable: 4.92 ft</p>	